

RATCLIFFE'S UNDERLAYS

Stanley Mill, Shackleton Street, Burnley, Lancashire. BB10 3BH

Tel: 01282 421026 Fax: 01282 412321 Email: ratcliffe2002@gmail.com www.foxirugtamer.co.uk

P & R Ratcliffe (Underlays) Ltd

Data Sheet

SN8 Felt ~ All Widths

Construction

Recycled Jute & Other Fibres Needled to a Polythene membrane

Fibre Composition

approx. 50% Natural Jute Fibres, 50% Recycled Wool / Nylon Fibres

Weight

 $320g / m^2 + / - 10\%$

Options

Black Polythene, width from 3.5" upwards, length 24' or 72'

Health & Safety Advice

Jute fibres can cause irritation to exposed skin, particularly forearms. We advise that persons using this product wear adequate forearm protection to avoid the risk of irritation.

Dust particles from the jute can cause nasal irritation, but there we know of no known health hazards associated with such exposure. Operatives may prefer to wear dust masks, but we don't consider this generally necessary.

SN8 passes the flooring test for flammability BS4790, with a low radius of effects of ignition. Simply this means that SN8 is not highly flammable, but it will burn if exposed to an existing fire. Normal fire prevention measures should be taken when using SN8 and we strongly recommend its use is restricted to no-smoking environments.

Please contact us for any further information.

Data prepared by Peter Ratcliffe, Director, P&R Ratcliffe (Underlays) Ltd.

Current as of 12 December 2019

12/13

Needlefelts

FoxiFix Combination Underlays