| | | | | Application | | | Bag Details | | |
|-------------|-----------------|--|--|-----------------|----------------|------------------------|--------------------------|--------------------|---|
| | | | | Bedding Coat | Finish Coat | Patching and Repair | Drying Time | Sizes available | Coverage |
| Powdered | Air-drying | KHAUF PRATICIONAD ADMISSIVE | Knauf Plasterboard Adhesive A multi-purpose gypsum-based adhesive used to direct bond Knauf Plasterboards and Knauf Insulating Laminates to masonry surfaces. | X | X | √ | 2-3h | 25kg | 4.6m² (dot and dab) |
| | | | Wickes Reinforcing Joint Tape For Plasterboards White paper tape for reinforcing joints by hand or machine application. Use with either powdered or ready-mixed jointing products. | 1 | X | J | - | Per roll | 150m |
| Powdered | Accelerated Set | FILE FINISH 60 PREMIUM PREMIUM Language and press of the second of the | Knauf Fill & Finish 60 Premium A fast setting multi-purpose gypsum-based compound for bedding tapes and beads as well as finishing. 60 minutes working time. | √ | √ | ✓ | 60min working time | 10kg | 45m² |
| | | KNAUF JOINT FILLER PREMIUM | Knauf Joint Filler Premium A fast-setting gypsum compound for bedding joints by hand application. 90 minutes working time. | 1 | X | √ | 90min working time | 10kg | 55m² |
| Ready-mixed | Air-drying | FILL & FINISH FILL & FINISH FILL & FINISH FROM FOR THE PROPERTY OF THE PROP | Knauf Fill & Finish Light Lightweight ready-mixed compound for bedding tapes and finishing joints in drywall partitions and cellings. | √ | 1 | √ | 12-24h | 5kg | 11.25m² |
| | | Facy Pichia | Knauf Easy Plaster Lightweight patching plaster specially designed for small to large repairs to cracks in walls and ceilings. It will not shrink or crack. | × | 1 | √ | 24h | 2.5l 6l | 1.88m² @6mm thick 4.5m² @6mm thick |
| | | PROROLL The state of the state | Knauf ProRoll Light Roller applied plaster. Use as a finish on Knauf ProRoll Max or onto plasterboard backgrounds for a superior finish. | X | 1 | √ | 24h @ 1mm | 12.5kg | 10m² @1mm thick |
| | | PROROLL Supply of a feat. | Knauf ProRoll Max Roller applied plaster. Use to level the surface of existing internal walls and ceilings. Ideal for covering textured backgrounds. Use with Knauf ProRoll Light for a superior finish. | X | 1 | J | 24h @ 1mm | 13.5kg | 10m² @1mm thick |

. . .