DECLARATION OF PERFORMANCE

No. FB104-CPR-24-04-2018

Unique identification code of the

product-type:

Setcrete Exterior

Intended use/es:

Repair mortar (PCC) for non-structural repair of concrete structures with low performance requirements in buildings and

civil engineering works; Principle 3 (CR), Method 3.1

Manufacturer:

F. Ball and Co. Ltd., Churnetside Business Park, Station Road,

SETCRETE

Cheddleton, Leek, Staffordshire, ST13 7RS, UK

Tel: +44 (0) 1538 361 633

Fax: +44 (0) 1538 361 622

Email: contact@setcrete.co.uk

System/s of AVCP: System 4, Reaction to fire: System 4

Harmonised standard: EN 1504-3:2005

Notified body/ies: No tasks require the intervention of notified bodies

Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	Class R2 ≥ 15 MPa	EN 1504-3:2005
Chloride ion content	≤ 0,05%	EN 1504-3:2005
Adhesive bond	≥ 0,8 MPa	EN 1504-3:2005
Thermal compatibility, Part 1: Freeze-thaw	≥ 0,8 MPa	EN 1504-3:2005
Slip/ skid resistance	Class III ≥ 55 wet	EN 1504-3:2005
Capillary absorption	≤ 0,5 kg.m ⁻² .h ^{-0.5}	EN 1504-3:2005
Reaction to fire	F	EN 13501-1:2007+A1:2009
Dangerous substances	comply with 5.4	EN 1504-3:2005

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mr Stuart Whiteley

At Leek on 14 September 2018







