

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 15

SDS No.: 558122

V003.1 Revision: 24.08.2022

printing date: 16.04.2023

Replaces version from: 27.04.2021

UniBond Bath EasySmooth BLANCO

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

UniBond Bath EasySmooth BLANCO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealants

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +

+44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word: Warning

Hazard statement: H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement: P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statement: P273 Avoid release to the environment.

Prevention P280 Wear eye protection.

Precautionary statement: P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

Response contact lenses, if present and easy to do. Continue rinsing.

Precautionary statement:

Disposal

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration >= 0.1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

octamethylcyclotetrasiloxane	PBT/vPvB
556-67-2	

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Alcohols, C11-14-iso-, C13-rich, ethoxylated 78330-21-9	1- < 3 %	Aquatic Chronic 3, H412 Acute Tox. 4, Oral, H302 Eye Dam. 1, H318		
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	0,1-< 1 %	Carc. 2, Inhalation, H351		
octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36	0,025-< 0,25 % (0,25 %o- < 2,5 %o)	Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226	M chronic = 10	SVHC PBT/vPvB

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities Keep container tightly sealed. Store in a cool, dry place.

Temperatures between +5 °C and +25 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Joint sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

ngredient [Regulated substance] ppm		mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list	
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL	
Calcium carbonate 471-34-1 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL	
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL	
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL	

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Calcium carbonate		4	Time Weighted Average		IR_OEL
471-34-1			(TWA):		
[CALCIUM CARBONATE]					

Calcium carbonate 471-34-1 [CALCIUM CARBONATE]	10	Time Weighted Average (TWA):	IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]	4	Time Weighted Average (TWA):	IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]	10	Time Weighted Average (TWA):	IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE]	4	Time Weighted Average (TWA):	IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE]	10	Time Weighted Average (TWA):	IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]	4	Time Weighted Average (TWA):	IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]	10	Time Weighted Average (TWA):	IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]	10	Time Weighted Average (TWA):	IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]	4	Time Weighted Average (TWA):	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value			Remarks	
			mg/l	ppm	mg/kg	others	
Titanium dioxide 13463-67-7	Predator						no potential for bioaccumulation
Octamethylcyclotetrasiloxane 556-67-2	aqua (freshwater)		0,0015 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	aqua (marine water)		0,00015 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	sewage treatment plant (STP)		10 mg/l				
Octamethylcyclotetrasiloxane 556-67-2	sediment (freshwater)				3 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	sediment (marine water)				0,3 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	oral				41 mg/kg		
Octamethylcyclotetrasiloxane 556-67-2	Soil				0,54 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application	Route of	Health Effect	Exposure	Value	Remarks
Titanium dioxide 13463-67-7	Workers	Exposure inhalation	Long term exposure - local effects	Time	10 mg/m3	no potential for bioaccumulation
Titanium dioxide 13463-67-7	General population	oral	Long term exposure - systemic effects		700 mg/kg	no potential for bioaccumulation
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - systemic effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - local effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - systemic effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - local effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Long term exposure - systemic effects		3,7 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. material thickness > 0.1 mm

Perforation time > 30 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state solid
Delivery form solid

Colour varied, according to coloration

Odor characteristic Melting point $0 \,^{\circ}\text{C} \, (32 \,^{\circ}\text{F})$

Solidification temperature Not applicable, Product is a solid.

Initial boiling point 100 °C (212 °F)

Flammability

Explosive limits

Not applicable, Product is a solid.

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen

conditions of use

10 - 11,4

pH 10 (20 °C (68 °F); Conc.: 100 %)

Viscosity (kinematic)

Not applicable, Product is a solid.

Flow cup viscosity

10 min no method

Flow cup viscosity 10 min no method 10 m

Solubility (qualitative) Partially miscible

(20 °C (68 °F); Solvent: Water)
Partition coefficient: n-octanol/water

Not applicable

Vapour pressure 23 hPa $(20 \,^{\circ}\text{C } (68 \,^{\circ}\text{F}))$

Density 1,324 g/cm3 Density of pasty masses (immersion weighing

 $(20 \, ^{\circ}\text{C} \, (68 \, ^{\circ}\text{F}))$ method)

Relative vapour density:

Particle characteristics

Not applicable, Product is a solid.

Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Titanium dioxide	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down
13463-67-7				Procedure)
octamethylcyclotetrasilox	LD50	> 4.800 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
ane				Toxicity)
556-67-2				

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Titanium dioxide	LD50	> 10.000 mg/kg	rabbit	not specified
13463-67-7				
octamethylcyclotetrasilox	LD50	> 2.375 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
ane				Dermal Toxicity)
556-67-2				

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Titanium dioxide	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
13463-67-7						
octamethylcyclotetrasilox	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
ane						Inhalation Toxicity)
556-67-2						

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Titanium dioxide	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
13463-67-7				
octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute
ane				Dermal Irritation / Corrosion)
556-67-2				

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Titanium dioxide	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
13463-67-7				
octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
ane				Irritation / Corrosion)
556-67-2				

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
Titanium dioxide	not sensitising	Mouse local lymphnode	mouse	equivalent or similar to OECD Guideline
13463-67-7		assay (LLNA)		429 (Skin Sensitisation: Local Lymph
				Node Assay)
Titanium dioxide	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
13463-67-7				
octamethylcyclotetrasilox	not sensitising	Guinea pig maximisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
ane		test		
556-67-2				

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
octamethylcyclotetrasilox ane 556-67-2	negative	bacterial gene mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
octamethylcyclotetrasilox ane 556-67-2	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
octamethylcyclotetrasilox ane 556-67-2	negative	inhalation		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide	not carcinogenic	oral: feed	103 w	rat	male/female	not specified
13463-67-7			daily			

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
Titanium dioxide	NOAEL P \geq 1.000 mg/kg	one-	oral: feed	rat	OECD Guideline 443
13463-67-7		generation			(Extended One-Generation
	NOAEL F1 $>= 1.000 \text{ mg/kg}$	study			Reproductive Toxicity
					Study)
octamethylcyclotetrasilox	NOAEL P 300 ppm	two-	inhalation	rat	equivalent or similar to
ane		generation			OECD Guideline 416 (Two-
556-67-2	NOAEL F1 300 ppm	study			Generation Reproduction
					Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Route of	Exposure time /	Species	Method
CAS-No.		application	Frequency of		
			treatment		
Titanium dioxide	NOAEL > 1.000 mg/kg	oral: gavage	92 d	rat	OECD Guideline 408
13463-67-7			daily		(Repeated Dose 90-Day
					Oral Toxicity in Rodents)
octamethylcyclotetrasilox	LOAEL 35 ppm	inhalation	6 h nose only	rat	OECD Guideline 412
ane			inhalation		(Repeated Dose
556-67-2			5 days/week for 13		Inhalation Toxicity:
			weeks		28/14-Day)
octamethylcyclotetrasilox	NOAEL 960 mg/kg	dermal	3 w	rabbit	equivalent or similar to
ane			5 d/w		OECD Guideline 410
556-67-2					(Repeated Dose Dermal
					Toxicity: 21/28-Day
					Study)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Titanium dioxide	LC50	Toxicity > Water	48 h	Leuciscus idus	OECD Guideline 203 (Fish,
13463-67-7		solubility			Acute Toxicity Test)
octamethylcyclotetrasiloxane	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name:	EPA OPPTS 797.1600 (Fish
556-67-2				Oncorhynchus mykiss)	Early Life Stage Toxicity
					Test)
octamethylcyclotetrasiloxane	LC50	Toxicity > Water	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish
556-67-2		solubility			Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Titanium dioxide	EC50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202
13463-67-7		solubility			(Daphnia sp. Acute
					Immobilisation Test)
octamethylcyclotetrasiloxane	EC50	Toxicity > Water	48 h	Daphnia magna	EPA OTS 797.1300
556-67-2		solubility			(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater
					Daphnids)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Titanium dioxide	NOEC	Toxicity > Water	21 d	Daphnia magna	OECD Guideline 202
13463-67-7		solubility			(Daphnia sp. Chronic
					Immobilisation Test)
octamethylcyclotetrasiloxane	NOEC	7.9 µg/l	21 d	Daphnia magna	EPA OTS 797.1330
556-67-2					(Daphnid Chronic Toxicity
					Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
octamethylcyclotetrasiloxane 556-67-2	EC10	0,022 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	3 h	activated sludge	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Alcohols, C11-14-iso-, C13-rich, ethoxylated 78330-21-9	readily biodegradable				
octamethylcyclotetrasiloxane 556-67-2	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

12.3. Bioaccumulative potential

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)				
octamethylcyclotetrasiloxane	12.400	28 d		Pimephales	EPA OTS 797.1520 (Fish
556-67-2				promelas	Bioconcentration Test-Rainbow
					Trout)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
octamethylcyclotetrasiloxane	6,98	21,7 °C	other guideline:
556-67-2			

12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB	
CAS-No.		
Titanium dioxide	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not	
13463-67-7	be conducted for inorganic substances.	
octamethylcyclotetrasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very	
556-67-2	Bioaccumulative (vPvB) criteria.	

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080409

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content 0,0 %

(VOCV 814.018 VOC regulation

CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.