









ROBUST BITUMINOUS CORRUGATED ROOF SHEET

FOR PROFESSIONALS

www.onduline.co.uk

Onduline Lightweight roofing systems







ONDULINE® DURO SX 35



Premium quality bituminous corrugated sheet with industrial aesthetics for a professional finish



Technical characteristics



Length	L	200 cm
Width		82 cm
Thickness		3.5 mm
Height of corrugation	Н	38 mm
Pitch of corrugation	Р	96 mm
Product surface		1.64 m ²
Weight of product		5.9 kg
Weight per product surface		3.62 kg/m²
Corrugations / Flat sections		6/5

Accessories

For complete waterproofing for 20-years, ONDULINE DURO SX 35 can be fitted with a range of complementary accessories and fixings:



For maximum ventilation, **ONDUTISS** membranes are the recommended air permeable membrane to use with DURO SX 35 for all timber build structures.



A number of accessories and fixings are available to colour match the full range of **ONDULINE DURO SX 35** sheets:

- Ridges
 - Verges

See the full range of accessories at www.onduline.co.uk

Colour range



Intense **Anthracite Grey**









Forest Green

Onduline Building Products Ltd

Dawson House Jewry Street London | EC3N 2EX enquiries@onduline.net +44 (0)207 727 0533