



Benefits

- Easy to use and install
- High efficiency
- Integrated JB4 distributor ports

Key Features

- Depth of 16mm
- Available as 6W/15W/30W
- 2m mains cable included
- Short circuit & overload protection
- Surge and thermal protection

Product Overview

Measuring at only 16mm in depth, the low-profile driver is a discreet solution that can be hidden away easily during installation.

The driver features integrated JB4 ports rather than a traditional distribution block, which streamlines the design and reduces unnecessary parts and materials.

Protected from short-circuiting, overloading and electrical surge, the driver is a safe solution ideal for many applications.

Technical Specification

Drivers	6W	15W	30W
Rated Input Voltage (Vac)	220-240	220-240	220-240
Input Voltage Range (Vac)	198-264	198-264	198-264
Frequency (Hz)	50/60 ± 3%	50/60 ± 3%	50/60 ± 3%
Output Voltage (V)	24 ± 5%	24 ± 5%	24 ± 5%
Output Current (A)	0.250	0.625	1.25
Short Circuit Protection	Yes	Yes	Yes
Overload Protection	Yes	Yes	Yes
Thermal Protection	Yes	Yes	Yes
Surge Protection	Yes	Yes	Yes
Operating Temperature	-20°C to +40°C	-20°C to +40°C	-20°C to +40°C
Humidity	10% to 90%RH	10% to 90%RH	10% to 90%RH
Mains Cable Length (M)	2	2	2
Number of JB4 Ports	4	6	6

Mechanical Specification

Product	Dimensions (mm) L x W x D	Weight (grams)	IP Rating
Titan – 6W Drivers	95 x 48 x 16.5	52	20
Titan – 15W Drivers	120 x 48 x 16.5	68	20
Titan – 30W Drivers	158 x 56 x 16.5	116	20

Order Codes

Description	Order Code	Barcode	Carton (QTY)
Titan – 6W	SE490950	5060522083641	50
Titan – 6W (With Plug)	SE487950	5060522083955	50
Titan – 15W	SE491950	5060522083665	50
Titan – 15W (With Plug)	SE488950	5060522083962	50
Titan – 30W	SE492950	5060522083672	50
Titan – 30W (With Plug)	SE489950	5060522083979	50