

HDB95623NB



Gas and induction cooking options right at your fingertips

There's no need to choose between gas and induction heating anymore! This hob gives you the benefits of both, with gas as well as induction cooking zones.

Product Benefits & Features



Your perfect cooking partner

Induction helps you master any cooking technique faster. It heats quicker than other types of hob – it even boils water in under 90 seconds* – so you can get on with your cooking straight away. And the heat adjustments are so subtle that they help you produce the finest tastes and textures every

- · Hob type: Mixed with induction
- Touch-control
- · Rotary knob controls
- · Controls position: Front Left & Right
- Illuminated controls
- · Digital indications for each zone
- Induction zones with power booster function
- Left front zone: Induction, 1800W/2800W/180mm
 Left rear zone: Induction, 1800W/2800W/180mm
- Middle front zone: No, 000W/00mm
- Middle rear zone: No, 000W/00mm
- Right front zone: Semi Rapid Burner, Vertical flame, 1900W/78mm
 Right rear zone: Ultra Rapid Burner, Vertical flame, 2700W/124mm
 Stop and Go function for short interruptions
- Key-lock function
- · Child safety lock function
- Acoustic signal
- Timer function
- OptiHeat Control
- Easy installation thanks to snap-in system
- · Main colour: Black



HDB95623NB

Product Specification		
Product Installation	Built_In	Fastening
Product Typology	Mixed_Hob	Gas origin
Product Classification	Exploration	Gas repla
Installation	Independent	ous replic
Size	90	Gas repla
Hob type	Induction Mix	Gas cate
Design family	AEG	Frequenc
Main colour	Black	Voltage
Control Panel material	Glass	Required
Frame type	No	Cord leng
Frame material	No	
Knobs colour	Black	
Top Control Place	Front Left & Right	
Type of controls	Knobs 9 Steps Power	
Control function	3 step residual heat, Acoustic signal, Booster, Bridge function, Child-lock, Flexible Powermanagement, Key-lock function, Minute minder, Pot detection, Stop+go function, Timer	
Width mm	880	
Depth mm	520	
Built in height mm	47	
Width cutting	830	
Depth cutting	490	
Radius cutting	No	

Fastening	Snap in System	
Gas original	G25.3 (2EK) 25 mbar	
Gas replacement 2	G30/G31 (3B/P) 30/30 mbar, With Additional Injectors	
Gas replacement 3	G20 (2E) 20 mbar, with additional injectors	
Gas category	II2EK3B/P, II2L3B/P	
Frequency	50	
Voltage	220-240V/400V2N	
Required fuse (A)	No	
Cord length external	1.5	

