High density
PU foam
underlay
perfect for
heavy duty
domestic use

■ High Density...hardwearing

The polyurethane foam in PowerWalk is extra high density (130kg/m³) so it's extremely hardwearing, keeping your carpet looking good for longer.

■ Performance under pressure

Under pressure, this is an underlay that really performs – able to spring back much better than a typical sponge rubber product – to help your carpet keep that 'just-fitted' look.

■ Keeps flooring in its place

PowerWalk Gold has excellent stability to stop movement in your carpet, greatly reducing wear and tear!

Technical Data		
Properties	Value	Test Method
Thickness	11mm ±0.5mm	
Roll Size	$11m \times 1.37m = 15.07m^2$	
Roll Weight	21.5kg ±5%	
Density	130 kg/m³ ±5%	
BS5808: 1991 Classification	L/U Luxury Use	BS5808: 1991 (2011)
Thermal Resistance	2.92 tog	BS 4745: 2005
Flammability (hot metal nut test)	Pass - low radius of effect	BS 4790:1987 (2009)
Impact Sound Reduction	44 dB	BS EN ISO 717-2:2013 BS EN ISO 10140-3:2010
Guarantee	Lifetime of carpet	
Loss in Thickness after dynamic loading (1000 impacts)	3.4%	BS5808: 1991 (2011)
Loss in thickness after Static Loading (24 hours recovery)	6.5%	BS5808: 1991 (2011)

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive Liverpool L24 8RL Tel: 0151 495 3434

Fax: 0151 427 0484

Email: sales@qaflooringsolutions.com www.qaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Heavy Traffic

Carpet





Best for

Cushioning

Moisture Protection Sound Reduction

Level Floors Compression Recovery

Underfloor Heating

Hard Wearing Heat Insulation Commercia Use*

*Suitable for hotels and public buildings

Available in

Code	QAU-PWG-01	
Size	1.37m x 11m (15.07m ²)	
Thickness	11mm	