Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

SAFETY DATA SHEET

Date of issue/Date of revision

: 3 January 2018



: 1

Version

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: WICKES QUICK DRYING FLOOR VARNISH GLOSS
Product code	: 17100RUR034
Other means of identification	: Not available.

1.2 Relevant identified us	es of the substance	or i	mixtu	re a	nd	uses	adv	/ise	d agains	t
	•			_	-					

Product use	: Consumer applications, Professional applications.
Use of the substance/ mixture	: Coating.

1.3 Details of the supplier of the safety data sheet

PPG Architectural Coatings UK Ltd Huddersfield Road Birstall, West Yorkshire WF179XA United Kingdom Tel: +44 (0) 1924 354000 Fax: +44 (0) 1924 354533

- e-mail address of person : regulatoryaffairs@ppg.com responsible for this SDS
- 1.4 Emergency telephone number Supplier

Telephone number :

+44 (0) 1924 354000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word

: No signal word.

Hazard statements

: No known significant effects or critical hazards.

Precautionary statements

Code	: 17100RUR034	Date of issue/Date of revision	: 3 January
WICKES QU	IICK DRYING FLOOR VARNISH GLOS	S	

SECTION 2: Hazards identification

General	: Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable. P102, P101
Hazardous ingredients	: Not applicable.
Supplemental label elements	: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Other hazards which do	: None known.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures :	Mixture			
Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
propane-1,2-diol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≥1.0 - ≤5.0	Not classified.	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code	: 17100RUR034	Date of issue/Date of revision	: 3 January 2018
WICKES QUI	CK DRYING FLOOR VARNISH GLOS	S	

SECTION 4: First aid measures

4.1 Description of first aid measures			
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.		
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. 		
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. 		
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.		

4.2 Most important symptoms and effects, both acute and delayed Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	mptoms
Eye contact	: No specific data.
Inhalation	: No specific data.

Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising fro	m	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon oxides
5.3 Advice for firefighters		
Special precautions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

: 17100RUR034

Date of issue/Date of revision

: 3 January 2018

WICKES QUICK DRYING FLOOR VARNISH GLOSS

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
---	---	---

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	teo	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	coi	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	•	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Code : 17100RUR034

Date of issue/Date of revision

: 3 January 2018

WICKES QUICK DRYING FLOOR VARNISH GLOSS

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities	:	Storage temperature: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate
		containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient	name	Exposure limit values
propane-1,2-diol		EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 10 mg/m ³ 8 hours. Form: Particulate TWA: 150 ppm 8 hours. Form: Sum of vapour and particulates TWA: 474 mg/m ³ 8 hours. Form: Sum of vapour and particulates
Recommended monitoring : procedures	atmosphere or of the ventilation protective equip the following: E the assessmen limit values and atmospheres - exposure to che (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness in or other control measures and/or the necessity to use respiratory oment. Reference should be made to monitoring standards, such as European Standard EN 689 (Workplace atmospheres - Guidance for t of exposure by inhalation to chemical agents for comparison with I measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment of emical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be

DNELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
propane-1,2-diol	DNEL	Long term Inhalation	168 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	10 mg/m³	Workers	Local
	DNEL	Long term Inhalation	50 mg/m³	Consumers	Systemic
	DNEL	Long term Inhalation	10 mg/m³	Consumers	Local

PNECs

: 17100RUR034

Date of issue/Date of revision

: 3 January 2018

WICKES QUICK DRYING FLOOR VARNISH GLOSS

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
propane-1,2-diol	-	Fresh water	260 mg/l	Assessment Factors
	-	Marine water	26 mg/l	Assessment Factors
	-	Sewage Treatment Plant	20000 mg/l	Assessment Factors
	-	Fresh water sediment	572 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	57.2 mg/kg dwt	Equilibrium Partitioning
	-	Soil	50 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls		
Appropriate engineering controls	Good general ventilation should be sufficient to control worker exposure to airl contaminants.	oorne
Individual protection measu		
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clo Wash contaminated clothing before reusing. Ensure that eyewash stations an safety showers are close to the workstation location.	othing.
Eye/face protection	Safety glasses with side shields. Use eye protection according to EN 166.	
Skin protection		
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard s be worn at all times when handling chemical products if a risk assessment ind this is necessary.	
Gloves	For prolonged or repeated handling, use the following type of gloves:	
	Recommended: nitrile rubber	
Body protection	Personal protective equipment for the body should be selected based on the t being performed and the risks involved and should be approved by a specialis before handling this product.	
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should approved by a specialist before handling this product.	l be
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. I workers are exposed to concentrations above the exposure limit, they must us appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates necessary. Wear a respirator conforming to EN140. Filter type: organic vapor (Type A) and particulate filter P3	lf e this is
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to e they comply with the requirements of environmental protection legislation. In s cases, fume scrubbers, filters or engineering modifications to the process equi will be necessary to reduce emissions to acceptable levels.	some

Code : 17100RUR034

Date of issue/Date of revision

: 3 January 2018

WICKES QUICK DRYING FLOOR VARNISH GLOSS

SECTION 9: Physical and chemical properties

9.1 Information on basic physical	and chemical properties
<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Various
Odour	: Faint odour.
Odour threshold	: Not available.
рН	: 8
Melting point/freezing point	: May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -4.78°C (23.4°F)
Initial boiling point and boiling range	: >37.78°C
Flash point	: Closed cup: Not applicable. [Product does not sustain combustion.]
Evaporation rate	: 0.01 (propane-1,2-diol) compared with butyl acetate
Material supports combustion.	: No.
Flammability (solid, gas)	: liquid
Upper/lower flammability or explosive limits	: Not applicable.
Vapour pressure	 Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.92 kPa (21.9 mm Hg) (at 20°C)
Vapour density	: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 4.77 (Air = 1)
Relative density	: 1.02
Solubility(ies)	: Partially soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	: Not applicable.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
Viscosity	: Kinematic (40°C): >0.21 cm ² /s
Explosive properties	: Product does not present an explosion hazard.
Oxidising properties	: Product does not present an oxidizing hazard.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	 When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

Conforms to Regulation (EC)	Io. 1907/2006 (REACH), Annex II, as amended by Re	egulation (EU) No. 2015/830
Code : 17100RUR034 WICKES QUICK DRYING FLC	Date of issue/Date of revision OR VARNISH GLOSS	: 3 January 2018
SECTION 10: Stabilit	y and reactivity	
10.5 Incompatible materials	: Keep away from the following materials to prevent oxidising agents, strong alkalis, strong acids.	strong exothermic reactions:

10.6 Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propane-1,2-diol	LD50 Dermal LD50 Oral	Rabbit Rat	20800 mg/kg	-
		Rai	20 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value	
Inhalation (gases)	1510982.9 ppm	
Inhalation (vapours)	5616.7 mg/l	

	5
Irritation/Corrosion	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitisation	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Mutagenicity</u>	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxi	<u>city (single exposure)</u>
Not available.	
Specific target organ toxi	<u>city (repeated exposure)</u>
Not available.	
Aspiration hazard	
Not available.	
Information on likely	: Not available.
routes of exposure	
Potential acute health effe	ects
Inhalation	: No known significant effects or critical hazards.
	-

ode : 17100RUR03		Date of issue/Date of revision	: 3 January 2018
VICKES QUICK DRYING FL	OOR VARNISH (GLOSS	
SECTION 11: Toxico	ological info	ormation	
Ingestion	: No known s	significant effects or critical hazards.	
Skin contact	: No known s	significant effects or critical hazards.	
Eye contact	: No known s	significant effects or critical hazards.	
Symptoms related to the p	hysical, chemica	al and toxicological characteristics	
Inhalation	: No specific	data.	
Ingestion	: No specific	data.	
Skin contact	: No specific	data.	
Eye contact	: No specific	data.	
<u>Delayed and immediate eff</u>	ects as well as o	chronic effects from short and long-term	<u>n exposure</u>
Short term exposure			
Potential immediate effects	: Not availabl	le.	
Potential delayed effects	S: Not availabl	le.	
Long term exposure			
Potential immediate effects	: Not availabl	le.	
Potential delayed effects	s : Not availabl	le.	
Potential chronic health eff	<u>fects</u>		
Not available.			
Conclusion/Summary	: Not availabl	le.	
General	: No known s	significant effects or critical hazards.	
Carcinogenicity	: No known s	significant effects or critical hazards.	
Mutagenicity	: No known s	significant effects or critical hazards.	
Teratogenicity	: No known s	significant effects or critical hazards.	
Developmental effects	: No known s	significant effects or critical hazards.	
Fertility effects	: No known s	significant effects or critical hazards.	
Other information	: Not availabl	la	

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Code	: 17100RUR034	Date of issue/Date of revision

: 3 January 2018

WICKES QUICK DRYING FLOOR VARNISH GLOSS

SECTION 12: Ecological information

F	Product/ingredient name	LogPow	BCF	Potential
р	propane-1,2-diol	-0.92	-	low

-	1	2.4	Мо	bilit	y in	soil	
---	---	-----	----	-------	------	------	--

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment			
PBT	Not applica	able.	
vPvB	Not applica	able.	

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation		
08 01 12	01 12 waste paint and varnish other than those mentioned in 08 01 11		
Packaging Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Type of packaging	European waste catalogue (EWC)		

Container	15 01 04	metallic packaging
Special precautions	or liners may retain	s container must be disposed of in a safe way. Empty containers some product residues. Avoid dispersal of spilt material and vith soil, waterways, drains and sewers.

: 17100RUR034

Date of issue/Date of revision

: 3 January 2018

WICKES QUICK DRYING FLOOR VARNISH GLOSS

14. Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
ADN	: None identified.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not applicable.
according to Annex II of	
Marpol and the IBC Code	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

<u>Annex XIV</u>

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Ozone depleting substances (1005/2009/EU)

Not listed.

VOC for	Ready-for-Use
Mixture	

: IIA/i. One-pack performance coatings. EU limit values: 140g/l (2010.) This product contains a maximum of 80 g/l VOC.

Seveso Directive

: 17100RUR034

Date of issue/Date of revision

: 3 January 2018

WICKES QUICK DRYING FLOOR VARNISH GLOSS

SECTION 15: Regulatory information

This product is not controlled under the Seveso Directive.

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

- assessment
- , ,

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number PBT = Persistent, Bioaccumulative and Toxic vPvB = Very Persistent and Very Bioaccumulative ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway IMDG = International Maritime Dangerous Goods IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

Not applicable.

Full text of classifications [CLP/GHS]

Not applicable.

<u>History</u>	
Date of issue/ Date of revision	: 3 January 2018
Date of previous issue	: No previous validation
Prepared by	: EHS
Version	: 1

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.