

Uniclass L621 / CI/SfB / March 2014

/Yg2/

/

# TECHNICAL INFORMATION

# QUICKSET CONCRETE

Ready-to-use Quickset Concrete Product Data Sheet

Tarmac QUICKSET CONCRETE is a premixed, quick-setting concrete manufactured from cement, specially selected sand and admixtures. When sprinkled with water it sets in approximately 30 minutes.

# **GENERAL INFORMATION**

Tarmac QUICKSET CONCRETE can be used for paths, patios, slabs, paving and floors. It is premixed and ready to use, and only requires the addition of clean water. This product is manufactured to a third-party accredited BS EN 9001 Quality Management System.

### **PACKAGING AND COVERAGE**

Tarmac QUICKSET CONCRETE is available in weatherproof and tear-resistant plastic packaging.

1 bag will produce approximately 0.45 m² of concrete at a thickness of 25 mm.

### **WORKING TEMPERATURE**

Do not use at temperatures below 5°C or above 30°C without taking precautions to ensure that new work is protected from freezing or drying-out.





### **USE**

- Dampen the area to be repaired on concreted ensuring that there is no standing water
- The premixed concrete should be poured from the bag into the area to be concreted. The maximum recommended depth of concrete is 50 mm. Concrete naturally expands and contracts with changing temperatures, therefore to avoid cracking limit the area to be concreted to no more than 2 m<sup>2</sup>
- Level the dry concrete using a straight-edge or trowel
- Sprinkle with water using a fine rose until wet, using a maximum of 3 litres of water per m<sup>2</sup> (do not allow pools of water to form)
- Compact the concrete using a straight-edge or float
- Re-wet the concrete 2 hours after the first application of water (for indoor conditions or in dry weather, a further application of water after 12 hours may be appropriate)
- Newly-finished concrete should always be protected from drying-out by covering with polythene sheeting or wet hessian (sacking) for a minimum of 7 days
- Clean all tools and equipment immediately after use and before the material has set
- Tarmac QUICKSET CONCRETE sets in about 30 minutes.

# **STORAGE AND SHELF LIFE**

Tarmac QUICKSET CONCRETE is a cement-based material and should be handled and stored with care. Unopened bags can be stored in either outdoor or indoor conditions. Open bags should be stored in dry cool conditions protected from wind. Information on the maximum storage period (shelf life) of the product is shown on the bag. Normal manual handling procedures (Manual Handling Operations Regulations 1992) should be followed when unloading or moving bags.

# **AVAILABILITY**

Tarmac QUICKSET CONCRETE is available in large pack bags throughout Great Britain from Tarmac Cement stockists.



### **TECHNICAL SUPPORT**

Further information and advice on this product and the full range of Tarmac Cement products can be obtained through the contacts listed below.

# **RESPONSIBLE SOURCING**

This product has been externally assessed and awarded a 'Very Good' classification to the prestigious BES 6001, Responsible Sourcing Standard.

#### **HEALTH AND SAFETY**

Tarmac QUICKSET CONCRETE contains cement; contact between cement and body fluids may cause irritation, dermatitis or burns. For further information, including control of soluble hexavalent chromium, refer to the appropriate Tarmac Cement Health and Safety Information Sheet.



For futher information

Technical helpdesk

Tel: 0845 812 6232

E-mail info-cement@tarmac.com

Customer services & sales

Tel: 0845 812 6300

E-mail customerservice@tarmac.com

'Tarmac' and the 'circle logo' are registered trademarks. ©2015 Tarmac Trading Limited.

The information in this data sheet is accurate at the time of printing, but Tarmac reserves the right to amend details as part of its product development programme. The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.