



SAFETY DATA SHEET

Acrypol+ Colours

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Acrypol + Colours

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Coating for Roof Maintenance and Repair.

1.3. Details of the supplier of the safety data sheet

Supplier

Cromar Building Products, Units 3,4,5
 Northside Ind Park, Whitley Bridge, Goole,
 DN14 0GH
 t: +44 (0)1977 663 133
 f: +44 (0)1977 662 186
 sales@cromar.uk.com
 www.acrypolproducts.co.uk

1.4. Emergency telephone number

Emergency telephone +44 1977 663 133 (not 24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.
 EUH208 Contains alpha-[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4- hydroxyphenyl]-1-
 1-. May produce an allergic reaction.

Acrypol + Colours

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P240 Ground/ bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-methoxy-1-methylethyl acetate			30-60%
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01-2119475791-29-XXXX	

Classification

Flam. Liq. 3 - H226

Titanium Dioxide			10-30%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-XXXX	

Classification

Not Classified

POLYCAPROLACTAM; POLY[IMINO(1-OXO-1, 6-HEXANEDIYL)]			<1%
CAS number: 25038-54-4			

Classification

Not Classified

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	If in doubt, get medical attention promptly.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration.
Ingestion	Get medical attention immediately. Keep affected person warm and at rest. Do not induce vomiting.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Do not use organic solvents.
Eye contact	Wash with plenty of water.

Acrypol + Colours

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapour from this product may be hazardous by inhalation. May cause respiratory irritation. Prolonged or repeated exposure may cause the following adverse effects: Coughing. Vapours may cause drowsiness and dizziness.

Ingestion Pneumonia may be the result if vomited material containing solvents reaches the lungs. May be fatal if swallowed and enters airways.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Causes serious eye irritation. Prolonged or repeated exposure may cause the following adverse effects: Profuse watering of the eyes. Redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

Specific treatments No specific chemical antidote is known to be required after exposure to this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Fire-water run-off in sewers may create fire or explosion hazard. Harmful to aquatic life with long lasting effects. Control run-off water by containing and keeping it out of sewers and watercourses.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO). Acrid smoke or fumes. Metal oxide(s). Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting In case of fire: Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk into spilled material. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe gas, fume, vapours or spray. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Use protective equipment appropriate for surrounding materials.

Acrypol + Colours

For emergency responders Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Eliminate all sources of ignition. Use only in well-ventilated areas. For professional users only. Wear protective clothing as described in Section 8 of this safety data sheet. Earth container and transfer equipment to eliminate sparks from static electricity. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Use only non-sparking tools. Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and protective equipment before entering eating areas. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at temperatures between 10°C and 25°C. Store in accordance with national regulations. Store in tightly-closed, original container. Avoid contact with oxidising agents.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

2-methoxy-1-methylethyl acetate

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m³

Sk

Titanium Dioxide

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

POLYCAPROLACTAM; POLY[IMINO(1-OXO-1, 6-HEXANEDIYL)]

Long-term exposure limit (8-hour TWA): 10 mg/m³ 3 mg/m³ dust

Short-term exposure limit (15-minute): 15 mg/m³ 5 mg/m³ dust

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Acrypol + Colours

2-methoxy-1-methylethyl acetate (CAS: 108-65-6)

DNEL	Industry - Dermal; Long term : 153.5 mg/kg/day Industry - Inhalation; Long term : 275 mg/m ³
PNEC	- Fresh water; 0.635 mg/l - Marine water; 0.0635 mg/l - Intermittent release; 6 mg/l - STP; 100 mg/l - Sediment (Freshwater); 3.29 mg/kg - Sediment (Marinewater); 0.329 mg/kg - Soil; 0.29 mg/kg

Titanium Dioxide (CAS: 13463-67-7)

DNEL	Workers - Inhalation; Long term local effects: 10 mg/m ³
PNEC	- Fresh water; 0.127 mg/l - Intermittent release; 0.61 mg/l - Marine water; 1 mg/l - Sediment (Freshwater); 1000 mg/kg - Sediment (Marinewater); 100 mg/kg - STP; 100 mg/l - Soil; 100 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Use explosion-proof ventilating equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. For exposure up to 8 hours, wear gloves made of the following material: Viton rubber (fluoro rubber). For exposure up to 4 hours, wear gloves made of the following material: Butyl rubber. Nitrile rubber. Neoprene. Polyvinyl alcohol (PVA).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for information on material and design requirements and test methods.

Acrypol + Colours

Hygiene measures	Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contaminated clothing and protective equipment before entering eating areas. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a full facepiece, supplied-air respirator.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Various colours.
Odour	Characteristic.
Flash point	23°C SCC (Setaflash closed cup).

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 420 g/l.
----------------------------------	---------------------------------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	------------------------------------------------------------------------------------------------

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---------------------------------------------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
-------------------------------------------	--------------------------------------------------------------------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition.
----------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Acids. Alkalis. Oxidising agents.
---------------------------	-------------------------------------------------------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Heating may generate the following products: Carbon monoxide (CO). Carbon dioxide (CO ₂). Nitrous gases (NO _x).
-----------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

SECTION 12: Ecological Information

Acrypol + Colours

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.
Disposal methods	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains.
Waste class	08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



Acrypol + Colours

14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Health and environmental listings	None of the ingredients are listed.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE = Acute Toxicity Estimate
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
Revision date	14/07/2020
Revision	3
SDS number	5727

Acrypol + Colours

Hazard statements in full	H226 Flammable liquid and vapour. EUH208 Contains alpha-[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4- hydroxyphenyl]-1-]. May produce an allergic reaction.
Component	Base
Shelf life	1 year
EU Dir 2	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.