

**Yale**<sup>®</sup>

## P-YWHLCK40N Replacement Window Handle Fitting Instructions

### Tools Required



Cross Head  
Screwdriver



Hacksaw

### Fitting Instructions

1. To remove your current window handle, turn the handle 90 degrees to expose the bottom fixing screw. Unscrew the fixing screw.
2. Take off the cover cap at the top of the window handle and unscrew the top fixing screw. The handle can now be removed.
3. The spindle and screws included with your new window handle may need to be cut down to fit your window lock. To check, place the new window handle into the same position as the old handle ensuring the spindle is fully pushed back into the lock.
4. If the handle sits flush against the window then you do not need to cut down the spindle or screws.
5. If the handle does not sit flush against the window then you will need to cut the spindle and fixing screws to size. Take your old window handle and measure the length of the spindle and fixing screws. The new spindle and screws need to be cut to this size using a hack saw.
6. Place the window handle back into position on the window. Screw the fixing screws in the bottom and top fixing holes and check the handle is fitted securely and operates correctly. To finish, stick the cover cap over the top fixing screw.

**Yale**<sup>®</sup>

**The world's favourite lock since 1843**

School Street, Willenhall, West Midlands WV13 3PW

[www.yale.co.uk](http://www.yale.co.uk) Tel: +44 (0) 1902 364647 E-mail: [info@yale.co.uk](mailto:info@yale.co.uk)

3188282001 Issue No: 01-2012

An ASSA ABLOY Group brand

**ASSA ABLOY**