



NO GROW™



**WEED INHIBITING DANSAND
FOR BEAUTIFUL PATIOS & DRIVES**



DANSAND® NO GROW™ NATURAL 20KG FOR NARROW JOINTS 1-5MM

DANSAND® NO GROW™ natural contains special organic minerals to inhibit weeds growing and the very high PH value makes it very difficult for new weeds to germinate. Requires a block height of at least 4cm and gap width of between 1-5mm.

Coverage: 20kg covers 5-10m²



DANSAND® NO GROW™ STONE DUST 20KG FOR BOTH PATIOS & DRIVEWAYS

DANSAND® Stone Dust consists of crushed granite from special rock which gives it a stylish dark colour. The joint filling material creates a very long lifespan compact joint and its unique composition makes it very difficult for new weeds to take hold. Requires a block height of at least 4cm and gap width of between 1-20mm.

Coverage: 20kg covers 2-10m²



DANSAND® NO GROW™ POLYMERIC 20KG FOR HARD JOINTS


DANSAND® NO GROW™ Polymeric is flexible joint filling sand which when moistened, then activates a binding agent to harden the joint to a depth of 1cm. It requires a block height of at least 4cm and also a joint width of between 3mm & 10mm.

Coverage: 20kg covers 5-10m²

DANSAND®



RENOVATIONS PROCESS



**CLEAN JOINTS
STEP 1**
⚠️IMPORTANT
Clean out the joints down to at least 40mm. Then use an environmentally approved weed killer.

Follow all of the manufacturers instructions for use.



**REMOVE WEEDS
STEP 2**
⚠️IMPORTANT
Completely remove weeds with an environmentally approved weedkiller before you start any work. **NO GROW™** will not eradicate existing weeds that have roots either in or underneath the joints. **NO GROW™** is not a weedkiller, it is a weed inhibitor.



**CLEAN SURFACE
STEP 3**
Clean off the surface with water as it will have been soiled from cleaning out the old joint filler. Leave the cleaned paving to completely dry out BEFORE filling with new **NO GROW™**.



**MIX NO GROW
STEP 4**
Mix the **NO GROW™** well before use. Sweep the **NO GROW™** into the joints using length-wise diagonal movements. Check there is enough **NO GROW™** in the joints by firmly pressing a utensil down into the filled area. The utensil should not sink.



**CLEAN WHOLE AREA
STEP 5**
When all of the joints are completely filled, clean the surface with a soft brush.

Maintenance:
Keep the joints clean, periodically top-up if required due to water and wind erosion.



AUTHORISED DANSAND IMPORTER & DISTRIBUTOR UK & IRELAND

active
products

ACTIVE PRODUCTS UK LTD

Barnston Warehouse, Chelmsford Road, Great Dunmow, Essex. CM6 1LP

T/ +44 (0) 1371 872842 www.active-products.co.uk www.dansand.co.uk