

SAFETY DATA SHEET
Wickes Quick Drying Ready Mixed Filler (Tube) - SKU 154900

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Wickes Quick Drying Ready Mixed Filler (Tube) - SKU 154900

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Dolomite (Substance with a workplace exposure limit) 60-100%

CAS number: 16389-88-1 EC number: 240-440-2

Classification

Not Classified

Limestone 5-10%

CAS number: 1317-65-3 EC number: 215-279-6

Classification

Not Classified

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

Wickes Quick Drying Ready Mixed Filler (Tube) - SKU 154900

SECTION 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Dolomite (Substance with a workplace exposure limit)

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Short-term exposure limit (15-minute): WEL 4 mg/m³ respirable dust

Limestone

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

1,2-benzisothiazol-3(2H)-one

No information on supplier MSDS and no information in HSE EH40/2005 Workplace Exposure Limits.

Pyrithione zinc

Long-term exposure limit (8-hour TWA):

According to the Suppliers MSDS this substance has no occupational exposure limit values.

WEL = Workplace Exposure Limit

Dolomite (Substance with a workplace exposure limit) (CAS: 16389-88-1)

DNEL The available hazard data does not support the need for any DNEL's

PNEC No data available from supplier MSDS or REACH Registration portal.

Limestone (CAS: 1317-65-3)

DNEL No data available from supplier MSDS or REACH Registration portal.

PNEC No data available from supplier MSDS or REACH Registration portal.

propan-2-ol (CAS: 67-63-0)

DNEL Industry - Dermal; Long term systemic effects: 888 mg/kg/day
Industry - Inhalation; Long term systemic effects: 500 mg/m³
Consumer - Dermal; Long term systemic effects: 319 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 89 mg/m³
Consumer - Oral; Long term systemic effects: 26 mg/kg/day

PNEC Industry - Fresh water; Long term 140.9 mg/l
Industry - Marine water; Long term 140.9 mg/l
Industry - Sediment; Long term 552 mg/kg
Industry - Soil; Long term 28 mg/kg
Industry - STP; Long term 2251 mg/l

1,2-benzisothiazol-3(2H)-one (CAS: 2634-33-5)

DNEL No data available from supplier of the substances.

PNEC No data available from the substance supplier.

Wickes Quick Drying Ready Mixed Filler (Tube) - SKU 154900

Pyrithione zinc (CAS: 13463-41-7)

DNEL	Data taken from the ECHA REACH Registration Portal. Industry - Dermal; Long term systemic effects: 0.01 mg/kg
PNEC	Data taken from the ECHA REACH Registration Portal. Industry - Fresh water; Long term 90 ng/l Industry - Marine water; Long term 90 ng/l Industry - STP; Long term 0.01 mg/l Industry - Sediment (Freshwater); Long term 0.0095 mg/kg - Sediment (Marinewater); Long term 0.0095 mg/kg - Soil; Long term 1.02 mg/kg

8.2. Exposure controls

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

SECTION 12: Ecological Information

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SECTION 14: Transport information

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

Wickes Quick Drying Ready Mixed Filler (Tube) - SKU 154900

SECTION 16: Other information

SDS number 5248