

# SAFETY INFORMATION

## MORTAR MIX ANNEX A

**Health and Safety Information** In accordance with Regulation (EC) No 1907/2006 (REACH) as amended by Regulation (EU) No 453/2010

Annex A: Exposure scenario for consumer (DIY) use of hydrated lime as a building or construction material

| Contents   |  | Page     |
|------------|--|----------|
| <b>A.1</b> | <b>Introduction</b>                                    | <b>2</b> |
| A.1.1      | Methodology used for occupational exposure assessment  | 2        |
| A.1.2      | Methodology used for environmental exposure assessment | 2        |
| <b>A.2</b> | <b>Exposure Scenario</b>                               | <b>2</b> |
| A.2.1      | Control of consumers exposure                          | 3        |
| A.2.2      | Control of environmental exposure                      | 4        |
| <b>A.3</b> | <b>Exposure estimation and reference to its source</b> | <b>4</b> |
| 3.1        | Post application exposure                              | 5        |
| 3.2        | Environmental exposure                                 | 5        |

### A.1 INTRODUCTION

The current document includes relevant occupational and environmental exposure scenarios (ES) for the production and use of calcium dihydroxide as required under the REACH Regulation (Regulation (EC) No 1907/2006). For the development of the ES the Regulation and the relevant REACH Guidance have been considered. For the description of the covered uses and processes, the "R.12 - Use descriptor system" guidance (Version: 2, March 2010, ECHA-2010-G-05-EN), for the description and implementation of risk management measures (RMM) the "R.13 - Risk management measures" guidance (Version: 1.1, May 2008), for the occupational exposure estimation the "R.14 - Occupational exposure estimation" guidance (Version: 2, May 2010, ECHA-2010-G-09-EN) and for the actual environmental exposure assessment the "R.16 - Environmental Exposure Assessment" (Version: 2, May 2010, ECHA-10-G-06-EN) was used.

### A.1.1 Methodology used for occupational exposure assessment

The environmental exposure scenarios only address the assessment at the local scale, including municipal sewage treatment plants (STPs) or industrial waste water treatment plants (WWTPs) when applicable, for industrial and professional uses as any effects that might occur is expected to take place on a local scale.

### A.1.2 Methodology used for environmental exposure assessment

By definition an ES has to describe under which conditions the substances, preparation or articles can be handled safely. In cases where neither measured data nor analogous data are available, exposure is assessed with the aid of a modelling tool. For consumers, the repeated dose DNEL for inhalation as well as the acute DNEL for inhalation are based on the respective recommendations of the Scientific Committee on Occupational Exposure Limits (SCOEL), being 1 mg/m<sup>3</sup> and 4 mg/m<sup>3</sup>, respectively. For inhalation exposure to powders the

data, derived from van Hemmen (van Hemmen, 1992: Agricultural pesticide exposure data bases for risk assessment. Rev Environ Contam Toxicol. 126: 1-85.), has been used to calculate the inhalation exposure. The inhalation exposure for consumers is estimated at 15 µg/hr or 0.25 µg/min. For larger tasks the inhalation exposure is expected to be higher. A factor of 10 is suggested when the product amount exceeds 2.5 kg, resulting in the inhalation exposure of 150 µg/hr. To convert these values in mg/m<sup>3</sup> a default value of 1.25 m<sup>3</sup>/hr for the breathing volume under light working conditions will be assumed (van Hemmen, 1992) giving 12 µg/m<sup>3</sup> for small tasks and 120 µg/m<sup>3</sup> for larger tasks. When the preparation or substance is applied in granular form or as tablets, reduced exposure to dust was assumed. To take this into account if data about particle size distribution and attrition of the granule are lacking, the model for powder formulations is used, assuming a reduction in dust formation by 10 % according to Becks and Falks (Manual for the authorisation of pesticides. Plant

protection products. Chapter 4 Human toxicology; risk operator, worker and bystander, version 1.0., 2006). For dermal exposure and exposure to the eye a qualitative approach has been followed, as no DNEL could be derived for this route due to the irritating properties of calcium oxide. Oral exposure was not assessed as this is not a foreseeable route of exposure regarding the uses addressed. Since the SCOEL recommendation refers to respirable dust while the exposure estimates by the model from van Hemmen reflect the inhalable fraction, an additional safety margin is inherently included in the exposure scenarios below, i.e. the exposure estimates are very conservative. The exposure assessment of calcium dihydroxide professional and industrial and consumer use is performed and organized based on several scenarios.

An overview of the scenarios and the coverage of substance life cycle is presented in Table 1.

| ES. Title                         | Consumer (DIY) use as a building and construction material |        |
|-----------------------------------|--|--------|
| <b>Identified uses</b>            | Manufacture  |        |
|                                   | Formulation  |        |
|                                   | End Use  |        |
|                                   | Consumer   | X      |
| <b>Resulting life cycle stage</b> | Service life of articles                                   |        |
|                                   | Linked to identified use                                   | 12     |
|                                   | Sector of use category SU                                  | 21     |
|                                   | Chemical Product Category (PC)                             | 9a, 9b |
|                                   | Process Category (PROC)                                    |        |
|                                   | Article Category (AC)                                      |        |
|                                   | Environmental release category (ERC)                       | 8      |

## A.2 Exposure Scenario

| 1. Consumer use as a building and construction material |   |
|---|---|
| <b>Free short title</b>                                 | Consumer use as building and construction material  |
| <b>Systematic title based on use descriptor</b>         | SU21, PC 9a, PC 9b, ERC 8c, ERC 8d, ERC 8e, ERC 8f  |
| <b>Processes tasks and activities covered</b>           | Handling (mixing and filling) of powder formulations<br>Application of liquid, pasty lime preparations.   |
| <b>Assessment method</b>                                | Human health<br>A qualitative assessment has been performed for oral and dermal exposure as well as exposure to the eye. Inhalation exposure to dust has been assessed by the Dutch model (van Hemmen, 1992).<br>Environment<br>A qualitative justification assessment is provided. |

| 2. Operational conditions and risk management measures |   |
|--|---|
| <b>RMM</b>   | No product integrated risk management measures are in place.  |
| <b>PC/ERC</b>  | Description of activity referring to chemical product categories (pc) and environmental release categories (ERC)  |
| <b>PC 9a, 9b</b>                                       | Mixing and loading of powder containing lime substances.<br>Application of lime plaster, putty or slurry to the walls or ceiling.<br>Post-application exposure.   |
| <b>ERC 8c, 8d, 8e, 8f</b>                              | Wide dispersive indoor use resulting in inclusion into or onto a matrix<br>Wide dispersive outdoor use of processing aids in open systems<br>Wide dispersive outdoor use of reactive substances in open systems<br>Wide dispersive outdoor use resulting in inclusion into or onto a matrix |

## 2.1 Control of consumers exposure

| Product characteristics                    |   |                                     |  |   |
|--|---|-------------------------------------|--|---|
| Description of the mixture                 | Concentration of the substance in the mixture (% by wt) | Physical State of the mixture       | Dustiness (if relevant)  | Packaging Design                          |
| Hydrated lime substance                    | 100   | Solid, powder                       | High, Medium or Low depending on the type of Hydrated lime substance | Bulk or in bags up to 35 kg               |
| Plaster / Mortar                           | 20 - 40   | Solid, powder                       |  | Weatherproof plastic bags or plastic tubs |
| Plaster / Mortar                           | 20 - 40   | Pasty                               | -  | -   |
| Putty, filler                              | 30 - 55   | Pasty, highly viscous, thick liquid | -  | In tubes or buckets                       |
| Pre-mixed lime wash paint                  | - 30  | Solid, powder                       | High - low   | Bulk or in bags up to 35 kg               |
| Lime wash paint / milk of lime preparation | - 30  | Milk of lime preparation            | -  | -   |

| Amounts used               |  |
|----------------------------|--|
| Description of the mixture | Amount used per event  |
| Filler, putty              | 250 g - 1 kg powder (2:1 powder water)<br>Difficult to determine, because the amount is heavily dependent on the depth and size of the holes to be filled. |
| Plaster / lime wash paint  | - 25 kg depending on the size of the room, wall to be treated.   |
| Floor / wall equalizer     | - 25 kg depending on the size of the room, wall to be treated.   |

| Frequency and duration of exposure                                   |                                |                     |
|--|--------------------------------|---------------------|
| Description of the mixture   | Duration of exposure per event | Frequency of events |
| Mixing and loading of lime containing powder.                        | 1.33 minutes                   | 2/year              |
| Application of lime plaster, putty or slurry to the walls or ceiling | Several minutes - hours        | 2/year              |

| Human factors not influenced by risk management           |                    |                                     |                    |  |
|---|--------------------|-------------------------------------|--------------------|--|
| Description of task                                       | Population exposed | Breathing rate (m <sup>3</sup> /hr) | Exposed body part  | Corresponding skin area (cm <sup>2</sup> ) |
| Handling of powder  | Adult              | 1.25                                | Half of both hands | 430  |
| Application of wet mortar/render containing hydrated lime | Adult              | NR                                  | Hands and forearms | 1900                                       |

| Other given operational conditions affecting consumer exposure |                |                               |                            |
|--|----------------|-------------------------------|----------------------------|
| Description of task  | Indoor/Outdoor | Room Volume (m <sup>3</sup> ) | Air exchange rate          |
| Handling powder  | Indoor         | 1 (personal space)            | 0.6hr-1 (unspecified room) |
| Application of wet mortar/render containing hydrated lime      | Outdoor        | NR                            | NR                         |

### Conditions and measures related to information and behavioural advice to consumers

In order to avoid health damage, DIYers should comply with the same strict protective measures which apply to professional workplaces:

- Change wet clothing, shoes and gloves immediately
- Protect uncovered areas of skin (arms, leg, face). There are various effective skin protection products which should be used in accordance with a skin protection plan (skin protection, cleansing and care). Cleanse the skin thoroughly after the work and apply a care product

### Conditions and measures related to personal protection and hygiene

In order to avoid health damage, DIYers should comply with the same strict protective measures which apply to professional workplaces:

- When preparing or mixing building materials, wear protective goggles as well as face masks during dusty work
- Choose work gloves carefully, Leather gloves can become wet and can facilitate burns. When working in a wet environment, cotton gloves with plastic covering (nitrile) are better. Wear gauntlet gloves during overhead work because they can considerably reduce the amount of humidity which permeates the working clothes

## 2.2 CONTROL OF ENVIRONMENTAL EXPOSURE

### Product characteristics

Not relevant for exposure assessment

### Amounts used

Not relevant for exposure assessment

### Frequency and duration of use

Not relevant for exposure assessment

### Environment factors not influenced by risk management

Default river flow and dilution

### Other given operational conditions affecting environmental exposure

Indoor

Direct discharge to the wastewater is avoided

### Conditions and measures related to municipal sewage treatment plant

Default size of municipal sewage system/treatment and sludge treatment technique

### Conditions and measures related to external treatment of waste for disposal

Not relevant for exposure assessment

### Conditions and measures related to external recovery of waste

Not relevant for exposure assessment

## 3. Exposure estimation and reference to its source

The risk characterisation ratio (RCR) is the quotient of the refined exposure estimate and the respective DNEL (derived no effect level) and is given in parentheses below. For inhalation exposure the RCR is based on the acute DNEL for lime substances if 4 mg/m<sup>3</sup> (as respirable dust) and the respective inhalation exposure estimate (as inhalable dust). Thus the RCR includes an additional safety margin since the respirable fraction is a sub-fraction of the inhalable fraction according to EN 481. Since limes are classified as irritating to skin and eyes, a qualitative assessment has been performed for dermal exposure and exposure to the eye.

| Human exposure     |  |   |
|--------------------|--|---|
| Handling of powder |  |   |
| Route of exposure  | Exposure estimate  | Method used, Comments   |
| Oral               | -  | Qualitative assessment<br>Oral exposure does not occur as part of intended product use  |
| Dermal             | Small task: 0.1 µg/cm <sup>2</sup> (-)<br>Large task: 1 µg/cm <sup>2</sup> (-)         | Qualitative assessment<br>If risk reduction measures are taken into account no human exposure is expected. However, dermal exposure to dust from loading of lime substances or direct contact to the lime cannot be excluded if no protective gloves are worn during application. This may occasionally result in mild irritation easily avoided by prompt rinsing with water<br>Quantitative assessment<br>The constant rate model of ConsExpo has been used |
| Eye                | Dust   | Qualitative assessment<br>If risk reduction measures are taken into account no human exposure is expected. Dust from loading of lime substances cannot be excluded if no protective goggles are used. Prompt rinsing with water and seeking medical advice after accidental exposure is advised.  |
| Inhalation         | Small task: 12 µg/cm <sup>2</sup> (0.003)<br>Large task: 120 µg/cm <sup>2</sup> (0.03) | Quantitative assessment<br>Dust formation while pouring the powder is addressed by using the Dutch Model (van Hemming, 1992)  |

| Application of liquid pasty lime mixture ( e.g. wet mortar/render containing hydrated lime) |                   |  |
|---|-------------------|--|
| Route of exposure   | Exposure estimate | Method used, Comments  |
| Oral  | -                 | Qualitative assessment<br>Oral exposure does not occur as part of intended product use   |
| Dermal  | Splashes          | Qualitative assessment<br>If appropriate goggles are worn no exposure to the eyes needs to be expected. However, splashes to the eyes cannot be excluded if no protective goggles are worn during application of liquid or pasty lime preparations, especially during overhead work. Prompt rinsing with water and seeking medical advice after accidental exposure is advised |
| Inhalation  | -                 | Qualitative assessment. Not expected as the vapour pressure of limes in water is low and generation of mists or aerosols does not take place   |

### 3.1 Post-application exposure

No relevant exposure will be assumed as the aqueous lime mixture will quickly convert to calcium carbonate with carbon dioxide from the atmosphere

### 3.2 Environmental exposure

Referring to the OC/RMM's related to the environment to avoid discharging lime solutions directly into municipal wastewater, the pH of the influent of a municipal wastewater treatment plant is circum-neutral and therefore, there is no exposure

to the biological activity. The influent of a municipal wastewater treatment plant is often neutralized anyway and lime may even be used beneficially for pH control of acid wastewater streams that are treated in biological WWTP's.

Since the pH of the influent of the municipal wastewater treatment plant is circum neutral, the pH impact is negligible on the receiving environmental compartments, such as surface water, sediment and terrestrial compartments.

The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.

#### DISCLAIMER:

This material safety data sheet (MSDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this MSDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this MSDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the MSDS supersedes all previous versions.

#### For further information

**Technical helpdesk**

**Tel: 0845 812 6232**

**E-mail [info-cement@tarmac.com](mailto:info-cement@tarmac.com)**

**Customer services & sales**

**Tel: 0845 812 6300**

**E-mail [customerservice@tarmac.com](mailto:customerservice@tarmac.com)**

\*Tarmac' and the 'circle logo' are registered trademarks. ©2015 Tarmac Trading Limited.