



SAFETY DATA SHEET

SETCRETE CONCRETE REPAIR MORTAR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SETCRETE CONCRETE REPAIR MORTAR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cementitious Grout/Mortar

Uses advised against None

1.3. Details of the supplier of the safety data sheet

Supplier

F.Ball and Co. Ltd.
 Churnetside Business Park,
 Station Road,
 Cheddleton,
 Leek,
 Staffordshire. ST13 7RS
 Tel: 01538 361633 Mon-Fri 8.30am-5.00pm (Exc Bank Holidays)
 Fax: 01538 361622
 E.mail: msds@f-ball.co.uk

1.4. Emergency telephone number

Emergency telephone 01538 361633 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Not Classified

Human health

Prolonged contact with moist or wet product may cause burns. When mixed with water or gauging liquid splashes may cause serious eye damage. This material contains a low level of soluble Chromium VI. A reducing agent has been added which will, when mixed, reduce the level of soluble Chromium (VI) to no more than 0.0002% (2ppm) of the total dry weight of cement providing the product is stored correctly as indicated in section 7, and used within the recommended shelf life for the product. Persons with a known sensitivity to Chromium VI would be advised not to use this product.

Environmental

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

Physicochemical

When handled correctly, undamaged units represent no danger.

2.2. Label elements

SETCRETE CONCRETE REPAIR MORTAR

Pictogram



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.
 P264 Wash contaminated skin thoroughly after handling.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P313 Get medical advice/ attention.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

CEMENT

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

CEMENT

10-30%

CAS number: 65997-15-1

EC number: 266-043-4

Classification

Skin Irrit. 2 - H315
 Eye Dam. 1 - H318
 Skin Sens. 1 - H317
 STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

Composition comments

A blend of cement, inert filler, polymer and additives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from source of contamination.

Inhalation

Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion

Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.

Skin contact

Remove contaminated clothing. Rinse immediately with plenty of water. Get medical attention if any discomfort continues.

Eye contact

Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

SETCRETE CONCRETE REPAIR MORTAR

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Irritation of nose, throat and airway.
Ingestion	May cause discomfort if swallowed.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is non-combustible.

5.2. Special hazards arising from the substance or mixture

Specific hazards Dust may form explosive mixture with air. No unusual fire or explosion hazards noted.

Hazardous combustion products Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters Wear chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of dust. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid generation and spreading of dust. Preferably remove spillage with a vacuum cleaner. Collect spillage in containers, seal securely and deliver for disposal as hazardous waste.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid handling which leads to dust formation. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep separate from food, feedstuffs, fertilisers and other sensitive material. The product must be stored under cover, in unopened bags clear of the ground in cool dry conditions, protected from frost and excessive draught.

SETCRETE CONCRETE REPAIR MORTAR

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³

Short-term exposure limit (15-minute): WEL

CALCIUM CARBONATE

Long-term exposure limit (8-hour TWA): WEL 10 total dust; 4 respirable dust mg/m³

CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 total dust ; 4 respirable dust mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

Ingredient comments The product may contain a low level of respirable crystalline silica (WEL 0.1 mg/m³; 8 hours TWA).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of dust. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Always check applicability with your supplier of protective equipment.

Eye/face protection

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Break through times can vary depending on thickness, use and source. Change gloves regularly.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station. Promptly remove any clothing that becomes wet or contaminated. Wash promptly if skin becomes contaminated.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. A half mask dust respirator approved to EN 149 : 2001 FFP2 is recommended. Ensure that the mask fits tightly to ensure an efficient seal.

Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	Grey.
Odour	Slight.

SETCRETE CONCRETE REPAIR MORTAR

Odour threshold	Not determined.
pH	pH (concentrated solution): High alkaline pH when mixed with water.
Melting point	Not determined.
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	Variable, depends on packing effects and temperature
Bulk density	Not determined.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	Not applicable.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not determined.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not applicable.
Comments	Information given is applicable to the product in its ready-to-use form.

9.2. Other information

Other information	None.
Refractive index	Not determined.
Particle size	Not determined.
Molecular weight	Not determined.
Volatility	Not applicable.
Saturation concentration	Not determined.
Critical temperature	Not determined.
Volatile organic compound	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

SETCRETE CONCRETE REPAIR MORTAR

Reactivity	There are no known reactivity hazards associated with this product.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures and when used as recommended.
10.3. Possibility of hazardous reactions	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4. Conditions to avoid	
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation. Avoid handling which leads to dust formation.
10.5. Incompatible materials	
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
10.6. Hazardous decomposition products	
Hazardous decomposition products	Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No information available.
Acute toxicity - oral	
Notes (oral LD₅₀)	No specific test data are available.
Acute toxicity - dermal	
Notes (dermal LD₅₀)	No specific test data are available.
Acute toxicity - inhalation	
Notes (inhalation LC₅₀)	No specific test data are available.
Skin corrosion/irritation	
Skin corrosion/irritation	Irritating to skin.
Animal data	No specific test data are available.
Human skin model test	No specific test data are available.
Extreme pH	No specific test data are available.
Serious eye damage/irritation	
Serious eye damage/irritation	Corrosivity to eyes is assumed.
Respiratory sensitisation	
Respiratory sensitisation	No specific test data are available.
Skin sensitisation	
Skin sensitisation	Sensitising.
Germ cell mutagenicity	
Genotoxicity - in vitro	Does not contain any substances known to be mutagenic.
Genotoxicity - in vivo	Does not contain any substances known to be mutagenic.
Carcinogenicity	

SETCRETE CONCRETE REPAIR MORTAR

Carcinogenicity	Does not contain any substances known to be carcinogenic.
IARC carcinogenicity	Not listed.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Does not contain any substances known to be toxic to reproduction.
Reproductive toxicity - development	Does not contain any substances known to be toxic to reproduction.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	A single exposure may cause the following adverse effects: Asthma, pulmonary sensitisation.
Target organs	Respiratory system, lungs
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
General information	
	Contains chromium (VI). May produce an allergic reaction.
Inhalation	Dust in high concentrations may irritate the respiratory system. The product may contain a small percentage of respirable crystalline silica. Prolonged exposure to dust may result in long term irreversible effects
Ingestion	Ingestion of small amounts is unlikely to cause a significant reaction. Larger doses may result in irritation to the gastro intestinal tract.
Skin contact	Prolonged or repeated contact with the powder or mixtures with water may cause burns and/or irritant contact dermatitis
Eye contact	Risk of serious damage to eyes.
Acute and chronic health hazards	Irritating to eyes. May cause skin sensitisation or allergic reactions in sensitive individuals.
Route of entry	Skin and/or eye contact
Target organs	Eyes Skin
Medical symptoms	Irritation of eyes and mucous membranes. Allergic rash.
Medical considerations	Pre-existing eye problems. Skin disorders and allergies.

SECTION 12: Ecological Information

Ecotoxicity	The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms.
<u>12.1. Toxicity</u>	
Toxicity	Not available
Acute toxicity - fish	Not determined
Acute toxicity - aquatic invertebrates	Not determined.
Acute toxicity - aquatic plants	Not determined.
Acute toxicity - microorganisms	Not determined.
Acute toxicity - terrestrial	Not determined.

SETCRETE CONCRETE REPAIR MORTAR

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Phototransformation Not determined.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not applicable.

12.4. Mobility in soil

Mobility The product is non-volatile.

Adsorption/desorption coefficient Not determined.

Henry's law constant Not determined.

Surface tension Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Small quantities may be mixed with water, allowed to cure fully and disposed of as low hazard waste. Larger quantities should be disposed of as hazardous waste via a licensed waste operator.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

SETCRETE CONCRETE REPAIR MORTAR

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).
Guidance	Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations.
Health and environmental listings	None of the ingredients are listed.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Technical Data Sheet
Key literature references and sources for data	Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits.
Revision comments	This is first issue.
Revision date	05/09/2018
Revision	1
SDS number	21000
SDS status	Approved.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.