CLARK-DRAIN
DRAINAGE & ACCESS SOLUTIONS

TECHNICAL DATA SHEET

www.clark-drain.com

CD-401-MESH - Linear Drainage


KEY FEATURES

- Includes 3 x CD 422/Mesh channel, 1 x CD 402 End caps(pair) and 1 x CD 403 Debris trap
- CE and UKAS marked and fully certified to BS EN 1433:2002
- Lightweight non-rusting design, manufactured from recycled polypropylene
- Heat resistant (ideal for tarmac edging)
- 'Springlock' channel-to-channel male/female connection allows several metres of channel to be laid at a time
- Provision for locking screws in grating (purchased separately)
- 10 point ‘snap-lock’ slotted grating; secure yet easy to remove for cleaning and maintenance
- Installation guide clearly marked on the inside of the channel
- Suitable for garage thresholds, patios, gardens and play areas
- Where water-tight Clark Drain channel is mandatory, a suitable mastic sealant such as Sikaflex (219i, 11FC) or Geocel (945, Marine) should be used when fitting channels together (and accessories)



CD-401-MESH - Specifications

Product Weight (Kg)	5.95
Channel Material	Recycled Polypropylene
Channel Length(mm)	1000
Channel Height(mm)	105 Internal 117 External
Grating Slot Dimensions(mm)	8 X 17/23
Waterway Area (cm2)	534
Grating Qty and size per channel(mm)	1 X 1000



MADE IN BRITAIN

CD401MESH/V0.1/22-11-2023

Due to our continuous product improvement program features and sizes may be subject to change without notice.

CLARK DRAIN, STATION ROAD, YAXLEY, PETERBOROUGH, PE7 3EQ, TEL. +44 (0) 1733 765317