

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021

Revision date 03-Mar-2021 Revision Number 2.05

This Safety Data Sheet is prepared voluntarily: it is not required according to Article 31 of Regulation (EC) No 1907/2006

\_\_\_\_\_

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product Name EVO-STIK FRAME SILICONE SEALANT WHITE

Pure substance/mixture Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

# 1.3. Details of the supplier of the safety data sheet

# **Company Name**

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

# 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650

+353 (1) 8624900 (Monday- Friday 9am-5pm)

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

## 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

## Signal word

None

# **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

## **EU Specific Hazard Statements**

EUH210 - Safety data sheet available on request

# Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

#### 2.3. Other hazards

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021 Revision Number 2.05

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

Not applicable

# 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	932-078-5	1	10 - <20	Asp. Tox. 1 (H304)		01-2119552497- 29-xxxx
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <5	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215- 52-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	Carc. 2 (H351i)		01-2119489379- 17-XXXX
Methyl alcohol	200-659-6	67-56-1	0.1 - <1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	01-2119392409- 28-XXXX
Orthophosphoric acid	231-633-2	7664-38-2	0.1 - <1	Acute Tox. 4 (H302) Skin Corr. 1B (H314) Met. Corr. 1 (H290)	Eye Irrit. 2 :: 10%<=C<25% Skin Corr. 1B :: C>=25% Skin Irrit. 2 :: 10%<=C<25%	01-2119485924- 24-xxxx

# Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance. If medical advice is needed,

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021

have product container or label at hand.

**Inhalation** Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Revision date 03-Mar-2021

Revision Number 2.05

**Skin contact** Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

**Ingestion** Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when

the product is exposed to moisture or water. Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon oxides. Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon dioxide. Thermal

decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021 **Revision Number** 2.05

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

Do not eat, drink or smoke when using this product. Wash hands before breaks and after General hygiene considerations

work. Take off all contaminated clothing and wash it before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

## Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released

upon curing

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>	TWA: 260 mg/m <sup>3</sup>	TWA: 266 mg/m <sup>3</sup>
	*	STEL: 600 ppm	STEL: 250 ppm
		STEL: 780 mg/m <sup>3</sup>	STEL: 333 mg/m <sup>3</sup>
		Sk*	Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

#### **Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768-02-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Inhalation	27,6 mg/m³			
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d			

Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level	Safety factor

# **EVO-STIK FRAME SILICONE SEALANT WHITE**

Supercedes Date: 12-Feb-2021

Revision date 03-Mar-2021 Revision Number 2.05

		Transaction of the state of the	
		(DNEL)	
worker	Inhalation 10 mg/m <sup>3</sup>		
Long term			
Local health effects			
Methyl alcohol (67-56-1)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d	
Short term Systemic health effects worker	Inhalation	260 mg/m³	
Short term Local health effects worker	Inhalation	260 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	260 mg/m³	
Long term Local health effects worker	Inhalation	260 mg/m³	
Trimethoxyvinylsilane (2768 Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects	Inhalation	(DNEL) 18,9 mg/m³	
Long term Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	
Titanium dioxide (13463-67-7	7)		
Type			
	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Oral	Derived No Effect Level (DNEL) 700 mg/kg bw/d	Safety factor
Consumer	*	(DNEL)	Safety factor
Consumer Long term Systemic health effects  Methyl alcohol (67-56-1)	Oral	(DNEL) 700 mg/kg bw/d	
Consumer Long term Systemic health effects  Methyl alcohol (67-56-1) Type	Oral  Exposure route	(DNEL) 700 mg/kg bw/d  Derived No Effect Level (DNEL)	Safety factor  Safety factor
Consumer Long term Systemic health effects  Methyl alcohol (67-56-1) Type Consumer Short term	Oral	(DNEL) 700 mg/kg bw/d  Derived No Effect Level	
Consumer Long term Systemic health effects  Methyl alcohol (67-56-1) Type Consumer	Oral  Exposure route	(DNEL) 700 mg/kg bw/d  Derived No Effect Level (DNEL)	

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021 Revision Number 2.05

Consumer	Oral	8 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	50 mg/m <sup>3</sup>	
Long term			
Systemic health effects			
Consumer	Dermal	50 mg/kg bw/d	
Long term			
Systemic health effects			

**Predicted No Effect Concentration** No information available. **(PNEC)** 

Predicted No Effect Concentration (PNEC)				
Trimethoxyvinylsilane (2768-02-7)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.34 mg/l			
Marine water	0.034 mg/l			
Microorganisms in sewage treatment	110 mg/l			

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

#### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

**Skin and body protection** None under normal use conditions.

**Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Paste
Colour White

Odour No information available Odour threshold No information available

Property Values Remarks • Method

**pH** No data available Not applicable Insoluble in water

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Melting point / freezing point No data available 301 °C

Initial boiling point and boiling

Supercedes Date: 12-Feb-2021

range

100 °C

Flash point

**Evaporation rate** No data available **Flammability** Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

No data available Vapour pressure Relative vapour density No data available

Relative density 1.01

Immiscible in water Water solubility Solubility(ies) No data available **Partition coefficient** No data available

>200 °C **Autoignition temperature** 

No data available **Decomposition temperature** Kinematic viscosity 50 mm<sup>2</sup>/s Dynamic viscosity No data available No data available **Explosive properties** No data available **Oxidising properties** 

9.2. Other information

Solid content (%) No information available **VOC Content (%)** No information available **Liquid Density** No information available

# **SECTION 10: Stability and reactivity**

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Protect from moisture. Exposure to air or moisture over prolonged periods. Do not Conditions to avoid

freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon **Hazardous decomposition** 

Revision date 03-Mar-2021

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021 Revision Number 2.05

\_\_\_\_\_

**products** curing.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

## Information on likely routes of exposure

Product Information

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact**Based on available data, the classification criteria are not met.

**Ingestion** Based on available data, the classification criteria are not met.

# Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Numerical measures of toxicity

**Acute toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 37,818.90 mg/kg

 ATEmix (dermal)
 89,693.20 mg/kg

 ATEmix (inhalation-dust/mist)
 53.056 mg/l

 ATEmix (inhalation-vapour)
 155.76 mg/l

# Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C13-C23,	LD50 > 5000 mg/kg (Rattus)	LD50 > 2000 mg/kg	
n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	OECD 401	(Oryctolagus cuniculus) OECD 402	
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3360 μL/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
2768-02-7	(Rattus) OECD 401	cuniculus)	OECD TG 403
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus	=22500 ppm (Rattus) 8 h =
67-56-1		cuniculus)	64000 ppm (Rattus) 4 h
Orthophosphoric acid 7664-38-2	=1530 mg/kg (Rattus)	= 2740 mg/kg (Oryctolagus cuniculus)	>850 mg/m <sup>3</sup> (Rattus) 1 h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021

Revision date 03-Mar-2021 Revision Number 2.05

\_\_\_\_\_

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide	Carc. 2
13463-67-7	

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

11.2.2. Other information

Other adverse effects No information available.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity .

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	EL50 (72h) > 10 000 mg/L (Skeletonema costatum)	LL50 (96h) > 1028 mg/L (Scophthalmus maximus)	-	LL50 (48h) > > 3193 mg/l (Acartia tonsa)		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L	EC50 = 39000 mg/L 25 min	-		

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021 Revision Number 2.05

		(Pimephales promelas static)	EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min		
Orthophosphoric acid 7664-38-2	-	LC50: 3 - 3.5mg/L (96h, Gambusia affinis)	-	EC50: =4.6mg/L (12h, Daphnia magna)	

# 12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information				
Trimethoxyvinylsilane (2768-02-7)				
Method	Exposure time	Value	Results	
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily	
Biodegradability: Manometric			biodegradable	
Respirometry Test (TG 301 F)				

#### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## **Component Information**

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Trimethoxyvinylsilane 2768-02-7	1.1	-
Methyl alcohol 67-56-1	-0.77	10

# 12.4. Mobility in soil

Mobility in soil No information available.

# 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB. .

Chemical name	PBT and vPvB assessment	
Trimethoxyvinylsilane	The substance is not PBT / vPvB	
2768-02-7		
Titanium dioxide	The substance is not PBT / vPvB	
13463-67-7	PBT assessment does not apply	
Methyl alcohol	The substance is not PBT / vPvB	
67-56-1	PBT assessment does not apply	
	Further information relevant for the PBT assessment is	
	necessary	
Orthophosphoric acid	The substance is not PBT / vPvB	
7664-38-2	PBT assessment does not apply	

## 12.6. Other adverse effects

Other adverse effects No information available.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

Supercedes Date: 12-Feb-2021

\_\_\_\_\_\_

Waste from residues/unused Uncured product should be disposed of as hazardous waste. Dispose of

**products** contents/container in accordance with local, regional, national, and international

regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

#### **IMDG**

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
Not regulated
Not regulated
Not regulated

14.5 Marine pollutant NP14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Environmental hazardsNot applicable14.6Special ProvisionsNone

# Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

# Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

# **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Revision date 03-Mar-2021

#### **EVO-STIK FRAME SILICONE SEALANT WHITE**

Supercedes Date: 12-Feb-2021

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Methyl alcohol	67-56-1	69.
Dioctyltin oxide	870-08-6	20

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

# Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

# Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## **Persistent Organic Pollutants**

Not applicable

#### National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. Chemical Safety Assessment has been carried out for this mixture

# **SECTION 16: Other information**

#### Key or legend to abbreviations and acronyms used in the safety data sheet

# Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H290 - May be corrosive to metals

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H331 - Toxic if inhaled

H332 - Harmful if inhaled

H370 - Causes damage to organs

#### Legend

TWA (time-weighted average) **TWA STEL** STEL (Short Term Exposure Limit)

Ceiling Limit Value Ceiling Skin designation

**SVHC** Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

**EWC** European Waste Catalogue Revision date 03-Mar-2021

**EVO-STIK FRAME SILICONE SEALANT WHITE** 

•

\_\_\_\_\_

#### Key literature references and sources for data

No information available

Supercedes Date: 12-Feb-2021

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Mar-2021

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Revision date 03-Mar-2021