

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

Supercedes Date: 19-Oct-2020

Revision date 20-Oct-2021 Revision Number 2

\_\_\_

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK GLAZING SILICONE SEALANT CLEAR

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

## 1.3. Details of the supplier of the safety data sheet

Company Name
Bostik Limited
Common Rd
ST16 3EH
Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650

+353 (1) 8624900 (Monday- Friday 9am-5pm)

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

IChronic aquatic toxicity ICategory 3 - (H412)	Chronic aquatic toxicity	Category 3 - (H412)
------------------------------------------------	--------------------------	---------------------

## 2.2. Label elements

### Signal word

None

#### **Hazard statements**

H412 - Harmful to aquatic life with long lasting effects.

## **EU Specific Hazard Statements**

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no

United Kingdom - BE Page 1 / 11

Revision date 20-Oct-2021

**Revision Number** 2

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

Supercedes Date: 19-Oct-2020

substance considered to be very persistent nor very bioaccumulating (vPvB).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	40 - <80	Asp. Tox. 1 (H304)		01-2119827000- 58-XXXX
Triacetoxy(propyl)silane	241-816-9	17865-07-5	1- <2.5	Skin Corr. 1B (H314) (EUH071)		01-2119966899- 07-XXXX
4,5-dichloro-2-octyl-2H-i sothiazol-3-one [DCOIT]		64359-81-5	0.01 - <0.05	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) M=100 Aquatic Chronic 1 (H410) M=100 (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	-

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

**Inhalation** Remove to fresh air. If symptoms persist, call a doctor.

**Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

United Kingdom - BE Page 2 / 11

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

Supercedes Date: 19-Oct-2020

\_\_\_\_\_

**Skin contact** Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

**Ingestion** Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

Revision date 20-Oct-2021

**Revision Number** 2

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors**Treat symptomatically.

## **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

irritating and toxic gases and vapours.

5.3. Advice for firefighters

special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

United Kingdom - BE Page 3 / 11

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

·

\_\_\_

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Supercedes Date: 19-Oct-2020

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

Revision date 20-Oct-2021

**Revision Number** 2

### 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

#### 7.3. Specific end use(s)

### Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon

curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released

upon curing

Chemical name	European Union	United Kingdom
Acetic acid	TWA: 25 mg/m <sup>3</sup>	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m <sup>3</sup>
	STEL: 50 mg/m <sup>3</sup>	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m <sup>3</sup>

Derived No Effect Level (DNEL) No information available

**Predicted No Effect Concentration** No information available.

(PNEC)

8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

**Skin and body protection** None under normal use conditions.

**Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

United Kingdom - BE Page 4 / 11

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

Supercedes Date: 19-Oct-2020

\_\_\_\_\_

Revision date 20-Oct-2021

**Revision Number** 2

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state Solid Appearance Paste

ColourClear, colourlessOdourAcetic acid

Odour threshold No information available

Property Values Remarks • Method

pH No data available Not applicable Insoluble in water

pH (as aqueous solution)

Melting point / freezing point

Initial boiling point and boiling

No data available

No data available

range

Flash point > 100 °C
Evaporation rate No data available
Flammability Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data available

Relative density 0.94

Water solubility Product cures with moisture

Solubility(ies)

Partition coefficient

Autoignition temperature

Decomposition temperature

No data available
No data available
No data available

Kinematic viscosity > 21 mm²/s @ 40°C

Dynamic viscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Solid content (%) No information available

**VOC Content (%)** 

**Density** 0.94 g/cm<sup>3</sup>

## **SECTION 10: Stability and reactivity**

10.1. Reactivity

**Reactivity** Product cures with moisture.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

United Kingdom - BE Page 5 / 11

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

\_\_

Sensitivity to mechanical

Supercedes Date: 19-Oct-2020

impact

None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

Revision date 20-Oct-2021

**Revision Number** 2

sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

**Hazardous decomposition** 

products

None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information .

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. May cause sensitisation

in susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Numerical measures of toxicity

## **Acute toxicity**

### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 Inhalation(4h) >5266 MG/M3 (Rattus)
4,5-dichloro-2-octyl-2H-isothiaz ol-3-one [DCOIT] 64359-81-5	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h

United Kingdom - BE Page 6 / 11

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

Supercedes Date: 19-Oct-2020

Revision date 20-Oct-2021 Revision Number 2

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation The assessment of the result of testing was done in accordance with the guideline of the

Commission 92/69/EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal		6 days	Product score <=1
					Non-irritant

Serious eye damage/eye irritation

By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/ EEC.

Product Information						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
	Rabbit	eye		6 days	Product score <=1 Non-irritant	

Respiratory or skin sensitisation

May produce an allergic reaction. No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information					
Method	Species	Exposure route	Results		
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses		
Sensitisation			were observed		

**Germ cell mutagenicity**Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

## 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

## **SECTION 12: Ecological information**

United Kingdom - BE Page 7 / 11

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

Supercedes Date: 19-Oct-2020

Revision date 20-Oct-2021

**Revision Number** 2

\_\_\_\_\_

12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h)> 3193 mg/l (Acartia tonsa)		
Triacetoxy(propyl)silan e 17865-07-5	EC50 (72h): approx. 24 mg/l(Pseudokirc henriella subpicata)	LC50 (96h) = 108.89 mg/L	-	EC50 (48h) = 89.59 mg/L		
4,5-dichloro-2-octyl-2H- isothiazol-3-one [DCOIT] 64359-81-5	EC50 (72h) =0.025 mg/L Algae (Scenedesmus subspicatus)(OE CD 201)	• • •	-	EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202)	100	100

## 12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information					
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)					
Method	Exposure time	Value	Results		
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days		
Anaerobic Transformation in					
Aquatic Sediment Systems					

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## **Component Information**

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Triacetoxy(propyl)silane 17865-07-5	1.23	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one	4.4	13
[DCOIT]		
64359-81-5		

## 12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03%	The substance is not PBT / vPvB
aromatics	
RR-100252-4	

United Kingdom - BE Page 8 / 11

#### **EVO-STIK GLAZING SILICONE SEALANT CLEAR**

Triacetoxy(propyl)silane 17865-07-5	The substance is not PBT / vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	The substance is not PBT / vPvB

#### 12.6. Other adverse effects

Supercedes Date: 19-Oct-2020

Other adverse effects No information available.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

Waste from residues/unused

products

Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international

Revision date 20-Oct-2021

**Revision Number** 2

regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

## **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

## **IMDG**

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Maring application

14.5 Marine pollutant NP14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

## Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom - BE Page 9 / 11

## **EVO-STIK GLAZING SILICONE SEALANT CLEAR**

Supercedes Date: 19-Oct-2020

Revision date 20-Oct-2021 Revision Number 2

\_\_\_\_\_

**European Union** 

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

## **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

## National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

#### Key or legend to abbreviations and acronyms used in the safety data sheet

## Full text of H-Statements referred to under section 3

EUH071 - Corrosive to the respiratory tract

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

### Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

United Kingdom - BE Page 10 / 11

Revision date 20-Oct-2021

**Revision Number** 2

**EVO-STIK GLAZING SILICONE SEALANT CLEAR** 

\_\_\_\_\_

EWC European Waste Catalogue

### Key literature references and sources for data

No information available

Supercedes Date: 19-Oct-2020

Prepared By Product Safety & Regulatory Affairs

Revision date 20-Oct-2021

Indication of changes

**Revision note** SDS sections updated, 2, 3, 11, 12, 13, 15, 16.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 11 / 11