

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name CEMENTONE WATERSEAL
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Primers, Sealers, and Undercoaters.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

2.2. Label Elements

Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Petroleum distillates, hydrotreated light



Signal word
 DANGER

Hazard statements

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

H304 - May be fatal if swallowed and enters airways
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects
H226 - Flammable liquid and vapour

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe mist/vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P391 - Collect spillage
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public. This product requires child resistant fastenings if supplied to the general public. This product requires child resistant fastenings when supplied to the general public unless the product is placed on the market in the form of aerosols or in a container with a sealed spray attachment.

2.3. Other Hazards

No information available

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	--	80 - 100	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)		01-2119458049-33-XXXX
Petroleum distillates, hydrotreated light	265-149-8	64742-47-8	1 - <5	Asp. Tox. 1 (H304) (EUH066)		01-2119484819-18-XXXX

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

5.2. Special hazards arising from the substance or mixture

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Dyke far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

7.3. Specific end use(s)

Specific Use(s)

Primers, Sealers, and Undercoaters.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (--)

Type	Worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	330 mg/m ³

Type	Worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	44 mg/kg bw/d

Petroleum distillates, hydrotreated light (64742-47-8)

Derived No Effect Level (DNEL)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (--)

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	71 mg/m ³

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	26 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	26 mg/kg bw/d

Petroleum distillates, hydrotreated light (64742-47-8)

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	19 mg/kg bw/d

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Gloves made of plastic or rubber. Antistatic footwear. Wear fire/flamm resistant/retardant clothing.

Environmental exposure controls Local authorities should be advised if significant spillages cannot be contained. Do not allow into any sewer, on the ground or into any body of water. Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Colour No information available
Odour Characteristic
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	151 °C	
Flash point	38 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%) No information available
Softening Point No information available
Molecular weight No information available

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

VOC Content (%)	No information available
Liquid Density	No information available
Bulk density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

vomiting.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) --	LD50 >15000 mg/Kg (rat) OECD 401	LD50 > 3400 mg/kg (rat) OECD 402	LC50 (4hrs) >13.1 mg/l (rat)
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	EL50 (72h) = 4.1 mg/l (Pseudokirchnerella subcapitata)	10-30 mg/l	-	10-30mg/l (daphnia magna)	-

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

--	OECD 401				
Petroleum distillates, hydrotreated light 64742-47-8	-	LC50: =2.4mg/L (96h, Oncorhynchus mykiss) LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus)	-	LC50: =4720mg/L (96h, Den-dronereides heteropoda)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Petroleum distillates, hydrotreated light 64742-47-8	-	159

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Petroleum distillates, hydrotreated light 64742-47-8	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

Land transport (ADR/RID)

14.1 UN Number	UN1263
14.2 Proper Shipping Name	Paint, Environmentally Hazardous
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing Group	III
Description	UN1263, Paint, 3, III, (D/E), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special Provisions	163, 650, 367
Classification Code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	30

IMDG

14.1 UN number	UN1263
14.2 Proper Shipping Name	Paint (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), Marine Pollutant
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1263, Paint (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 3, III, (38°C c.c.), Marine Pollutant
14.5 Marine Pollutant	P
14.6 Special Provisions	163, 223, 367, 955
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	UN1263
14.2 Proper Shipping Name	Paint
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1263, Paint, 3, III
14.5 Environmental hazards	Yes
14.6 Special Provisions	A3, A72, A192
Limited Quantity (LQ)	10 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS
E2 - Hazardous to the Aquatic
Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No
Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL

Ceiling Maximum limit value *

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure

STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

STEL (Short Term Exposure Limit)
Skin designation

Key literature references and sources for data

No information available

Prepared By

Product Safety & Regulatory Affairs

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 06-Apr-2017

Revision date 24-Jun-2019
Revision Number 1.01

Revision date 24-Jun-2019

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet