

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019

Revision date 05-Aug-2021 Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK POLYURETHANE WOOD GLUE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik Limited
Common Rd
ST16 3EH
Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

United Kingdom +44 (1785) 272650

Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)

2.2. Label elements

Contains 4,4'-Methylenediphenyl diisocyanate



Signal word Danger

Hazard statements

H315 - Causes skin irritation.

United Kingdom - BE Page 1 / 13

Revision date 05-Aug-2021

Revision Number 1.01

EVO-STIK POLYURETHANE WOOD GLUE

....

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Supercedes Date: 27-Nov-2019

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P201 - Obtain special instructions before use

P260 - Do not breathe vapour

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

As from 24 August 2023 adequate training is required before industrial or professional use. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. Type A1 according to standard EN 14387) is used.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
4,4'-Methylenediphenyl diisocyanate	202-966-0	101-68-8	40 - <80	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	

United Kingdom - BE Page 2 / 13

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019 Revision Number 1.01

				(H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) STOT RE 2 (H373)	
Morpholine, 4,4'-(oxydi-2,1-ethanediy I)bis-	229-194-7	6425-39-4	1 - <5	Eye Irrit. 2 (H319)	01-2119969278- 20-XXXX

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation May cause allergic respiratory reaction. If breathing has stopped, give artificial

respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical

Revision date 05-Aug-2021

advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give

anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid contact with skin, eyes

or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more

information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/

or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Burning sensation. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsMay cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

United Kingdom - BE Page 3 / 13

EVO-STIK POLYURETHANE WOOD GLUE

5.1. Extinguishing media

Supercedes Date: 27-Nov-2019

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Product is or contains a sensitiser. May cause sensitisation by inhalation and skin

Revision date 05-Aug-2021

Revision Number 1.01

contact. May cause sensitisation by skin contact.

Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen cyanide. Isocyanates. **Hazardous combustion products**

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal Personal precautions

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak. Avoid breathing vapours or mists.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. **Environmental precautions**

6.3. Methods and material for containment and cleaning up

Methods for containment Keep from any possible contact with water.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact Advice on safe handling

with skin, eyes or clothing. Ensure adequate ventilation. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse. Avoid

breathing vapours or mists.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated

clothing and gloves, including the inside, before re-use. Wash hands before breaks and

immediately after handling the product.

United Kingdom - BE Page 4 / 13

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Keep away from water or moist air.

Revision date 05-Aug-2021

Revision Number 1.01

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
4,4'-Methylenediphenyl diisocyanate	-	TWA: 0.02 mg/m ³
101-68-8		STEL: 0.07 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
4,4'-Methylenediphenyl	-	1 µmol/mol Creatinine (urine -	-
diisocyanate		urinary Diamine post task)	
101-68-8			

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DN	EL)					
4,4'-Methylenediphenyl diiso	4,4'-Methylenediphenyl diisocyanate (101-68-8)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Short term Systemic health effects	Dermal	50 mg/kg bw/d				
worker Short term Systemic health effects	Inhalation	0.1 mg/m³				
worker Short term Local health effects	Dermal	28700 μg/cm²				
worker Short term Local health effects	Inhalation	0.1 mg/m³				
worker Long term Systemic health effects	Inhalation	0.05 mg/m³				
worker Long term Local health effects	Inhalation	0.05 mg/m³				

Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- (6425-39-4)				
Туре		Derived No Effect Level (DNEL)	Safety factor	
Long term	Inhalation	7.28 mg/m³		

United Kingdom - BE Page 5 / 13

Revision date 05-Aug-2021

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019 Revision Number 1.01

Systemic health effects worker			
Long term Systemic health effects	Dermal	1 mg/kg bw/d	
worker			

Derived No Effect Level (DN	Derived No Effect Level (DNEL)						
4,4'-Methylenediphenyl diiso	4,4'-Methylenediphenyl diisocyanate (101-68-8)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
Consumer Short term Systemic health effects	Dermal	25 mg/kg bw/d					
Consumer Short term Systemic health effects	Inhalation	0.05 mg/m ³					
Consumer Short term Systemic health effects	Oral	20 mg/kg bw/d					
Consumer Short term Local health effects	Dermal	17200 μg/cm ²					
Consumer Short term Local health effects	Inhalation	0.05 mg/m ³					
Consumer Long term Systemic health effects	Inhalation	0.025 mg/m ³					
Consumer Long term Local health effects	Inhalation	0.025 mg/m³					

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)					
4,4'-Methylenediphenyl diisocyanate (101-68-8	4,4'-Methylenediphenyl diisocyanate (101-68-8)				
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	1 mg/l				
Marine water	0.1 mg/l				
Soil	1 mg/kg dry weight				
Sewage treatment plant	1 mg/l				
Freshwater - intermittent	10 mg/l				

Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- (6425-39-4)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.1 mg/l		
Marine water	0.01 mg/l		
Freshwater sediment	8.2 mg/kg dry weight		
Marine sediment	0.82 mg/kg dry weight		
Freshwater - intermittent	1 mg/l		
Sewage treatment plant	100 mg/l		
Soil	1.58 mg/kg dry weight		

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

United Kingdom - BE Page 6 / 13

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the

gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min.

Revision date 05-Aug-2021

Revision Number 1.01

Gloves must conform to standard EN 374

Skin and body protection Suitable protective clothing. Suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases

and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Gel
Colour Cream
Odour Mustv

Odour threshold No information available

Property Values Remarks • Method

pH No data available
pH (as aqueous solution) No data available
Melting point / freezing point < 10 °C
Initial boiling point and boiling > 330 °C

range

Flash point > 200 °C CC (closed cup)

Evaporation rate approx No data available Flammability Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

imits

Lower flammability or explosive No data available

limits

Vapour pressure 0.01
Relative vapour density 8.5
Relative density 1.10

Water solubility Insoluble in water slightly soluble

Solubility(ies)

Partition coefficient

Autoignition temperature

Decomposition temperature

No data available

>600 °C

No data available

Kinematic viscosity > 21 mm²/s @ 40°C

Dynamic viscosity

Explosive properties

Oxidising properties

No data available

No data available

No data available

9.2. Other information

Solid content (%) No information available

VOC Content (%)

Density No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

United Kingdom - BE Page 7 / 13

Revision date 05-Aug-2021

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019 Revision Number 1.01

10.2. Chemical stability

Stability Reacts with water.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerisation Hazardous polymerisation may occur.

10.4. Conditions to avoid

Conditions to avoid Excessive heat. Exposure to water.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Thermal

products decomposition can lead to release of irritating and toxic gases and vapours. Hydrogen

cyanide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause sensitisation

in susceptible persons. (based on components). May cause irritation of respiratory tract.

Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged

skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional

affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing,

tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause

redness and tearing of the eyes.

Numerical measures of toxicity

United Kingdom - BE Page 8 / 13

Revision date 05-Aug-2021

Revision Number 1.01

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document ATEmix (inhalation-dust/mist) 2.54 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
4,4'-Methylenediphenyl	=31600 mg/kg (Rattus)	LD 50 > 9400 mg/kg	=1.5 mg/L (Rattus) 4 h
diisocyanate	= 9200 mg/kg (Rattus)	(Oryctolagus cuniculus)	-
101-68-8		OECD 402	
Morpholine,	LD50 =2025 mg/Kg (Rattus)	LD50 >3000 mg/Kg	
4,4'-(oxydi-2,1-ethanediyl)bis-		(Oryctolagus cuniculus)	
6425-39-4			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

Chemical name	European Union
4,4'-Methylenediphenyl diisocyanate	Carc. 2
101-68-8	

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

United Kingdom - BE Page 9 / 13

Revision date 05-Aug-2021

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019 Revision Number 1.01

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna		
Morpholine, 4,4'-(oxydi-2,1-ethanedi yl)bis- 6425-39-4	EC50 (72h) >100 mg/L Algae (Pseudokirchner ella subcapitata) Static		-	EC50 (48h) >100 mg/L (Daphnia magna) Static		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information				
4,4'-Methylenediphenyl diisocyanate (101-68-8) Method Exposure time Value Results				
			Not readily biodegradable	
Biodegradability: Modified MITI Test		5	, o	
(II)				

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51	200
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-6425-39-4	0.5	3

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
4,4'-Methylenediphenyl diisocyanate 101-68-8	The substance is not PBT / vPvB
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- 6425-39-4	The substance is not PBT / vPvB

United Kingdom - BE Page 10 / 13

EVO-STIK POLYURETHANE WOOD GLUE

12.6. Other adverse effects

Supercedes Date: 27-Nov-2019

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 07 02 08 other still bottoms and reaction residues

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

Revision date 05-Aug-2021

Revision Number 1.01

substances

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group 14.5 Environmental hazards Not applicable

14.6 Special Provisions None

IMDG

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated

NP 14.5 Marine pollutant 14.6 Special Provisions None

Not applicable 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

United Kingdom - BE Page 11/13

Revision date 05-Aug-2021

Revision Number 1.01

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019

•

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Sheck whether measures in accordance with birective 94/33/20 for the protection of young people at work must be take

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH
		Annex XVII
4,4'-Methylenediphenyl diisocyanate	101-68-8	56[a].
		74.
Diisocyantes		74
, in the second		

56 . If product supplied to the general public with substance ≥0.1%, then gloves must be provided with the product.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

United Kingdom - BE Page 12/13

Revision date 05-Aug-2021

Revision Number 1.01

EVO-STIK POLYURETHANE WOOD GLUE

Supercedes Date: 27-Nov-2019

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 05-Aug-2021

Indication of changes

Revision note Not applicable.

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE

INDUSTRIAL OR PROFESSIONAL USE

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13