

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

WICKES ALL WEATHER ACRYLIC WATERPROOFER Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name Pure substance/mixture WICKES ALL WEATHER ACRYLIC WATERPROOFER Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Uses advised against Primers, Sealers, and Undercoaters. None known

1.3. Details of the supplier of the safety data sheet

Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

 United Kingdom
 +44 (1785) 272650

 Ireland
 +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flammable liquids

Category 3 - (H226)

2.2. Label elements



Signal word Warning

Hazard statements H226 - Flammable liquid and vapour.

EU Specific Hazard Statements

EUH208 - Contains Fatty acids, C14-18 and C16-18-unsatd., maleated. May produce an allergic reaction EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

- P102 Keep out of reach of children
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P280 Wear protective gloves and eye/face protection

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Propylene glycol monomethyl ether acetate	203-603-9	108-65-6	15 - 25	Flam. Liq. 3 (H226)		01-2119475791- 29-XXXX
Propylene glycol monomethyl ether	203-539-1	107-98-2	5 - <10	STOT SE 3 (H336) Flam. Liq. 3 (H226)		01-2119457435- 35-xxxx
1-methoxy-2-propyl acetate	203-603-9	108-65-6	5 - <10	Flam Liq. 3 (H226) STOT SE 3 (H336)		01-2119475791- 29-xxxx
Titanium dioxide	236-675-5	13463-67-7	5 - <10	Carc. 2 (H351i)		01-2119489379- 17-XXXX
Xylenes (o-, m-, p- isomers)	215-535-7	1330-20-7	0.1 - <1	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H322) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)		01-2119488216- 32-XXXX

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

Ethylbenzene	202-849-4	100-41-4	0.1 - <1	STOT RE 2 (H373) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) Flam Liq. 2 (H225) Aquatic Chronic 3 (H412)	01-2119489370- 35-XXXX
Fatty acids, C14-18 and C16-18-unsatd., maleated	288-306-2	85711-46-2	0.1 - <1	Skin Irrit. 2 (H315) Skin Sens. 1 (H317)	01-2119976378- 19-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.		
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.		
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.		
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.		
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.		
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.		
4.2. Most important symptoms and	d effects, both acute and delayed		
Symptoms	No information available.		
4.3. Indication of any immediate m	nedical attention and special treatment needed		
Note to doctors	Treat symptomatically.		
SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.		

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Unsuitable extinguishing media	No information available.
5.2. Special hazards arising from t	he substance or mixture
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon dioxide (CO2). Hydrogen chloride. Silicon dioxide.
5.3. Advice for firefighters	
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.
SECTION 7: Handling and st	orage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

	ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.
7.2. Conditions for safe storage, in	ncluding any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
7.3. Specific end use(s)	
Specific use(s) Primers, Sealers, and Undercoaters.	
Dist. Management Matheads (DMM)	The information required is contained in this October Data Object

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Observe technical data sheet.

Other information

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	Ireland	United Kingdom
Propylene glycol monomethyl	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
ether acetate	TWA: 275 mg/m ³	TWA: 275 mg/m ³	TWA: 274 mg/m ³
108-65-6	STEL: 100 ppm	STEL: 100 ppm	STEL: 100 ppm
	STEL: 550 mg/m ³	STEL: 550 mg/m ³	STEL: 548 mg/m ³
	*	Sk*	Sk*
Propylene glycol monomethyl	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
ether	TWA: 375 mg/m ³	TWA: 375 mg/m ³	TWA: 375 mg/m ³
107-98-2	STEL: 150 ppm	STEL: 150 ppm	STEL: 150 ppm
	STEL: 568 mg/m ³	STEL: 568 mg/m ³	STEL: 560 mg/m ³
	*		Sk*
1-methoxy-2-propyl acetate	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
108-65-6	TWA: 275 mg/m ³	TWA: 275 mg/m ³	TWA: 274 mg/m ³
	STEL: 100 ppm	STEL: 100 ppm	STEL: 100 ppm
	STEL: 550 mg/m ³	STEL: 550 mg/m ³	STEL: 548 mg/m ³
	*	Sk*	Sk*
Titanium dioxide	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³	TWA: 4 mg/m ³
		STEL: 30 mg/m ³	STEL: 30 mg/m ³
		STEL: 12 mg/m ³	STEL: 12 mg/m ³
Talc	-	TWA: 10 mg/m ³	TWA: 1 mg/m ³
14807-96-6		TWA: 0.8 mg/m ³	STEL: 3 mg/m ³
		STEL: 30 mg/m ³	
		STEL: 2.4 mg/m ³	
Xylenes (o-, m-, p- isomers)	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
1330-20-7	TWA: 221 mg/m ³	TWA: 221 mg/m ³	TWA: 220 mg/m ³
	STEL: 100 ppm	STEL: 100 ppm	STEL: 100 ppm
	STEL: 442 mg/m ³	STEL: 442 mg/m ³	STEL: 441 mg/m ³
	*	Sk*	Sk*
Carbon black	-	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³
1333-86-4		STEL: 15 mg/m ³	STEL: 7 mg/m ³
Ethylbenzene	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
100-41-4	TWA: 442 mg/m ³	TWA: 442 mg/m ³	TWA: 441 mg/m ³

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

	- STEL: 200 ppm STEL: 884 mg/m ³ *	STEL: 200 ppm STEL: 884 mg/m ³ Sk*	STEL: 125 ppm STEL: 552 mg/m ³ Sk*
Magnesite 13717-00-5	-	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
Xylenes (o-, m-, p- isomers)	-	1.5 g/g Creatinine (urine -	650 mmol/mol creatinine urine
1330-20-7		Methylhippuric acids end of shift)	
Ethylbenzene	-	0.7 g/g Creatinine (urine - sum of	-
100-41-4		Mandelic acid and Phenylglyoxylic	
		acid end of shift at end of	
		workweek)	
		0.7 g (end-exhaled air - not	
		critical)	

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DN	EL)				
Propylene glycol monometh	Propylene glycol monomethyl ether acetate (108-65-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	275 mg/m³			
worker Short term Systemic health effects	Inhalation	550 mg/m³			
worker Long term Local health effects	Inhalation	550 mg/m³			
worker Long term Systemic health effects	Dermal	796 mg/kg bw/d			

Propylene glycol monomethyl ether (107-98-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Short term Systemic health effects	Inhalation	553.5 mg/m³		
worker Short term Local health effects	Inhalation	553.5 mg/m³		
worker Long term Systemic health effects	Dermal	183 mg/kg bw/d		
worker Long term Systemic health effects	Inhalation	369 mg/m³		

1-methoxy-2-propyl acetate (108-65-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	275 mg/m³	
worker Long term Systemic health effects	Dermal	796 mg/kg bw/d	

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Titanium dioxide (13463-67-7)			
Туре		Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	10 mg/m³	
Long term		-	
Local health effects			

Xylenes (o-, m-, p- isomers) (1330-20-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	77 mg/m³	
Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m³	

Derived No Effect Level (DNEL)			
Propylene glycol monometh	Propylene glycol monomethyl ether acetate (108-65-6)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	33 mg/m³	
Consumer Long term Local health effects	Inhalation	33 mg/m³	
Consumer Long term Systemic health effects	Dermal	320 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	36 mg/kg bw/d	

Propylene glycol monomethyl ether (107-98-2)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Dermal	78 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	43.9 mg/m³	
Long term			
Systemic health effects			
Consumer	Oral	33 mg/kg bw/d	
Long term			
Systemic health effects			

1-methoxy-2-propyl acetate (108-65-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	33 mg/m³	
Consumer	Inhalation	33 mg/m³	

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Long term Local health effects			
Consumer Long term Systemic health effects	Dermal	320 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	36 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level	Safety factor
	-	(DNEL)	-
Consumer	Oral	700 mg/kg bw/d	
Long term			
Systemic health effects			

Predicted No Effect Concentration No information available. (PNEC)

Propylene glycol monomethyl ether acetate (108-65-6)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	0.635 mg/l	
Marine water	0.064 mg/l	
Microorganisms in sewage treatment	100 mg/l	
Freshwater sediment	3.29 mg/kg dry weight	
Marine sediment	0.329 mg/kg dry weight	
Soil	0.29 ma/kg dry weight	

Propylene grycor monometnyl ether (107-98-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	52.3 mg/kg dry weight
Marine sediment	5.2 mg/kg dry weight
Soil	4.59 mg/kg dry weight

1-methoxy-2-propyl acetate (108-65-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.635 mg/l
Marine water	0.064 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	3.29 mg/l
Marine sediment	0.329 mg/kg dry weight
Soil	0.29 mg/kg dry weight

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

Personal protective equipment	
Eye/face protection	Tight sealing safety goggles.
Hand protection	Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced
Skin and body protection	regularly and if there is any sign of damage to the glove material. Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour threshold	Liquid Liquid Grey Characteristic No information available	
Property pH pH (as aqueous solution) Melting point / freezing point Initial boiling point and boiling	Values No data available No data available No data available 120 °C	Remarks • Method
range Flash point Evaporation rate Flammability Flammability Limit in Air	 > 32 °C No data available Not applicable for liquids . 	No information available
Upper flammability or explosive limits Lower flammability or explosive limits		
Vapour pressure Relative vapour density Relative density Water solubility	No data available No data available No data available No data available	
Solubility(ies) Partition coefficient Autoignition temperature Decomposition temperature	No data available No data available No data available No data available	
Kinematic viscosity Dynamic viscosity Explosive properties Oxidising properties	No data available No data available No data available No data available	
9.2. Other information Solid content (%)	No information available	
VOC Content (%) Liquid Density	1.0	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

No information available.

WICKES ALL WEATHER ACRYLIC WATERPROOFER Supercedes Date: 09-Oct-2020 Revision date 30-Apr-2021 Revision Number 2.07

10.2. Chemical stability			
Stability	Stable under normal conditions.		
Explosion data			
Sensitivity to mechanical	None.		
impact Sensitivity to static discharge	Yes.		
10.3. Possibility of hazardous reac	tions		
Possibility of hazardous reactions	None under normal processing.		
10.4. Conditions to avoid			
Conditions to avoid	Heat, flames and sparks.		
10.5. Incompatible materials			
Incompatible materials	None known based on information supplied.		
10.6. Hazardous decomposition pro	oducts_		
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.		
SECTION 11: Toxicological i	nformation		
11.1. Information on toxicological e	effects		
Information on likely routes of exp	osure		
Product Information			
Inhalation	Based on available data, the classification criteria are not met.		
Eye contact	Based on available data, the classification criteria are not met.		
Skin contact	Based on available data, the classification criteria are not met.		
Ingestion	Based on available data, the classification criteria are not met.		
Symptoms related to the physical, chemical and toxicological characteristics			
Symptoms	No information available.		
Numerical measures of toxicity			

The following values are calculated based on chapter 3.1 of the GHS document ATEmix (inhalation-dust/mist) 410.7524 mg/l

.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propylene glycol monomethyl	=8532 mg/kg (Rattus)	> 5 g/kg (Oryctolagus	= 16000 mg/m ³ (Rat) 6 h
ether acetate		cuniculus)	
108-65-6			

WICKES ALL WEATHER ACRYLIC WATERPROOFER Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

	-		
Propylene glycol monomethyl ether 107-98-2	>3500 mg/Kg (Rattus)	>2000 mg/Kg (Rattus)	>7559 ppm (Rattus) 6 h
1-methoxy-2-propyl acetate 108-65-6	=8532 mg/kg (Rattus)	> 5 g/kg (Oryctolagus cuniculus)	= 16000 mg/m ³ (Rat) 6 h
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
Xylenes (o-, m-, p- isomers) 1330-20-7	=3500 mg/kg (Rattus)	 > 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus) 	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h
Ethylbenzene 100-41-4	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.4 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide	Carc. 2
13463-67-7	

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity	Based on available data, the classification criteria are not met.			
STOT - single exposure	Based on available data, the classification criteria are not met.			
STOT - repeated exposure	Based on available data, the classification criteria are not met.			
Aspiration hazard	Based on available data, the classification criteria are not met.			
11.2. Information on other hazards				
11.2.1. Endocrine disrupting properties				
Endocrine disrupting properties	No information available.			
11.2.2. Other information				
Other adverse effects	No information available.			
SECTION 12: Ecological information				

WICKES ALL WEATHER ACRYLIC WATERPROOFER Supercedes Date: 09-Oct-2020

.

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Propylene glycol monomethyl ether acetate 108-65-6	-	LC50: =161mg/L (96h, Pimephales promelas)	-	EC50: >500mg/L (48h, Daphnia magna)		
Propylene glycol monomethyl ether 107-98-2	-	LC50: 4600 - 10000mg/L (96h, Leuciscus idus) LC50: =20.8g/L (96h, Pimephales promelas)	-	EC50: =23300mg/L (48h, Daphnia magna)		
1-methoxy-2-propyl acetate 108-65-6	-	LC50: =161mg/L (96h, Pimephales promelas)	-	EC50: >500mg/L (48h, Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Dappnia magna)		
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchner iella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)		
Fatty acids, C14-18 and C16-18-unsatd., maleated 85711-46-2	-	LC50: >100mg/L (96h, Danio rerio)	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information				
1-methoxy-2-propyl acetate (108-65-6)				
Method	Exposure time	Value	Results	
OECD Test No. 301F: Ready	28 days	83%	Readily biodegradable	
Biodegradability: Manometric	-			
Respirometry Test (TG 301 F)				

Xylenes (o-, m-, p- isomers) (1330-20-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	biodegradation	87.8 % Readily
Biodegradability: Manometric			biodegradable
Respirometry Test (TG 301 F)			-

12.3. Bioaccumulative potential

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Propylene glycol monomethyl ether acetate 108-65-6	0.43	-
Propylene glycol monomethyl ether 107-98-2	-0.437	2
1-methoxy-2-propyl acetate 108-65-6	0.43	-
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15	15
Ethylbenzene 100-41-4	3.2	15

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Propylene glycol monomethyl ether acetate 108-65-6	The substance is not PBT / vPvB
Propylene glycol monomethyl ether 107-98-2	The substance is not PBT / vPvB
1-methoxy-2-propyl acetate 108-65-6	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB
13463-67-7	PBT assessment does not apply
Xylenes (o-, m-, p- isomers) 1330-20-7	The substance is not PBT / vPvB
Ethylbenzene 100-41-4	The substance is not PBT / vPvB
Fatty acids, C14-18 and C16-18-unsatd., maleated 85711-46-2	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

WICKES ALL WEATHER ACRYLIC WATERPROOFER Supercedes Date: 09-Oct-2020 Revision date 30-Apr-2021 Revision Number 2.07

SECTION 14: Transport information

Note:	The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.
Land transport (ADR/RID) 14.1 UN number or ID number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Labels 14.4 Packing group Description 14.5 Environmental hazards 14.6 Special Provisions Classification code Tunnel restriction code Limited Quantity (LQ) ADR Hazard Id (Kemmler Number)	UN1263 Paint related material 3 3 III UN1263, Paint related material, 3, III, (D/E) Not applicable 163, 650, 367 F1 (D/E) 5 L 30
IMDG 14.1 UN number or ID number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) 14.4 Packing group Description 14.5 Marine pollutant 14.6 Special Provisions Limited Quantity (LQ) EmS-No 14.7 Transport in bulk according	UN1263 Paint related material 3 III UN1263, Paint related material, 3, III, (32°C c.c.) NP 163, 223, 367, 955 5 L F-E, S-E to Annex II of MARPOL and the IBC Code Not applicable
Air transport (ICAO-TI / IATA-DGR 14.1 UN number or ID number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) 14.4 Packing group Description 14.5 Environmental hazards 14.6 Special Provisions Limited Quantity (LQ) ERG Code	UN1263 Paint related material 3 III UN1263, Paint related material, 3, III Not applicable A3, A72, A192 10 L 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

WICKES ALL WEATHER ACRYLIC WATERPROOFER

Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

- H225 Highly flammable liquid and vapour
- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H373 May cause damage to organs through prolonged or repeated exposure
- H412 Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation

WICKES ALL WEATHER ACRYLIC WATERPROOFER Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021 Revision Number 2.07

SVHC PBT vPvB STOT RE STOT SE EWC	Substance(s) of Very High Concern Persistent, Bioaccumulative, and Toxic (PBT) Chemicals Very Persistent and very Bioaccumulative (vPvB) Chemicals Specific target organ toxicity - Repeated exposure Specific target organ toxicity - Single exposure European Waste Catalogue	
Key literature references and sources for data No information available		
Prepared By	Product Safety & Regulatory Affairs	
Revision date	30-Apr-2021	
Indication of changes		
Revision note	Not applicable.	
Training Advice	No information available	

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

No information available

Disclaimer

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet