



Wickes All Weather

ACRYLIC WATERPOOFER FOR FLAT ROOFS

Date: 21 September 2021

Fact Sheet No.: TDS00189

YOUR SMART ADVANTAGES

- Instantly waterproof
- Provides flexible, seamless coating for roofs
- No primer needed

USES

Wickes All Weather Acrylic Waterproofing for roofs is a flexible, acrylic resin waterproofing for roof protection. It stops leaks instantly and contains fibres to bridge splits and cracks up to 10mm wide. It is light grey in colour. Wickes All Weather Acrylic Waterproofing for roofs dries to a tough, durable coating, which is suitable for either localised repairs or remedial treatment over the whole roof area. It can be applied to damp surfaces and is not affected by rain during application or drying. Wickes All Weather Acrylic Waterproofing for roofs has excellent adhesion to a wide range of surfaces, including asphalt, bituminous roofing, fibre-reinforced sheeting, metal, concrete and brickwork. No primer is needed on sound, non-porous substrates. Highly porous or friable surfaces should be primed with a bitumen primer.

PRODUCT CHARACTERISTICS

Colour	Grey
Form	Brushable & trowellable paste
Specific Gravity	1.1 approx.
Composition	A fibre reinforced solution of an acrylic co-polymer
Product Code	30813205 Grey 4 litres x 2
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry

conditions within the temperature range +5°C to +25°C, out of direct sunlight and away from sources of heat and ignition. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +35°C
Service Temperature	-10°C to +85°C (depending on ambient conditions)
Coverage	1 to 2 litres (approx.) per m ² (depending on substrate, application technique and performance requirements)
Drying Times	Immediate waterproofing 2 to 3 days to dry (depending on coating thickness and drying conditions)
Heat Flow Resistance	The cured film will not sag or flow under normal conditions
Fire Resistance	Wet: Flammable Dry: Will burn
Cleaning	Clean tools and equipment with white spirit immediately after use. Dried product is difficult to remove

DIRECTIONS FOR USE

IMPORTANT: Before using Wickes All Weather Acrylic Waterproofing for roofs, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Ensure the roof is structurally sound, clean, dry and free from rust, dirt, oil, grease, loose paint, stone chippings,

rust, standing water and other surface contaminants.

2. Remove any organic growth i.e. moss or lichen with a fungicidal wash, following the instructions on pack.
3. Surfaces may be damp, but clear of standing water.
4. Most non-porous surfaces do not need to be primed.
5. New metal surfaces should be degreased with a suitable solvent. Metal surfaces with residual rust remaining after cleaning should be treated with a zinc phosphate or other suitable rust inhibitive primer. New galvanised sheeting should be primed with a suitable primer.
6. Highly porous or friable surfaces should be primed with a bitumen primer. Ensure that the primer is fully dry before applying Wickes All Weather Acrylic Waterproofing for roofs.

APPLICATION

7. Stir thoroughly before use.
8. Apply by brush, working well into damp areas to dispel moisture and ensure good adhesion. The use of disposable brushes is recommended.
9. Use liberally over splits and cracked areas. Cracks over 10mm should be covered with a suitable flexible scrim bedded into the coating. Ensure gaps or cracks are completely covered.
10. The waterproofing treatment should be carried up adjoining vertical surfaces for approximately 150mm and behind existing flashing. One coat is normally sufficient.
11. Do not apply over roof lights, glass or windows.

CLEANING

12. Clean tools and equipment immediately after use with white spirit. Dried product is difficult to remove.

PRECAUTIONS IN USE

For external use only.

Do not apply in areas that will be exposed to foot traffic and do not place heavy objects on top of areas coated with it.

Do not use in aquatic environments, or internally as a tanking membrane.

Shade variations may occur between batches. When completing project requiring multiple tins please ensure that they are from the same batch.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and

Safety Data sheet for Wickes All Weather Acrylic Waterproofing for roofs, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com