

WICKES ALL WEATHER POLYMER SEALANT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product name : WICKES ALL WEATHER POLYMER SEALANT
 Registration number REACH : Not applicable (mixture)
 Product type REACH : Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Relevant identified uses

Adhesive

1.2.2 Uses advised against

No uses advised against known

1.3 Details of the supplier of the safety data sheet:

Supplier of the safety data sheet

SODAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 📠 +32 14 42 65 14
 msds@soudal.com

Manufacturer of the product

SODAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 📠 +32 14 42 65 14
 msds@soudal.com

1.4 Emergency telephone number:

24h/24h (Telephone advice: English, French, German, Dutch):
 +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 3	H226: Flammable liquid and vapour.
STOT SE	category 3	H336: May cause drowsiness or dizziness.

2.2 Label elements:



Contains: n-butyl acetate.

Signal word
 H-statements

H226
 H336

P-statements

P101
 P102
 P210
 P243
 P280
 P304 + P340
 P303 + P361 + P353
 P312
 P501

Warning

Flammable liquid and vapour.
 May cause drowsiness or dizziness.

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharge.
 Wear protective gloves and eye protection/face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 Call a POISON CENTER/doctor if you feel unwell.
 Dispose of contents/container in accordance with local/regional/national/international regulation.

WICKES ALL WEATHER POLYMER SEALANT

Supplemental information

EUH066

Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards:

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1 Substances:

Not applicable

3.2 Mixtures:

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
n-butyl acetate	123-86-4 204-658-1	C>30 %	Flam. Liq. 3; H226 STOT SE 3; H336	(1)(2)(10)	Constituent

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1 Description of first aid measures:

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Central nervous system depression. Headache. Nausea. Dizziness. Narcosis. Disturbances of consciousness.

After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Red skin. Dry skin. Cracking of the skin.

After eye contact:

Slight irritation. ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the eye tissue. Lacrimation. Conjunctivitis.

After ingestion:

Irritation of the gastric/intestinal mucosa. AFTER INGESTION OF HIGH QUANTITIES: Central nervous system depression. Symptoms similar to those listed under inhalation.

4.2.2 Delayed symptoms

No effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

5.1.1 Suitable extinguishing media:

Water spray. Alcohol-resistant foam. ABC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2 Special hazards arising from the substance or mixture:

Upon combustion: CO and CO₂ are formed.

5.3 Advice for firefighters:

5.3.1 Instructions:

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

WICKES ALL WEATHER POLYMER SEALANT

If exposed to fire cool the closed containers by spraying with water. Do not move the load if exposed to heat.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2 Environmental precautions:

Contain leaking substance. Dam up the solid spill. Try to reduce evaporation. Prevent spreading in sewers. Use appropriate containment to avoid environmental contamination.

6.3 Methods and material for containment and cleaning up:

Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4 Reference to other sections:

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1 Precautions for safe handling:

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Gas/vapour heavier than air at 20°C. Avoid prolonged and repeated contact with skin. Keep container tightly closed. Remove contaminated clothing immediately. Do not discharge the waste into the drain.

7.2 Conditions for safe storage, including any incompatibilities:

7.2.1 Safe storage requirements:

Store at room temperature. Keep only in the original container. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Polyethylene.

7.2.4 Non suitable packaging material:

No data available

7.3 Specific end use(s):

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters:

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

The Netherlands

n-Butylacetaat	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	99 ppm
	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	480 mg/m ³

Belgium

Acétate de n-butyle	Time-weighted average exposure limit 8 h	150 ppm
	Time-weighted average exposure limit 8 h	723 mg/m ³
	Short time value	200 ppm
	Short time value	964 mg/m ³

USA (TLV-ACGIH)

n-Butyl acetate	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	150 ppm
-----------------	--	---------

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

3 / 12

WICKES ALL WEATHER POLYMER SEALANT

n-Butyl acetate	Short time value (TLV - Adopted Value)	200 ppm
-----------------	--	---------

Germany

n-Butylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	62 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	300 mg/m ³

France

Acétate de n-butyle	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	150 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	710 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	200 ppm
	Short time value (VL: Valeur non réglementaire indicative)	940 mg/m ³

UK

Butyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	150 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	724 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	200 ppm
	Short time value (Workplace exposure limit (EH40/2005))	966 mg/m ³

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

Butyl acetate (Volatile Organic compounds)	NIOSH	2549
n-Butyl Acetate (Esters I)	NIOSH	1450
n-Butyl Acetate	OSHA	1009

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL - Workers

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	480 mg/m ³	

DNEL - General population

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects dermal	3.4 mg/kg bw/day	
	Long-term systemic effects inhalation	12 mg/m ³	
	Long-term systemic effects oral	3.4 mg/kg bw/day	

PNEC

n-butyl acetate

Compartments	Value	Remark
Fresh water	0.18 mg/l	
Marine water	0.018 mg/l	
Fresh water sediment	0.981 mg/kg sediment dw	
Marine water sediment	0.0981 mg/kg sediment dw	
Soil	0.0903 mg/kg soil dw	
STP	35.6 mg/l	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2 Exposure controls:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Avoid prolonged and repeated contact with skin. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

c) Eye protection:

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

4 / 12

WICKES ALL WEATHER POLYMER SEALANT

Safety glasses.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical form	Viscous
Odour	Solvent-like odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	No data available
Flammability	Flammable liquid and vapour.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	23 °C - 60 °C
Evaporation rate	No data available
Relative vapour density	> 2
Vapour pressure	No data available
Solubility	water ; insoluble
Relative density	1.3
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2 Other information:

Absolute density	1300 kg/m ³
------------------	------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity:

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2 Chemical stability:

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

No data available.

10.4 Conditions to avoid:

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system.

10.5 Incompatible materials:

No data available.

10.6 Hazardous decomposition products:

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

11.1.1 Test results

Acute toxicity

WICKES ALL WEATHER POLYMER SEALANT

No (test) data on the mixture available

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

5 / 12

WICKES ALL WEATHER POLYMER SEALANT

n-butyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	10760 mg/kg bw - 12789 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	14112 mg/kg bw		Rabbit (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

WICKES ALL WEATHER POLYMER SEALANT

No (test)data on the mixture available

n-butyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	
Dermal	Not irritating	Equivalent to OECD 404		24; 48; 72 hours	Rabbit	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

WICKES ALL WEATHER POLYMER SEALANT

No (test)data on the mixture available

n-butyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 408			Guinea pig	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

WICKES ALL WEATHER POLYMER SEALANT

No (test)data on the mixture available

n-butyl acetate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation	NOAEC	EPA OTS 798.2450	500 ppm		No adverse systemic effects	13 weeks (daily, 5 days/week)	Rat (male/female)	Experimental value

Classification is based on the relevant ingredients

Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

Mutagenicity (in vitro)

WICKES ALL WEATHER POLYMER SEALANT

No (test)data on the mixture available

n-butyl acetate

Result	Method	Test substrate	Effect	Value determination
Negative	OECD 471	Bacteria (S.typhimurium)		Experimental value
Negative	OECD 473	Chinese hamster lung fibroblasts		Experimental value

Mutagenicity (in vivo)

WICKES ALL WEATHER POLYMER SEALANT

No (test)data on the mixture available

n-butyl acetate

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	OECD 474		Mouse (male/female)		Read-across

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

WICKES ALL WEATHER POLYMER SEALANT

Carcinogenicity

WICKES ALL WEATHER POLYMER SEALANT

No (test) data on the mixture available

Reproductive toxicity

WICKES ALL WEATHER POLYMER SEALANT

No (test) data on the mixture available

n-butyl acetate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Body weight, organ weight, food consumption		Experimental value
	NOAEC	Equivalent to OECD 414	1500 ppm		Rabbit			
Effects on fertility	NOAEC	OECD 416	2000 ppm	> 90 day(s)	Rat (male/female)	No effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion CMR

Not classified for reprotoxic or developmental toxicity

Not classified for mutagenic or genotoxic toxicity

Not classified for carcinogenicity

Toxicity other effects

WICKES ALL WEATHER POLYMER SEALANT

No (test) data on the mixture available

n-butyl acetate

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
NOEC	EPA OTS 798.6050	1500 ppm		Hypoactivity	6 h	Rat (male/female)	Experimental value
NOAEC	EPA OTS 798.6050	500 ppm		no neurotoxic effects	13 week(s)	Rat (male/female)	Experimental value

Classification is based on the relevant ingredients

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

WICKES ALL WEATHER POLYMER SEALANT

No effects known.

SECTION 12: Ecological information

12.1 Toxicity:

WICKES ALL WEATHER POLYMER SEALANT

No (test) data on the mixture available

n-butyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	18 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value
Acute toxicity invertebrates	EC50	Other	44 mg/l	48 h	Daphnia sp.	Static system	Fresh water	Experimental value
Toxicity algae and other aquatic plants	EC50	Other	674.7 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value
	NOEC	Other	200 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value
Long-term toxicity aquatic invertebrates	NOEC	OECD 211	23 mg/l	21 day(s)	Daphnia magna		Fresh water	Read-across

	Parameter	Method	Value	Duration	Species	Value determination
Toxicity terrestrial plants	EC50	Equivalent to OECD 208	> 1000 mg/kg soil dw	14 day(s)	Lactuca sativa	Experimental value

Classification of the mixture is based on the relevant ingredients

Conclusion

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

7 / 12

WICKES ALL WEATHER POLYMER SEALANT

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2 Persistence and degradability:

n-butyl acetate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D: Closed Bottle Test	83 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	3.3 day(s)	0.5E+06 /cm ³	Experimental value

Conclusion

Contains readily biodegradable component(s)

12.3 Bioaccumulative potential:

WICKES ALL WEATHER POLYMER SEALANT

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

n-butyl acetate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		15.3			Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		2.3	25 °C	Test data

Conclusion

Does not contain bioaccumulative component(s)

12.4 Mobility in soil:

n-butyl acetate

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.268 - 1.844	QSAR

Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
28.5 Pa.m ³ /mol		25 °C		Experimental value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5 Results of PBT and vPvB assessment:

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6 Other adverse effects:

WICKES ALL WEATHER POLYMER SEALANT

Global warming potential (GWP)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

n-butyl acetate

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1 Waste treatment methods:

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other dangerous substances). Depending on branch of industry and production process, also other waste codes may be applicable. Hazardous waste according to Directive 2008/98/EC.

13.1.2 Disposal methods

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

8 / 12

WICKES ALL WEATHER POLYMER SEALANT

Incinerate under surveillance with energy recovery. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Use appropriate containment to avoid environmental contamination.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1 UN number:

Transport	Not subject
-----------	-------------

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Hazard identification number	
Class	
Classification code	

14.4 Packing group:

Packing group	
Labels	

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	
Limited quantities	
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.2.3.1.5 of ADR, is not subject

Rail (RID)

14.1 UN number:

Transport	Not subject
-----------	-------------

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Hazard identification number	
Class	
Classification code	

14.4 Packing group:

Packing group	
Labels	

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	
Limited quantities	
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.2.3.1.5 of RID, is not subject

Inland waterways (ADN)

14.1 UN number:

Transport	Not subject
-----------	-------------

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Class	
Classification code	

14.4 Packing group:

Packing group	
Labels	

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	
Limited quantities	
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.2.3.1.5 of ADN, is not subject

Sea (IMDG/IMSBC)

14.1 UN number:

UN number	1133
-----------	------

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

9 / 12

WICKES ALL WEATHER POLYMER SEALANT

14.2 UN proper shipping name:

Proper shipping name	Adhesives
----------------------	-----------

14.3 Transport hazard class(es):

Class	3
-------	---

14.4 Packing group:

Packing group	III
Labels	3

14.5 Environmental hazards:

Marine pollutant	-
Environmentally hazardous substance mark	no

14.6 Special precautions for user:

Special provisions	223
Special provisions	955
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.3.2.5 of IMDG, is not subject to IMDG Code chapters 4.1, 5.2 and 6.1

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

Annex II of MARPOL 73/78	Not applicable, based on available data
--------------------------	---

Air (ICAO-TI/IATA-DGR)

14.1 UN number:

UN number	1133
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Adhesives
----------------------	-----------

14.3 Transport hazard class(es):

Class	3
-------	---

14.4 Packing group:

Packing group	III
Labels	3

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	A3
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
39 %	
507 g/l	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
n-butyl acetate	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

10 / 12

WICKES ALL WEATHER POLYMER SEALANT

		<p>b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>
n-butyl acetate	<p>Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.</p>	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:</p> <p>"For professional users only".</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>

National legislation The Netherlands

WICKES ALL WEATHER POLYMER SEALANT

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 03
Waterbezwaarlijkheid	9

National legislation Germany

WICKES ALL WEATHER POLYMER SEALANT

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

n-butyl acetate

Schwangerschaft Gruppe	C
MAK 8-Stunden-Mittelwert ppm	1-Butylacetat; 100 ppm
MAK 8-Stunden-Mittelwert mg/m ³	1-Butylacetat; 480 mg/m ³
TA-Luft	5.2.5; I

National legislation France

WICKES ALL WEATHER POLYMER SEALANT

No data available

National legislation Belgium

WICKES ALL WEATHER POLYMER SEALANT

No data available

Other relevant data

WICKES ALL WEATHER POLYMER SEALANT

No data available

15.2 Chemical safety assessment:

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption,

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

11 / 12

WICKES ALL WEATHER POLYMER SEALANT

storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

WICKES
SOLD

Reason for revision: ATP4

Publication date: 2004-05-08

Date of revision: 2015-06-24

Revision number: 0103

Product number: 46215

12 / 12