

Wickes High Strength Contact Adhesive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Wickes High Strength Contact Adhesive
 Registration number REACH : Not applicable (mixture)
 Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Adhesive

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

SOUDAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 ☐ +32 14 42 65 14
 msds@soudal.com

Manufacturer of the product

SOUDAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 ☐ +32 14 42 65 14
 msds@soudal.com

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):
 +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 2	H225: Highly flammable liquid and vapour.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

2.2. Label elements



Contains: cyclohexane; acetone; hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane; ethyl acetate.

Signal word : Danger

H-statements

H225 : Highly flammable liquid and vapour.
 H319 : Causes serious eye irritation.
 H315 : Causes skin irritation.
 H336 : May cause drowsiness or dizziness.
 H411 : Toxic to aquatic life with long lasting effects.

Wickes High Strength Contact Adhesive

P-statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P261	Avoid breathing vapours/mist.
P273	Avoid release to the environment.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

- This product is not to be used under conditions of poor ventilation.
- This product is not to be used for carpet laying.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
cyclohexane 01-2119463273-41	110-82-7 203-806-2	10%<C<25%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)(10)	Mono-constituent
acetone 01-2119471330-49	67-64-1 200-662-2	10%<C<25%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Mono-constituent
butanone 01-2119457290-43	78-93-3 201-159-0	10%<C<25%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Mono-constituent
hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane 01-2119475514-35		7.5%<C<20%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	UVCB
ethyl acetate 01-2119475103-46	141-78-6 205-500-4	10%<C<20%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Mono-constituent
n-hexane 01-2119480412-44	110-54-3 203-777-6	0.3%<C<1%	Flam. Liq. 2; H225 Repr. 2; H361f Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(8)(10)	Mono-constituent

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(8) Specific concentration limits, see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

2 / 26

Wickes High Strength Contact Adhesive

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not give milk/oil to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Feeling of weakness. Irritation of the respiratory tract. Nausea. Vomiting. Headache. Central nervous system depression. Dizziness. Narcosis. Excited/restless. Drunkenness. Disturbed motor response. Respiratory difficulties. Disturbances of consciousness.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue.

After ingestion:

Dry/sore throat. Risk of aspiration pneumonia. Gastrointestinal complaints. Central nervous system depression. Symptoms similar to those listed under inhalation.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Polyvalent foam. BC powder. Carbon dioxide. MAJOR FIRE: Water.

5.1.2 Unsuitable extinguishing media:

Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

On heating/burning: release of carbon monoxide - carbon dioxide.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Do not move the load if exposed to heat. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Face-shield. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Face-shield. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Try to reduce evaporation. Prevent soil and water pollution. Prevent spreading in sewers. Use appropriate containment to avoid environmental contamination.

6.3. Methods and material for containment and cleaning up

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

3 / 26

Wickes High Strength Contact Adhesive

Take up liquid spill into a non combustible material e.g.: sand, earth, vermiculite. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Observe normal hygiene standards. Keep container tightly closed. Remove contaminated clothing immediately. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Store in a cool area. Ventilation at floor level. Fireproof storeroom. Keep only in the original container. Meet the legal requirements. Max. storage time: 18 month(s).

7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

Tin.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m ³
Butanone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	600 mg/m ³
	Short time value (Indicative occupational exposure limit value)	300 ppm
	Short time value (Indicative occupational exposure limit value)	900 mg/m ³
Cyclohexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	700 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	72 mg/m ³

Belgium

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

4 / 26

Wickes High Strength Contact Adhesive

2-Butanone	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	600 mg/m ³
	Short time value	300 ppm
	Short time value	900 mg/m ³
Acétate d'éthyle	Time-weighted average exposure limit 8 h	400 ppm
	Time-weighted average exposure limit 8 h	1461 mg/m ³
Acétone	Time-weighted average exposure limit 8 h	500 ppm
	Time-weighted average exposure limit 8 h	1210 mg/m ³
	Short time value	1000 ppm
	Short time value	2420 mg/m ³
Cyclohexane	Time-weighted average exposure limit 8 h	100 ppm
	Time-weighted average exposure limit 8 h	350 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	72 mg/m ³

The Netherlands

2-Butanon	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	197 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	590 mg/m ³
	Short time value (Public occupational exposure limit value)	300 ppm
	Short time value (Public occupational exposure limit value)	900 mg/m ³
Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	501 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m ³
	Short time value (Public occupational exposure limit value)	1002 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m ³
Cyclohexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	700 mg/m ³
	Short time value (Public occupational exposure limit value)	400 ppm
	Short time value (Public occupational exposure limit value)	1400 mg/m ³
Ethylacetaat	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	150 ppm
	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	550 mg/m ³
	Short time value (Private occupational exposure limit value)	300 ppm
	Short time value (Private occupational exposure limit value)	1100 mg/m ³
n-Hexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	72 mg/m ³
	Short time value (Public occupational exposure limit value)	40 ppm
	Short time value (Public occupational exposure limit value)	144 mg/m ³

France

Acétate d'éthyle	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	400 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1400 mg/m ³
Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m ³
Cyclohexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	700 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	375 ppm
	Short time value (VL: Valeur non réglementaire indicative)	1300 mg/m ³

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

5 / 26

Wickes High Strength Contact Adhesive

Méthyléthylcétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	600 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	300 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	900 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	72 mg/m ³

Germany

Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m ³
Butanon	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	600 mg/m ³
Cyclohexan	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	700 mg/m ³
Ethylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	400 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1500 mg/m ³
n-Hexan	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	180 mg/m ³

UK

Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m ³
Butan-2-one (methyl ethyl ketone)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	899 mg/m ³
Cyclohexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	100 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	350 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1050 mg/m ³
Ethyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm
	Short time value (Workplace exposure limit (EH40/2005))	400 ppm
n-Hexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	20 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	72 mg/m ³

USA (TLV-ACGIH)

Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Cyclohexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	100 ppm
Ethyl acetate	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	400 ppm
Methyl ethyl ketone (MEK)	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	300 ppm
n-Hexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
-----------------	-----------------------------------------	---------	--------------------------------------------------------------------------------------------

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

6 / 26

Wickes High Strength Contact Adhesive

Butanon (2-Butanon; Ethylmethylketon) (Butanon (2-Butanon))	Urin: expositionsende, bzw. schichtende	2 mg/l	05/2015 DFG
Cyclohexan (1,2-Cyclohexandiol (nach Hydrolyse))	Urin: bei langzeitexposition: nach mehreren vorangegangenen schichten expositionsende, bzw. schichtende	150 mg/g Kreatinin	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
Hexan (n-Hexan) (2,5-Hexandion plus 4,5-Dihydroxy-2-Hexanon (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende	5 mg/l	5/2013 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG

UK

Butan-2-one (butan-2-one)	Urine: post shift	70 µmol/L	
---------------------------	-------------------	-----------	--

USA (BEI-ACGIH)

Acetone (Acetone)	Urine: end of shift	20 mg/L	Nonspecific - Intended changes
Acetone (Acetone)	Urine: end of shift	25 mg/L	
Methyl ethyl ketone (MEK)	urine: end of shift	2 mg/L	
n-Hexane (2,5-Hexanedion)	Urine: end of shift at end of workweek	0,4 mg/L	

8.1.2 Sampling methods

If applicable and available it will be listed below.

2-Butanone (MEK) (Methyl ethyl ketone)	NIOSH	2500
2-Butanone (Methyl ethyl ketone)	OSHA	84
2-Butanone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
2-Butanone (Volatile Organic compounds)	NIOSH	2549
2-Butanone	OSHA	1004
2-Butanone	OSHA	13
Acetone (ketones 1)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Acetone	OSHA	69
Cyclohexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
Cyclohexane	NIOSH	95-117
Cyclohexane	OSHA	7
Ethyl acetate (Volatile Organic compounds)	NIOSH	2549
Ethyl Acetate	NIOSH	1457
Ethyl Acetate	OSHA	7
MEK	NIOSH	8002
Methyl Ethyl Ketone (ketones I)	NIOSH	2555
Methyl Ethyl Ketone	OSHA	16
n-Hexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
n-Hexane (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
n-Hexane (Volatile Organic compounds)	NIOSH	2549
n-Hexane	NIOSH	95-117
n-Hexane	OSHA	7

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

cyclohexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	700 mg/m ³	
	Acute systemic effects inhalation	700 mg/m ³	
	Long-term local effects inhalation	700 mg/m ³	
	Acute local effects inhalation	700 mg/m ³	
	Long-term systemic effects dermal	2016 mg/kg bw/day	

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1210 mg/m ³	
	Acute local effects inhalation	2420 mg/m ³	
	Long-term systemic effects dermal	186 mg/kg bw/day	

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

7 / 26

Wickes High Strength Contact Adhesive

butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	600 mg/m ³	
	Long-term systemic effects dermal	1161 mg/kg bw/day	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2035 mg/m ³	
	Long-term systemic effects dermal	773 mg/kg bw/day	

ethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	734 mg/m ³	
	Acute systemic effects inhalation	1468 mg/m ³	
	Long-term local effects inhalation	734 mg/m ³	
	Acute local effects inhalation	1468 mg/m ³	
	Long-term systemic effects dermal	63 mg/kg bw/day	

n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	75 mg/m ³	
	Long-term systemic effects dermal	11 mg/kg bw/day	

DNEL/DMEL - General population

cyclohexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	206 mg/m ³	
	Acute systemic effects inhalation	412 mg/m ³	
	Long-term local effects inhalation	206 mg/m ³	
	Acute local effects inhalation	412 mg/m ³	
	Long-term systemic effects dermal	1186 mg/kg bw/day	
	Long-term systemic effects oral	59.4 mg/kg bw/day	

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects inhalation	200 mg/m ³	
	Long-term systemic effects oral	62 mg/kg bw/day	

butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	106 mg/m ³	
	Long-term systemic effects dermal	412 mg/kg bw/day	
	Long-term systemic effects oral	31 mg/kg bw/day	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	608 mg/m ³	
	Long-term systemic effects dermal	699 mg/kg bw/day	
	Long-term systemic effects oral	699 mg/kg bw/day	

ethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	367 mg/m ³	
	Acute systemic effects inhalation	734 mg/m ³	
	Long-term local effects inhalation	367 mg/m ³	
	Acute local effects inhalation	734 mg/m ³	
	Long-term systemic effects dermal	37 mg/kg bw/day	
	Long-term systemic effects oral	4.5 mg/kg bw/day	

n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	16 mg/m ³	
	Long-term systemic effects dermal	5.3 mg/kg bw/day	
	Long-term systemic effects oral	4 mg/kg bw/day	

PNEC

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

8 / 26

Wickes High Strength Contact Adhesive

cyclohexane

Compartments	Value	Remark
Fresh water	0.207 mg/l	
Marine water	0.207 mg/l	
Aqua (intermittent releases)	0.207 mg/l	
STP	3.24 mg/l	
Fresh water sediment	3.627 mg/kg sediment dw	
Marine water sediment	3.627 mg/kg sediment dw	
Soil	2.99 mg/kg soil dw	

acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	
STP	100 mg/l	

butanone

Compartments	Value	Remark
Fresh water	55.8 mg/l	
Marine water	55.8 mg/l	
Aqua (intermittent releases)	55.8 mg/l	
STP	709 mg/l	
Fresh water sediment	284.74 mg/kg sediment dw	
Marine water sediment	284.7 mg/kg sediment dw	
Soil	22.5 mg/kg soil dw	
Food	1000 mg/kg food	

ethyl acetate

Compartments	Value	Remark
Fresh water	0.24 mg/l	
Marine water	0.024 mg/l	
Aqua (intermittent releases)	1.65 mg/l	
STP	650 mg/l	
Fresh water sediment	1.15 mg/kg sediment dw	
Marine water sediment	0.115 mg/kg sediment dw	
Soil	0.148 mg/kg soil dw	
Oral	0.2 g/kg food	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges. Work under local exhaust/ventilation.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

9 / 26

Wickes High Strength Contact Adhesive

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Viscous
Odour	Characteristic odour
Odour threshold	No data available
Colour	Colourless
Particle size	No data available
Explosion limits	1 - 7.4 vol %
Flammability	Highly flammable liquid and vapour.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	< -50 °C ; 1013 hPa
Boiling point	60 °C - 95 °C ; 1013 hPa
Flash point	-25 °C ; 1013 hPa
Evaporation rate	No data available
Relative vapour density	No data available
Vapour pressure	240 hPa ; 20 °C
Solubility	water ; 0.02 g/100 ml ; 20 °C
Relative density	No data available
Decomposition temperature	No data available
Auto-ignition temperature	260 °C ; 1013 hPa
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Absolute density	No data available
------------------	-------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from naked flames/heat. Insufficient ventilation: keep naked flames/sparks away. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: take precautions against electrostatic charges.

10.5. Incompatible materials

(strong) acids, (strong) bases.

10.6. Hazardous decomposition products

On heating/burning: release of carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

Wickes High Strength Contact Adhesive

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LC50		≥ 2000 mg/kg bw		Rat	Calculated value	
Dermal	LD50		≥ 2000 mg/kg bw		Rabbit	Calculated value	
Inhalation	LC50		≥ 5 mg/l/4h		Rat	Calculated value	
Inhalation (vapours)	ATE		5 mg/l/4h			Calculated value	

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

10 / 26

Wickes High Strength Contact Adhesive

Inhalation (mist)	ATE		5 mg/l/4h			Calculated value	
-------------------	-----	--	-----------	--	--	------------------	--

cyclohexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw		Rabbit (male/female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 32.88 mg/l air	4 h	Rat (male/female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 19.07 mg/l	4 h	Rat (male/female)	Experimental value	

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	20000 mg/kg		Rabbit (male)	Experimental value	
Dermal	LD50		> 7426 mg/kg bw		Rabbit (female)	Weight of evidence	
Inhalation (vapours)	LC50	Other	76 mg/l	4 h	Rat (female)	Experimental value	
Inhalation (vapours)	LCL0	Other	16000 ppm	4 h	Rat	Experimental value	

butanone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	2193 mg/kg bw		Rat (male/female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 10 ml/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)						Data waiving	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Other	> 5840 mg/kg bw		Rat (male/female)	Read-across	
Dermal	LD50	Other	> 2800 mg/kg bw	24 week(s)	Rat (male/female)	Similar product	
Inhalation (vapours)	LC50	Other	> 25.2 mg/l	4 h	Rat (male/female)	Experimental value	

ethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	10200 mg/kg bw		Rat (female)	Experimental value	
Dermal	LD50	24 hour cuff method	> 20000 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC0	Equivalent to OECD 403	29.3 mg/l	4 h	Rat	Experimental value	

n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	16000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5000 ppm	24 h	Rat (male)	Experimental value	

Judgement of the mixture is based on test data on the mixture as a whole

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Wickes High Strength Contact Adhesive

No (test)data on the mixture available

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

11 / 26

Wickes High Strength Contact Adhesive

cyclohexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Slightly irritating	Equivalent to OECD 405		1 hour	Rabbit	Experimental value	
Skin	Not irritating	EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Inhalation	Irritating					Literature study	

acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405		24; 48; 72 hours	Rabbit	Weight of evidence	
Skin	Not irritating	Other	3 day(s)	24; 48; 72 hours	Guinea pig	Weight of evidence	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature	

butanone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single exposure
Skin	Not irritating	OECD 404	4 h	4; 24; 48; 72 hours	Rabbit	Read-across	

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Other			Rabbit	Read-across	
Skin	Irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

ethyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating; category 2					Annex VI	
Skin	Slightly irritating	Equivalent to OECD 404	24 h	24; 48; 72 hours	Rabbit	Experimental value	

n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		72 hours	Rabbit	Read-across	
Skin	Irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Read-across	

Classification is based on the relevant ingredients

Conclusion

- Causes skin irritation.
- Causes serious eye irritation.
- Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

Wickes High Strength Contact Adhesive

No (test) data on the mixture available

cyclohexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	EU Method B.6		24; 48 hours	Guinea pig (male/female)	Experimental value	

acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test		48 hours	Hamster (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Literature	

butanone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406		24; 48 hours	Guinea pig (female)	Experimental value	

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Wickes High Strength Contact Adhesive

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (male/female)	Read-across	

ethyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Intradermal	Not sensitizing	OECD 406		24; 48 hours	Guinea pig (female)	Experimental value	

n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse	Read-across	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

Wickes High Strength Contact Adhesive

No (test)data on the mixture available

cyclohexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	EPA OPPTS 870.3465	7000 ppm		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	20 mg/l		No effect	13 week(s)	Mouse (male/female)	Experimental value
Dermal								Not relevant, expert judgement
Inhalation (vapours)	NOAEC	Other	19000 ppm		No effect	8 week(s)	Rat (male)	Literature
Inhalation (vapours)		Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Inconclusive, insufficient data

butanone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	5041 ppm		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)			STOT SE cat.3	Central nervous system	Drowsiness, dizziness			Annex VI

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation (vapours)	NOAEC	Other	4200 mg/m ³ air		No effect	3 days (8h/day)	Rat (male)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	6646 ppm		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	2220 ppm		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Read-across
Inhalation (vapours)	LOAEC	Other	14 g/m ³	Central nervous system	Behavioural disturbances	3 days (8h/day)	Rat (male)	Experimental value

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

13 / 26

Wickes High Strength Contact Adhesive

ethyl acetate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	EPA OTS 795.2600	900 mg/kg bw/day	General	No effect	90 day(s) - 92 day(s)	Rat (male/female)	Experimental value
Oral (stomach tube)	LOAEL	EPA OTS 795.2600	3600 mg/kg bw/day	General	Body weight, organ weight, food consumption	90 day(s) - 92 day(s)	Rat (male/female)	Experimental value
Inhalation	NOEC	EPA OTS 798.2450	350 ppm	General	No adverse systemic effects	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Subchronic toxicity test	567 mg/kg bw/day - 1135 mg/kg bw/day		No effect	13 weeks (5 days/week)	Rat (male)	Experimental value
Oral (stomach tube)	LOAEL	Subchronic toxicity test	3956 mg/kg bw/day	Central nervous system	neurotoxic effects	17 weeks (5 days/week)	Rat (male)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	LOAEC	Subchronic toxicity test	3000 ppm	Central nervous system	Impairment of the nervous system	16 weeks (daily)	Rat (male)	Experimental value
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Literature study

Classification is based on the relevant ingredients

Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

Mutagenicity (in vitro)

Wickes High Strength Contact Adhesive

No (test) data on the mixture available

cyclohexane

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value

acetone

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
Negative	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value

butanone

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 473	Rat liver cells	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 473	Rat liver cells	No effect	Read-across
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across
Negative	OECD 476		No effect	Read-across

ethyl acetate

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

14 / 26

Wickes High Strength Contact Adhesive

n-hexane

Result	Method	Test substrate	Effect	Value determination
Negative	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

Mutagenicity (in vivo)

Wickes High Strength Contact Adhesive

No (test)data on the mixture available

cyclohexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 475	5 days (6h/day)	Rat (male/female)	Bone marrow	Experimental value

acetone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative		13 week(s)	Mouse (male/female)		Literature

butanone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474		Mouse (male/female)		Experimental value

ethyl acetate

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474		Mouse (male)		Experimental value

n-hexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative		8 weeks (6h/day, 5 days/week)	Mouse (male)		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

Wickes High Strength Contact Adhesive

No (test)data on the mixture available

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Other	79 mg	51 week(s)	Mouse (female)	No effect		Literature

n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	3000 ppm	104 weeks (6h/day, 5 days/week)	Mouse (female)	No carcinogenic effect		Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h/day, 5 days/week)	Mouse (female)	Tumor formation	Liver	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h/day, 5 days/week)	Mouse (male)	No carcinogenic effect		Read-across

Judgement is based on the relevant ingredients

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

Wickes High Strength Contact Adhesive

No (test)data on the mixture available

Wickes High Strength Contact Adhesive

cyclohexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	7000 ppm	10 days (6h/day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEC	Equivalent to OECD 414	2000 ppm	10 days (6h/day)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEC	Equivalent to OECD 416	7000 ppm	> 11 weeks (6h/day, 5 days/week)	Rat (male/female)	No effect		Experimental value

acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	11000 ppm	6 days (gestation, daily) - 19 days (gestation, daily)	Rat (male/female)			Experimental value
Effects on fertility	NOAEL	Other	900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Literature

butanone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h/day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h/day)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEL	Equivalent to OECD 416	1644 mg/kg bw/day - 1771 mg/kg bw/day		Rat (male/female)	No effect		Read-across

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Other	≥ 1200 ppm	10 days (6h/day)	Rat	No effect		Read-across
	NOAEL	Equivalent to OECD 414	3000 ppm	10 days (6h/day)	Mouse	No effect		Read-across
	LOAEL	Equivalent to OECD 414	9000 ppm	10 days (6h/day)	Mouse	Minor skeletal variations	Skeleton	Read-across
Maternal toxicity	NOAEC		1200 ppm		Rat (female)	No effect		Read-across
	NOAEL	Equivalent to OECD 414	900 ppm	10 days (6h/day)	Rat (female)	No effect		Read-across
	LOAEL	Equivalent to OECD 414	3000 ppm	10 days (6h/day)	Rat (female)	Lung tissue affection/degeneration	Lungs	Read-across
Effects on fertility	NOAEL (P/F1)	Equivalent to OECD 416	9000 ppm		Rat (male/female)	No effect		Read-across

ethyl acetate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	> 3600 mg/kg bw/day	7 day(s)	Mouse	No effect	Foetus	Read-across
Maternal toxicity	NOAEL	Equivalent to OECD 414	2200 mg/kg bw/day	8 days (gestation, daily) - 14 days (gestation, daily)	Mouse	No effect		Read-across
	LOAEL	Equivalent to OECD 414	3600 mg/kg bw/day	8 days (gestation, daily) - 14 days (gestation, daily)	Mouse	Mortality	General	Read-across
Effects on fertility	NOAEL	Equivalent to OECD 416	20700 mg/kg bw/day	13 weeks (6h/day, 5 days/week)	Mouse (male/female)	No effect		Experimental value

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

16 / 26

Wickes High Strength Contact Adhesive

n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h/day)	Rat	No effect		Experimental value
Maternal toxicity	NOAEC	Equivalent to OECD 414	3000 ppm	10 days (gestation, 6h/day)	Rat	No effect		Experimental value
	LOAEL	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h/day)	Rat	Weight gain		Experimental value
Effects on fertility	NOAEC	Equivalent to OECD 416	9000 ppm	≥ 13 weeks (6h/day, 5 days/week)	Rat (male/female)	No effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

Wickes High Strength Contact Adhesive

No (test)data on the mixture available

cyclohexane

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
NOAEC	Other	2000 ppm		neurotoxic effects	6 h	Rat (male)	Experimental value
LOAEC	Other	7000 ppm		neurotoxic effects	6 h	Rat (male)	Experimental value

acetone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature study

butanone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
	Equivalent to OECD 404		Skin	Skin dryness or cracking			Read-across

ethyl acetate

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature

Chronic effects from short and long-term exposure

Wickes High Strength Contact Adhesive

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Skin rash/inflammation. Dry/sore throat. Headache. Nausea. Feeling of weakness. Possible inflammation of the respiratory tract.

SECTION 12: Ecological information

12.1. Toxicity

Wickes High Strength Contact Adhesive

No (test)data on the mixture available

Wickes High Strength Contact Adhesive

cyclohexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	4.53 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	EC50	Equivalent to OECD 202	0.9 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	Equivalent to OECD 201	9.317 mg/l	72 h	Pseudokirchneriella subcapitata			Experimental value; GLP
	EC50	OECD 201	9.317 mg/l	72 h	Pseudokirchneriella subcapitata			Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea								Data waiving
Toxicity aquatic micro-organisms	IC50		29 mg/l	15 h	Aerobic micro-organisms			Experimental value; Nominal concentration

acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	EU Method C.1	5540 mg/l	96 h	Salmo gairdneri	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	LC50	Other	12600 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50		> 7000 mg/l	96 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Nominal concentration

butanone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	2993 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	308 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	ErC50	OECD 201	1972 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	EC0	DIN 38412-8	1150 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	11.4 mg/l WAF	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	3.0 mg/l WAF	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	ErC50	OECD 201	30 mg/l WAF - 100 mg/l WAF	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOELR		2.045 mg/l	28	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOEC	OECD 211	0.17 mg/l WAF	21 day(s)	Daphnia magna	Static system	Fresh water	Read-across
	LOEC	OECD 211	0.32 mg/l WAF	21 day(s)	Daphnia magna	Static system	Fresh water	Read-across
Toxicity aquatic micro-organisms	EL50		35.57 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth inhibition
	NOELR		7.959 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth inhibition

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Wickes High Strength Contact Adhesive

ethyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	US EPA	230 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value
Acute toxicity crustacea	EC50		154 mg/l	48 h	Daphnia magna			Literature
Toxicity algae and other aquatic plants	NOEC	OECD 201	> 100 mg/l	72 h	Scenedesmus subspicatus	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	ECOSAR v1.00	6.3 mg/l	32 day(s)	Pisces		Fresh water	QSAR
	NOEC	OECD 210	< 9.65 mg/l	32 day(s)	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Growth rate
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	2.4 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC50		5870 mg/l	15 minutes	Photobacterium phosphoreum	Static system	Salt water	Experimental value; Inhibitory

n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		13.3 mg/l	96 h	Oncorhynchus mykiss		Fresh water	Read-across; Nominal concentration
Acute toxicity crustacea	EL50		23.22 mg/l	48 h	Daphnia magna		Fresh water	Read-across; Nominal concentration
Toxicity algae and other aquatic plants	EL50		9.902 mg/l	72 h	Pseudokirchneriella subcapitata		Fresh water	Read-across; Growth rate
Long-term toxicity fish	NOELR		2.976 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	Read-across; Nominal concentration
Long-term toxicity aquatic crustacea	NOELR		5.195 mg/l	21 day(s)	Daphnia magna		Fresh water	Read-across; Nominal concentration

Classification of the mixture is based on the relevant ingredients and on application of the summation method

Conclusion

Toxic to aquatic organisms

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

cyclohexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	77 %; GLP	28 day(s)	Experimental value

Half-life soil (t1/2 soil)

Method	Value	Primary degradation/mineralisation	Value determination
	28 day(s) - 180 day(s)		Literature study

acetone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B: CO2 Evolution Test	90.9 %	28 day(s)	Experimental value

butanone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D: Closed Bottle Test	98 %; GLP	28 day(s)	Experimental value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	98 %; GLP	28 day(s)	Experimental value

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

19 / 26

Wickes High Strength Contact Adhesive

ethyl acetate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B: CO2 Evolution Test	93.9 %	28 day(s)	Experimental value
OECD 301D: Closed Bottle Test	100 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
	40 h	500000 /cm ³	QSAR

n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	98 %, GLP	28 day(s)	Read-across

Conclusion

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

Wickes High Strength Contact Adhesive

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

cyclohexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	31 - 129	8 week(s)	Cyprinus carpio	Literature study

Log Kow

Method	Remark	Value	Temperature	Value determination
Other		3.44	25 °C	Experimental value

acetone

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.69		Pisces	

BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFWIN	3			Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.24		Test data

butanone

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		0.3	40 °C	Experimental value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Log Kow

Method	Remark	Value	Temperature	Value determination
		> 3		

ethyl acetate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		30	3 day(s)	Leuciscus idus	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
EPA OPPTS 830.7560		0.68	25 °C	Experimental value

n-hexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	Other	501.187		Pimephales promelas	QSAR

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		4	20 °C	Experimental value

Conclusion

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Wickes High Strength Contact Adhesive

Contains bioaccumulative component(s)

12.4. Mobility in soil

cyclohexane

(log) Koc

Parameter	Method	Value	Value determination
log Koc	Other	2.89	QSAR

butanone

(log) Koc

Parameter	Method	Value	Value determination
log Koc		1.53	Calculated value

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	98 %	0 %	0.9 %	0 %	1.3 %	Calculated value

ethyl acetate

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	51.3 %	0 %	0.27 %	13.3 %	35.3 %	Calculated value

n-hexane

(log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	QSAR

Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
1.8 atm m ³ /mol		25 °C		Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

Wickes High Strength Contact Adhesive

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

cyclohexane

Ground water

Ground water pollutant

butanone

Ground water

Ground water pollutant

ethyl acetate

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

21 / 26

Wickes High Strength Contact Adhesive

13.1.2 Disposal methods

Incinerate under surveillance with energy recovery. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

14.3. Transport hazard class(es)

Hazard identification number	
Class	3
Classification code	F1

14.4. Packing group

Packing group	III
Labels	3

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
------------------------------------------	-----

14.6. Special precautions for user

Special provisions	
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Specific mention	Viscous liquid with a flash point lower than 23°C, which meets the conditions indicated in 2.2.3.1.4 of ADR

Rail (RID)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

14.3. Transport hazard class(es)

Hazard identification number	33
Class	3
Classification code	F1

14.4. Packing group

Packing group	III
Labels	3

14.5. Environmental hazards

Environmentally hazardous substance mark	yes
------------------------------------------	-----

14.6. Special precautions for user

Special provisions	
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Specific mention	Viscous liquid with a flash point lower than 23°C, which meets the conditions indicated in 2.2.3.1.4 of RID

Inland waterways (ADN)

14.1. UN number

UN number	1133
-----------	------

14.2. UN proper shipping name

Proper shipping name	Adhesives
----------------------	-----------

14.3. Transport hazard class(es)

Class	3
Classification code	F1

14.4. Packing group

Packing group	III
---------------	-----

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

22 / 26

Wickes High Strength Contact Adhesive

Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Specific mention	Viscous liquid with a flash point lower than 23°C, which meets the conditions indicated in 2.2.3.1.4 of ADN

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1133
14.2. UN proper shipping name	
Proper shipping name	Adhesives
14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	III
Labels	3
14.5. Environmental hazards	
Marine pollutant	P
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	223
Special provisions	955
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Specific mention	Viscous liquid with a flash point lower than 23°C, which meets the conditions indicated in 2.3.2.3 of IMDG
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Annex II of MARPOL 73/78	Not applicable, based on available data

Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1133
14.2. UN proper shipping name	
Proper shipping name	Adhesives
14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	III
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A3
Limited quantities: maximum net quantity per packaging	10 L
Specific mention	Viscous liquid with a flash point lower than 23°C, which meets the conditions indicated in 3.3.3.1 of ICAO

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
≥ 50 %	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

23 / 26

Wickes High Strength Contact Adhesive

<ul style="list-style-type: none"> · cyclohexane · acetone · butanone · hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane · ethyl acetate · n-hexane 	<p>Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>1. Shall not be used in:</p> <ul style="list-style-type: none"> — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects. <p>2. Articles not complying with paragraph 1 shall not be placed on the market.</p> <p>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <ul style="list-style-type: none"> — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304. <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</p> <p>6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.</p> <p>7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>
<ul style="list-style-type: none"> · cyclohexane · acetone · butanone · hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane · ethyl acetate · n-hexane 	<p>Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.</p>	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:</p> <p>"For professional users only".</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
<ul style="list-style-type: none"> · cyclohexane 	<p>Cyclohexane</p>	<p>1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g.</p> <p>2. Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.</p> <p>3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows:</p> <ul style="list-style-type: none"> — This product is not to be used under conditions of poor ventilation. — This product is not to be used for carpet laying."

National legislation Belgium

Wickes High Strength Contact Adhesive

No data available

National legislation The Netherlands

Wickes High Strength Contact Adhesive

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 04
----------------------------------------	-----------------------------------------

butanone

Huidopname (wettelijk)	2-Butanon; H
------------------------	--------------

n-hexane

SZW - Lijst van voor de voortplanting giftige stoffen (vruchtbaarheid)	n-Hexaan; 2; Suspected of damaging fertility.
------------------------------------------------------------------------	-----------------------------------------------

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

24 / 26

Wickes High Strength Contact Adhesive

National legislation France

Wickes High Strength Contact Adhesive

No data available

butanone

VME - Risque de pénétration percutanée	Méthyléthylcétone; PP
----------------------------------------	-----------------------

n-hexane

Catégorie toxique pour la reproduction	n-Hexane; R2
----------------------------------------	--------------

National legislation Germany

Wickes High Strength Contact Adhesive

WGK	2; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	-----------------------------------------------------------------------------------------------------------------------------------------------------------------

cyclohexane

TA-Luft	5.2.5; I
---------	----------

acetone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Aceton; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

butanone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Butanon; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	Butanon; H; Hautresorptiv

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

TA-Luft	5.2.5; I
---------	----------

ethyl acetate

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Ethylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

n-hexane

TA-Luft	5.2.5; I
TRGS900 - Risiko der Fruchtschädigung	n-Hexan; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

National legislation United Kingdom

Wickes High Strength Contact Adhesive

No data available

butanone

Skin absorption	Butan-2-one (methyl ethyl ketone); Sk
-----------------	---------------------------------------

Other relevant data

Wickes High Strength Contact Adhesive

No data available

acetone

TLV - Carcinogen	Acetone; A4
------------------	-------------

n-hexane

Skin absorption	n-Hexane; Skin; Danger of cutaneous absorption
-----------------	------------------------------------------------

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

25 / 26

Wickes High Strength Contact Adhesive

(*)	INTERNAL CLASSIFICATION BY BIG
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

M-factor

cyclohexane	1	Acute	ECHA
-------------	---	-------	------

Specific concentration limits CLP

n-hexane	C ≥ 5 %	STOT RE 2; H373	CLP Annex VI (ATP 0)
----------	---------	-----------------	----------------------

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 7.2.1

Publication date: 2007-05-09

Date of revision: 2017-01-05

Revision number: 0301

Product number: 45108

26 / 26