



Wickes Hi-Tack Flashing

SELF-ADHESIVE FLASHING

Date: 01 September 2021

Fact Sheet No.: TDS00309

YOUR SMART ADVANTAGES

- Waterproofs
- Seals permanently
- Self-adhesive

USES

Wickes Hi-Tack Flashing is a self-adhesive sealing bitumen strip, which bonds instantly to provide a permanent, watertight seal. It is suitable for new build, patching and repair.

It bonds to most building materials including brick, masonry, slates, concrete roof tiles, wood, metal, concrete, terracotta tiles, roofing felt and rigid plastics.

It's suitable for repairing lead flashing, sealing valley gutters, mending leaks in drainpipes & guttering and repairing roofing felt joints on flat roofs.

PRODUCT CHARACTERISTICS

Colour	Grey finish
Form	Resin modified bituminous mastic in roll form. Adhesive surface is protected by a removable release backing
Weight	1.6kg per square metre
Composition	Resin modified bituminous mass
Product Codes	30813126 100mm x 3.75m x 6 rolls 30813132 150mm x 3.75m x 4 rolls 30813128 225mm x 3.75m x 4 rolls 30813129 100mm x 10m x 3 rolls 30813130 150mm x 10m x 2 rolls

	30813131 225mm x 10m x 2 rolls
Storage/Shelf Life	Store for up to 24 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C In cold weather (below +15°C) application may be easier by warming the surfaces and storing Wickes Hi-Tack Flashing in a warm place prior to use
Temperature Resistance	-10°C to +100°C (depending on operating conditions)

DIRECTIONS FOR USE

IMPORTANT: Before using Wickes Hi-Tack Flashing, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Surfaces must be sound, clean, dry and free from surface contaminants such as grease, oil, rust, dirt, paint and loose materials.
2. Gaps, deep hollows and depressions greater than 3mm should be filled with an appropriate filler.
3. For improved adhesion on porous, rough or dusty surfaces, apply Wickes Hi-Tack Flashing Primer.
4. Using a dampened brush, apply Wickes Hi-Tack Flashing Primer according to the relevant data sheet. Allow to dry, but protect from rain or frost.
5. Do not leave the Wickes Hi-Tack Flashing Primer for more than 24 hours and therefore only coat an area sufficient for covering within the working day.

- Surfaces such as mineralised felt or textured brick may require two coats; apply the second coat when the first coat has dried.

APPLICATION

- In cold weather, application will be made easier by warming the surfaces and by storing Wickes Hi-Tack Flashing in a warm place prior to use. Do not apply if the surface temperature is below +5°C.
- Cut Wickes Hi-Tack Flashing to required length.
- Remove approximately 50mm of release backing paper and carefully position the sealing strip.
- To avoid creasing when applying Wickes Hi-Tack Flashing, hold the release backing paper firmly and remove it steadily from the sealing strip as the product is applied.
- Smooth gently into position using hand pressure only. Avoid excessive pressure.
- Using a seam roller or a piece of rounded wood, smooth the tape to ensure good overall contact and expel any air, especially on overlaps and at edges.
- When laying adjacent rolls, Wickes Hi-Tack Flashing should be overlapped by a minimum of 25mm for a watertight seal.
- Wickes Hi-Tack Flashing can be over-painted with conventional decorative paints, but a little staining may occur at the edges.
- Wickes Hi-Tack Flashing does not accommodate appreciable joint movement. For small movements, apply a strip of release film 50mm narrower than the Wickes Hi-Tack Flashing along the joint prior to the application of the Wickes Hi-Tack Flashing.
- For larger movement, polyethylene foam can be laid proud of the joint, enabling the web of supported flashing strip to accept the movement.
- Whilst Wickes Hi-Tack Flashing will not damage plastic sheets, it is important to bear in mind the high thermal movement of these materials. If long lengths of plastic are to be sealed use, 500mm lengths overlapped by 25mm to reduce the effect of the movement.

PRECAUTIONS IN USE

Wickes Hi-Tack Flashing may become brittle if enclosed in a cementitious mix. Wickes Hi-Tack Flashing is not resistant to attack by acidic or alkaline materials. Avoid using Wickes Hi-Tack Flashing where it will come into regular contact with solvents and oils. Wickes Hi-Tack Flashing is bituminous and must not come into contact with silicone sealants, flexible PVC or vinyl.

Always gently warm surfaces so that they are not too hot to touch. Do not warm the foil side of Wickes Hi-Tack Flashing. Do not overheat or melt the bitumen.

Wickes Hi-Tack Flashing is not intended to withstand vehicular traffic. It should not be used in areas where it may be walked upon.

As with most covering materials supplied in roll form, some batch-to-batch variation in colour can occur. If aesthetic appearance is important, users are advised to check that all rolls are of the same colour and batch number.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Wickes Hi-Tack Flashing, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com