

Gorilla Wood Glue

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name
CAS No.
EC No.
REACH Registration No.
Gorilla Wood Glue
Not applicable.
Not applicable.
Not known.

Unique Formula Identifier (UFI) Q800-U0RP-S00J-1PNP

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)
Uses Advised Against
Adhesives.
Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer

Company Identification Gorilla Glue Europe Ltd Address of Manufacturer 26 Eaton Avenue

Matrix Park Buckshaw Village Chorley Lancashire

Postal code PR7 7NA Telephone: 01257 241 319

E-mail Eucustomercare@gorillaglue.com

Office hours 08:30 - 17:00

Supplier

Company Identification GG Brands Netherlands B.V.

Address of Supplier

Lichttoren 32
5611 BJ

Eindhoven

Telephone +31 85 064 4029

E-mail Eucustomercare@gorillaglue.com

1.4 Emergency telephone number

Supplier Contact: Stuart Shotton Emergency Phone No. Stuart Shotton +44 (0)843 507 1200

Northern Ireland: NHS Direct Emergency Phone No. +44 111 (24 hours)

Republic of Ireland: NPIC Ireland

Emergency Phone No. +353 (0) 1 809 2166 (8am - 10pm)

SECTION 2: HAZARDS IDENTIFICATION

2.2 Label elements

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP) Skin Sens. 1A: May cause an allergic skin reaction.

Eye Irrit. 2 : Causes serious eye irritation.

According to Regulation (EC) No. 1272/2008 (CLP)

Product Name Gorilla Wood Glue

Hazard Pictogram(s)

GHS07

Signal Word(s) Warning

Hazard Statement(s) H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.



Gorilla Wood Glue

Precautionary Statement(s) P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children. P261: Avoid breathing vapours.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents in accordance with local, state or national legislation.

2.3 Other hazards

None known. **2.4 Additional Information**

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / REACH	%W/W	Hazard Statement(s)	Hazard
		Registration No.			Pictogram(s)
Acetic acid ethenyl ester, polymer with ethenol	25213-24-5	607-648-9	1-5	Eye Irrit. 2 H319	GHS07
1-phenoxypropan-2-ol		212-222-7 01-2119486566-23- XXXX	1-5	Eye Irrit. 2 H319	GHS07

Aluminum chloride, basic	1327-41-9	215-477-2 01-2119531563-43- XXXX	0.1-1.0	Met. Corr. 1 H290 Eye Dam. 1 H318	GHS05
Vinyl acetate	108-05-4	203-545-4 01-2119471301-50- XXXX	<0.1	Flam. Liq. 2 H225 Acute Tox. 4 H332 STOT SE 3 H335 Carc. 2 H351	GHS02 GHS08 GHS07
Methanol	67-56-1	200-659-6 01-2119392409-28- XXXX	<0.1	Flam. Liq. 2 H225 Acute Tox. 3 H301 Acute Tox. 3 H311 Acute Tox. 3 H331 STOT SE 1 H370	GHS02 GHS06 GHS08
Formaldehyde	50-00-0	200-001-8 01-2119488953-20- XXXX	<0.05	Acute Tox. 3 H301 Acute Tox. 3 H311 Skin Corr. 1B H314 Skin Sens. 1 H317 Acute Tox. 3 H331 Muta. 2 H341 Carc. 1B H350	GHS06 GHS05 GHS08 GHS07
2-methyl-2H-isothiazol-3-one	2682-20-4	220-239-6 01-2120764690-50- XXXX	<0.05	Acute Tox. 3 H301 Acute Tox. 3 H311 Skin Corr. 1B H314 Skin Sens. 1A H317 Eye Dam. 1 H318 Acute Tox. 2 H330 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 EUH071	GHS06 GHS05 GHS07 GHS09
Acetaldehyde	75-07-0	200-836-8 01-2119918285-36- XXXX	<0.01	Flam. Liq. 1 H224 Eye Irrit. 2 H319 STOT SE 3 H335 Muta. 2 H341 Carc. 1B H350	GHS02 GHS08 GHS07
Acrylamide	79-06-1	201-173-7 01-2119463260-48- XXXX	<0.01	Acute Tox. 3 H301 Acute Tox. 4 H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Acute Tox. 4 H332	GHS06 GHS08 GHS07



Gorilla Wood Glue

Muta. 1B H340
Carc. 1B H350
Repr. 2 H361f
STOT RE 1 H372

HAZARDOUS INGREDIENT(S)	CAS No.	Specific Concentration Limit		M-factor	ATE
Vinyl acetate	108-05-4				Acute Tox. 4 (H332): 11.000
Methanol	67-56-1		C>= 10.00 <= 100.00		Acute Tox. 3 (H301): 100.000
		STOT SE 2	C>= 3.00 < 10.00		Acute Tox. 3 (H311): 300.000
					Acute Tox. 3 (H331): 3.000
Formaldehyde	50-00-0	Skin Corr. 1B	C>= 25.00 <= 100.00		Acute Tox. 3 (H301): 100.000
		Skin Irrit. 2	C>= 5.00 < 25.00		Acute Tox. 3 (H311): 300.000
		Skin Sens. 1	C>= 0.20 <= 100.00		Acute Tox. 3 (H331): 3.000
		Eye Irrit. 2	C>= 5.00 < 25.00		
		STOT SE 3	C>= 5.00 <= 100.00		
2-methyl-2H-isothiazol-	2682-20-4	Skin Sens. 1A	C>= 0.0015 <= 100.00	Aquatic	Acute Tox. 3 (H301): 100.000
3-one				Acute 1: 10	Acute Tox. 3 (H311): 300.000
					Acute Tox. 2 (H330): 0.500
Acrylamide	79-06-1				Acute Tox. 3 (H301): 100.000
					Acute Tox. 4 (H312): 1100.000
					Acute Tox. 4 (H332): 11.000

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Skin Contact

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing. If symptoms develop, obtain medical attention. Wash with plenty of water. If skin irritation or rash occurs: Get medical

advice/attention.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Ingestion Wash out mouth with water. If symptoms develop, obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical,

foam or waterspray.

Unsuitable extinguishing media None.

5.2 Special hazards arising from the substance or mixture

None anticipated. May decompose in a fire, giving off toxic and irritant vapours.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained

breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Gorilla Wood Glue

Provide adequate ventilation. Wear appropriate personal protective equipment, avoid direct contact. Wash hands and exposed skin after use. Contaminated work clothing should not be allowed out of the workplace.

6.2 Environmental precautions

Do not release large quantities into the surface water or into drains.

6.3 Methods and material for containment and cleaning up

Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a

container for disposal.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

General hygiene measures for the handling of chemicals are applicable. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Avoid breathing vapours. Avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands and exposed skin thoroughly after handling. Take off contaminated clothing and wash it before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated place. Do not freeze.

Ambient.

Storage temperature Storage life Stable under normal conditions.

Incompatible materials Strong oxidising agents.

7.3 Specific end use(s)

Adhesives.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m³)	Note
Aluminium salts, soluble	1327-41-9		2			
Vinyl acetate	108-05-4	5	17.6	10	35.2	
Formaldehyde	50-00-0	2	2.5	2	2.5	Carc
Methanol	67-56-1	200	266	250	333	Sk
Acetaldehyde	75-07-0	20	37	50	92	Carc
Acrylamide	79-06-1		0.1			Carc SI

Region

United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark

Carc Sk

Capable of causing cancer and/or heritable genetic damage.

Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic

8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation. A washing facility/water for eye and skin cleaning

purposes should be present.

8.2.2. Personal protection equipment

Eye Protection Wear protective eye glasses for protection against liquid splashes.

Skin protection

Wear suitable gloves if prolonged skin contact is likely: Nitrile rubber.

Breakthrough time of the glove material: refer to the information provided by the

gloves' producer.

GORILLA

Date of Issue: 24-02-2022 Date of Revision: 12-06-2023

Gorilla Wood Glue

Respiratory protection

Normally no personal respiratory protection is necessary.

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Not applicable.

8.2.3. Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state Liquid.

Colour Brown.

Odour Ether-like.

Melting point/freezing point 0°C

Boiling point or initial boiling point and 100°C

boiling range

Flammability
Lower and upper explosion limit
Flash Point
Auto-ignition temperature
Decomposition Temperature
pH
Kinematic Viscosity
Non-flammable.
Not known.
Not known.
Not known.
Not known.
Not known.

Solubility Solubility (Water) : Dispersible.
Solubility (Other) : Not known.

Partition coefficient n-octanol/water (log Not known.

value)

Vapour pressure 23hPa @ 20°C
Density and/or relative density Not known.
Relative vapour density Not known.
Particle characteristics Not applicable.

9.2 Other information

None.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Heat and direct sunlight. Do not allow material to freeze.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Ingestion Low oral toxicity.

Calculated acute toxicity estimate (ATE): 86206.90000

Acute toxicity - Skin Contact Low acute toxicity.

Calculated acute toxicity estimate (ATE): 261904.77000

Acute toxicity - Inhalation Low acute toxicity.

GORILLA

Date of Issue: 24-02-2022 Date of Revision: 12-06-2023

Gorilla Wood Glue

Calculated acute toxicity estimate (ATE): 1434.78000

Skin corrosion/irritation Non-irritant.

Serious eye damage/irritation Causes serious eye irritation. No data.
Skin sensitization data May cause an allergic skin reaction. No data.

Germ cell mutagenicity There is no evidence of mutagenic potential.

Carcinogenicity No evidence of carcinogenic effects. Reproductive toxicity No evidence of reproductive effects.

Lactation Not classified.

STOT - single exposure None anticipated.

STOT - repeated exposure None anticipated.

Aspiration hazard Not classified.

11.2 Information on other hazards

Not known.

11.2.1 Endocrine disrupting properties

None known.

11.2.2 Other information

None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity - Aquatic invertebrates Low toxicity to invertebrates. Toxicity - Fish Low toxicity to fish.

Toxicity - Fish

Toxicity - Algae

Toxicity - Sediment Compartment

Toxicity - Terrestrial Compartment

Low toxicity to fish.

Low toxicity to algae.

Not classified.

Not classified.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

Dispersible in water. The product is predicted to have high mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dispose of with household waste. Dispose at suitable refuse site. Incineration

by an approved method could be considered.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

Not classified as hazardous for transport.

14.1 UN number or ID number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

Gorilla Wood Glue

14.5 Environmental hazards

Not classified as a Marine Pollutant.

14.6 Special precautions for user

Not known

14.7 Maritime transport in bulk according to IMO instruments

Not known

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Regulations - Authorisations and/or Restrictions On Use

Acrylamide (79-06-1), N(hydroxymethyl)acrylamide (924-42-5) Candidate List of Substances of Very

High Concern for Authorisation

REACH: ANNEX XIV list of substances Not listed

subject to authorisation

mixtures and articles

REACH: Annex XVII Restrictions on the Formaldehyde (50-00-0), Methanol (67-56-1), Acetaldehyde (75-07-0),

Acrylamide (79-06-1), Acetic acid ethenyl ester, polymer with ethenol (25213-24-5), manufacture, placing on the market and use of certain dangerous substances,

1-phenoxypropan-2-ol (770-35-4), Aluminum chloride, basic (1327-41-9), 2-methyl-2H-isothiazol-3-one (2682-20-4), Vinyl acetate (108-05-4)

Aluminum chloride, basic (1327-41-9), Vinyl acetate (108-05-4), Community Rolling Action Plan (CoRAP)

Formaldehyde (50-00-0), Methanol (67-56-1)

Regulation (EU) N° 2019/1021 of the European Parliament and of the Council

on persistent organic pollutants Regulation (EC) N° 1005/2009 on

substances that deplete the ozone layer Regulation (EU) N° 649/2012 of the European Parliament and of the Council

concerning the export and import of hazardous chemicals

National regulations

Not known.

Not listed

Not listed

Not listed

15.2 Chemical Safety Assessment

A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

3.11

LEGEND

Hazard Pictogram(s)



GHS07

GHS02: GHS: Flame GHS05: GHS: Corrosion

GHS06: GHS: Skull and crossbones GHS08: GHS: Health hazard GHS09: GHS: Environment

Hazard classification Flam. Liq. 1: Flammable liquid, Category 1

Flam. Liq. 2: Flammable liquid, Category 2

Met. Corr. 1 : Substance or mixture corrosive to metals, Category 1

Acute Tox. 3: Acute toxicity, Category 3 Acute Tox. 4: Acute toxicity, Category 4

Skin Corr. 1B: Skin corrosion/irritation, Category 1B Skin Irrit. 2: Skin corrosion/irritation, Category 2 Skin Sens. 1: Skin sensitization, Category 1 Skin Sens. 1A: Skin sensitization, Category 1A Eye Dam. 1 : Serious eye damage/irritation, Category 1 Eye Irrit. 2 : Serious eye damage/irritation, Category 2

Acute Tox. 2: Acute toxicity, Category 2

STOT SE 3: Specific target organ toxicity — single exposure, Category 3



Gorilla Wood Glue

Muta. 1B: Germ cell mutagenicity, Category 1B Muta. 2: Germ cell mutagenicity, Category 2 Carc. 1B: Carcinogenicity, Category 1B Carc. 2 : Carcinogenicity, Category 2 Repr. 2 : Reproductive toxicity, Category 2

STOT SE 1 : Specific target organ toxicity — single exposure, Category 1 STOT RE 1 : Specific target organ toxicity — repeated exposure, Category 1 Aquatic Acute 1: Hazardous to the aquatic environment. Acute. Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment, Chronic, Category 1

Hazard Statement(s)

H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H290: May be corrosive to metals.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H330: Fatal if inhaled.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H340: May cause genetic defects.

H341: Suspected of causing genetic defects.

H350: May cause cancer.

H351: Suspected of causing cancer.

H361f: Suspected of damaging fertility.

H370: Causes damage to organs.

H372: Causes damage to organs through prolonged or repeated exposure.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

EUH071: Corrosive to the respiratory tract.

Precautionary Statement(s)

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P261: Avoid breathing vapours.

P264: Wash hands and exposed skin thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace. P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P337+P313: If eye irritation persists: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ATE: Acute Toxicity Estimate CAS: Chemical Abstracts Service

CLP: Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substances and mixtures EC: European Community LTEL: Long term exposure limit

PBT: Persistent, Bioaccumulative and Toxic

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

STEL: Short term exposure limit STOT: Specific Target Organ Toxicity

vPvB: very Persistent and very Bioaccumulative

Key literature references and sources for Regulation (EC) No. 1272/2008 (CLP) data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves



Gorilla Wood Glue

of the suitability of the product for their own particular purpose. Gorilla Glue Europe Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Gorilla Glue Europe Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.