

BRIWAX ORIGINAL WAX POLISH

Page: 1

Compilation date: 18/03/2017 Revision date: 06/01/2020

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BRIWAX ORIGINAL WAX POLISH

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX United Kingdom Tel: +44 (0)208 450 4666 Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)208 450 4666 OFFICE HOURS ONLY

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336
Most important adverse effects: Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Label elements:	
Hazard statements:	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H361d: Suspected of damaging the unborn child.
	H373: May cause damage to organs through prolonged or repeated exposure.
Hazard pictograms:	GHS07: Exclamation mark
	GHS08: Health hazard



Signal words: Warning

BRIWAX ORIGINAL WAX POLISH

Page: 2

	P314: Get medical advice/attention if you feel unwell.
	P308+P313: IF exposed or concerned: Get medical advice/attention.
	breathing.
	P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for
	P302+P352: IF ON SKIN: Wash with plenty of water.
	P280: Wear protective gloves.
Precautionary statements:	P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TOLUENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-625-9	108-88-3	- Flam. Liq. 2: H225; Repr. 2: H		79.130%
			Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	

ection 4: First aid measures		
4.1. Description of first aid m	easures	
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash	
	immediately with plenty of soap and water.	
Eye contact:	Bathe the eye with running water for 15 minutes.	
Ingestion:	Wash out mouth with water.	
Inhalation:	Consult a doctor.	
4.2. Most important symptom	ns and effects, both acute and delayed	
Skin contact:	There may be mild irritation at the site of contact.	
Eye contact:	There may be irritation and redness.	
Ingestion:	There may be irritation of the throat.	
Inhalation:	No symptoms.	
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.	
4.3. Indication of any immediate medical attention and special treatment needed		

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

BRIWAX ORIGINAL WAX POLISH

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for	or safe handling
----------------------	------------------

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:Store in a cool, well ventilated area. Keep container tightly closed. Keep away from
sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

BRIWAX ORIGINAL WAX POLISH

8.1. Control parameters

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Workplace exposure limits:			Respirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m3	384 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical		
	equipment are not a source of ignition.		
Respiratory protection:	Respiratory protection not required.		
Hand protection:	Protective gloves.		
Eye protection:	Safety glasses. Ensure eye bath is to hand.		
Skin protection:	Protective clothing.		

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Wax		
Colour:	Off-white		
Odour:	Characteristic odour		
Evaporation rate:	No data available.		
Oxidising:	No data available.		
Solubility in water:	Insoluble		
Also soluble in:	Benzene.		
Viscosity:	Viscous		
Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	23 - 55	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	No data available.	pH:	No data available.
VOC g/I:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

BRIWAX ORIGINAL WAX POLISH

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Reproductive toxicity		Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

BRIWAX ORIGINAL WAX POLISH

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

BRIWAX ORIGINAL WAX POLISH

Page: 7

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H225: Highly flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H361d: Suspected of damaging the unborn child.
	H373: May cause damage to organs through prolonged or repeated exposure.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.