

Page 1/9

THE PERFECT FINISH Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4) Revision: 30.03.2022 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML · Article number: 009444 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category Paint remover · Process category PROC7 Industrial spraying PROC11 Non industrial spraying · Application of the substance / the mixture Spray varnish · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: European Aerosols B.V. Wolfraamweg 2 NL-8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 e-mail: sds-nl@european-aerosols.com • Further information obtainable from: Department Product Safety • 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h) UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111 IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

 <i>Pecautionary statements</i> If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. <i>Iditional information:</i> <i>U</i>H066 Repeated exposure may cause skin dryness or cracking. <i>U</i>H211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 		(Contd. of page
 gnal word Danger azard-determining components of labelling: vdrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. 336 May cause drowsiness or dizziness. ecautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 211 Do not spray on an open flame or other ignition source. 251 Do not pierce or burn, even after use. 260 Do not breathe spray. 110+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 301 Dispose of contents / container in accordance with regional regulations. 111 Honde Repeated exposure may cause skin dryness or cracking. 11211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	Hazard p	nictograms
 gnal word Danger azard-determining components of labelling: vdrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. 336 May cause drowsiness or dizziness. ecautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 211 Do not spray on an open flame or other ignition source. 251 Do not pierce or burn, even after use. 260 Do not breathe spray. 110+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 301 Dispose of contents / container in accordance with regional regulations. 111 Honde Repeated exposure may cause skin dryness or cracking. 11211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	$\mathbf{\Lambda}$	\wedge
 gnal word Danger azard-determining components of labelling: vdrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. 336 May cause drowsiness or dizziness. ecautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 211 Do not spray on an open flame or other ignition source. 251 Do not pierce or burn, even after use. 260 Do not breathe spray. 110+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 301 Dispose of contents / container in accordance with regional regulations. 111 Honde Repeated exposure may cause skin dryness or cracking. 11211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	J.	
 gnal word Danger azard-determining components of labelling: vdrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. 336 May cause drowsiness or dizziness. eccautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 211 Do not spray on an open flame or other ignition source. 251 Do not pierce or burn, even after use. 260 Do not breathe spray. 110+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 301 Dispose of contents / container in accordance with regional regulations. 1110 Dispose of contents / container in accordance with regional regulations. 11211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	<u>63</u>	
 gnal word Danger azard-determining components of labelling: vdrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. 336 May cause drowsiness or dizziness. ecautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 211 Do not spray on an open flame or other ignition source. 251 Do not pierce or burn, even after use. 260 Do not breathe spray. 110+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 301 Dispose of contents / container in accordance with regional regulations. 111 Honde Repeated exposure may cause skin dryness or cracking. 11211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 		
 azard-determining components of labelling: aydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. 336 May cause drowsiness or dizziness. recautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 104 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 105 Do not spray on an open flame or other ignition source. 106 Do not breathe spray. 107 H10+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 108 J10 J50 Se of contents / container in accordance with regional regulations. 109 H06 Repeated exposure may cause skin dryness or cracking. 111 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 30 Other hazards 	GHS02	GHS07
 ydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness. recautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 211 Do not spray on an open flame or other ignition source. 251 Do not pierce or burn, even after use. 260 Do not breathe spray. 410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 261 Dispose of contents / container in accordance with regional regulations. 271 Honof Repeated exposure may cause skin dryness or cracking. 271 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 37 Other hazards 	Signal w	ord Danger
 ydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) azard statements 222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness. recautionary statements 101 If medical advice is needed, have product container or label at hand. 102 Keep out of reach of children. 210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. 211 Do not spray on an open flame or other ignition source. 251 Do not pierce or burn, even after use. 260 Do not breathe spray. 410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 261 Dispose of contents / container in accordance with regional regulations. 271 Honof Repeated exposure may cause skin dryness or cracking. 271 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 37 Other hazards 	Hazard-a	letermining components of labelling:
 Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness. Ecautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Iditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 		
 May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Iditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Other hazards 	Hazard s	tatements
 <i>recautionary statements</i> If medical advice is needed, have product container or label at hand. <i>Keep out of reach of children.</i> <i>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</i> Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. <i>Hoto fermation:</i> <i>Hot</i>	H222-H2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
 If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Hoto Repeated exposure may cause skin dryness or cracking. Who66 Repeated exposure may cause skin dryness or cracking. WH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Other hazards 	H336	May cause drowsiness or dizziness.
 Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Kational information: WH066 Repeated exposure may cause skin dryness or cracking. WH066 Repeated exposure may cause skin dryness or cracking. WH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Other hazards 	Precauti	onary statements
 <i>Keep</i> away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. <i>P</i>410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. <i>Hational information:</i> <i>UH066 Repeated exposure may cause skin dryness or cracking.</i> <i>UH066 Repeated exposure may cause skin dryness or cracking.</i> <i>UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</i> <i>Other hazards</i> 	P101	<i>If medical advice is needed, have product container or label at hand.</i>
 smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. H0+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Iditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	P102	Keep out of reach of children.
 Do not pierce or burn, even after use. Do not breathe spray. Potect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Iditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	P210	
 Do not breathe spray. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents / container in accordance with regional regulations. Iditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Other hazards 	P211	Do not spray on an open flame or other ignition source.
 410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. 501 Dispose of contents / container in accordance with regional regulations. Aditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	P251	Do not pierce or burn, even after use.
 Dispose of contents / container in accordance with regional regulations. Iditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	P260	Do not breathe spray.
 Iditional information: UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	P410+P4	12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 UH066 Repeated exposure may cause skin dryness or cracking. uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards 	P501	Dispose of contents / container in accordance with regional regulations.
uildup of explosive mixtures possible without sufficient ventilation. UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 3 Other hazards	Addition	al information:
UH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.3 Other hazards	EUH066	Repeated exposure may cause skin dryness or cracking.
mist. 3 Other hazards	Buildup o	of explosive mixtures possible without sufficient ventilation.
3 Other hazards	EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or
-		mist.
	2.3 Other	r hazards
esults of PBT and vPvB assessment		

- *PBT:* Not applicable.
- **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%) Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) ♦ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8))	2.5-<5%

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

		Contd. of page 2)
CAS: 13463-67-7	titanium dioxide	<i>≥</i> 1-<2.5%
EINECS: 236-675-5	🚸 Carc. 2, H351	
Index number: 022-006-00-2		
Reg.nr.: 01-2119489379-17		
Ũ		

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

\cdot 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -

*

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

- Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.
- Keep ignition sources away Do not smoke.
- Keep respiratory protective device available.

(Contd. on page 4)

⁻⁻⁻⁻GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

(Contd. of page 3)

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles:

- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
 Further information about storage conditions: Keep container tightly sealed.
- Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³ *total inhalable **respirable

· DNELs

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%)

-		
		125 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	208 mg/kg /per day (Worker, longterm systemic)
	DNEL	125 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	871 mg/m3 (Worker, longterm systemic)
	DNEL	185 mg/m3 (Consumer, longterm systemic)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection Not required.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
 Physical state

Aerosol

(Contd. on page 5)

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

	(Contd. of page
Colour:	Different according to colouring
Odour:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.5 Vol %(64742-47-8 Distillates (petroleum),
	hydrotreated light)
Unnav	10.9 Vol % (74-98-6 propane)
Upper:	
Flash point:	Not applicable, as aerosol.
Auto-ignition temperature:	365 °C (689 °F) (106-97-8 butane (containing < 0,1 %
	butadiene (203-450-8)))
Decomposition temperature:	Not determined.
рН	Mixture is non-soluble (in water).
Viscosity:	· · · · ·
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 $^{\circ}C$ (68 $^{\circ}F$):	3500 hPa (2625.2 mm Hg)
Density and/or relative density	
Density at 20 °C (68 °F):	$0.8 \ g/cm^3 (6.7 \ lbs/gal)$
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	A 1
Form:	Aerosol
Important information on protection of health and	đ
environment, and on safety.	
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	55.0 %
Water:	35.7 %
VOC (EC)	
	616.2 g/l
VOC-EU%	55.05 %
Solids content:	2.0 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard classe	S
Explosives	Void
Flammable gases	Void
Aerosols	<i>Extremely flammable aerosol. Pressurised container:</i>
	May burst if heated.
Oridising ages	Void
Oxidising gases	
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void

GB

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

		(Contd. of page 5)
· Substances and mixtures, which emit flo	ummable	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%)

Oral LD50 >5000 mg/kg /per day (rat) (OECD 401)

Dermal LD50 >2000 *mg/kg* (*rat*) (*OECD* 402)

Inhalative LC50 / 4 h >5000 mg/m3 (rat) (OECD 403)

· Skin corrosion/irritation No irritant effect.

· Serious eye damage/irritation No irritating effect.

- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- $\cdot \textit{Aquatic toxicity: No further relevant information available.}$
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- \cdot Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 7)

GB

*

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

(Contd. of page 6)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
 14.2 UN proper shipping name ADR IMDG IATA 	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	2.1
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group · ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Code Segregation Code 	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from" c 1 except for division 1.4.

Page 8/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

	(Contd. of page
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk accord	ling to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.

(Contd. on page 9)

Page 9/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 5 (replaces version 4)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9444 STONE MANHATTAN MIST 6UC 400 ML

	(Contd. of pag	ge 8)
H304	May be fatal if swallowed and enters airways.	
H336	May cause drowsiness or dizziness.	
H351	Suspected of causing cancer.	
EUH06	66 Repeated exposure may cause skin dryness or cracking.	
	ication according to Regulation (EC) No 1272/2008	
•	based on internal technical data and technical data from suppliers.	
	iations and acronyms:	
	cord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the	
	onal Carriage of Dangerous Goods by Road)	
	nternational Maritime Code for Dangerous Goods	
	ternational Air Transport Association	
	obally Harmonised System of Classification and Labelling of Chemicals	
	European Inventory of Existing Commercial Chemical Substances	
	European List of Notified Chemical Substances	
	emical Abstracts Service (division of the American Chemical Society)	
	latile Organic Compounds (USA, EU)	
	Derived No-Effect Level (UK REACH)	
	thal concentration, 50 percent	
	ethal dose, 50 percent	
	sistent, Bioaccumulative and Toxic	
	ry Persistent and very Bioaccumulative	
	is IA: Flammable gases – Category IA	
	1: Aerosols – Category 1	
	as (Comp.): Gases under pressure – Compressed gas	
	<i>q. 3: Flammable liquids – Category 3</i>	
	Carcinogenicity – Category 2	
	3: Specific target organ toxicity (single exposure) – Category 3	
*	1: Aspiration hazard – Category 1	
* Data	compared to the previous version altered.	
		- GB