

Knauf Fill & Finish 60 Premium

Data Sheet



Knauf Fill & Finish 60 Premium is a fast-setting, multi-purpose gypsum-based compound for bedding tapes and beads, as well as finishing. For hand application. 60 minute working time.

Knauf Application

- Interior applications only
- For jointing of gypsum boards
- For bedding joint tapes and finishing joints by hand application only
- Available in 5kg and 10kg bags

Physical Characteristics

Bag Size	Bags per pallet	Material No.	Approx. Coverage
kg			m ² per bag
5	200	622331	22.5 (to bed, fill and finish)
10	100	622332	45 (to bed, fill and finish)

Storage and Handling

Store dry. Protect against frost, high temperatures and exposure to direct sunlight. Recommended for use within 9 months of manufacture.

Compliance

Jointing Compound for Gypsum Plasterboard in acc. to BS EN 13693: 2014. Dual purpose compound, Type 3B.

Performance Data

In compliance with BS EN 13963: 2014, the product is subject to initial type testing and continuous factory product control and bears the CE marking.

Technical Data

- Reaction to fire: A1
- Flexural Strength: NPD

Product Features

- 9 months shelf life
- 60 minute working time

Application/Installation

Mixing:
Sprinkle the powder into a suitable clean mixing container with clean, cold tap water. Allow to soak for 5 minutes before mixing to a workable consistency.

Mechanical mix with care – Do not over mix.

The mixed product remains useable for 60 minutes.

Bedding and Finishing joint tape:
Apply Knauf Fill & Finish 60 Premium to the recess formed by the plasterboard tapers. Apply Knauf Joint Tape, submerging the tape into the compound with a taping knife or trowel.

When dry, apply a second coat to finish.

If sanding is required, at least 120 grit sandpaper is recommended.

Knauf Fill & Finish 60 Premium is a filler and finishing material. Only two coats are required to achieve a smooth finished surface.

Suitability:
Suitable for use on all plasterboards manufactured to BS EN 520:2004.

Use in accordance with British Standard Code of Practice BS 8212:1995 and BS 8000: Part 8:1994 workmanship.

Cleaning:
Clean containers and tools with water immediately after use.

Related products

Knauf Fill & Finish 60 Premium should be used in conjunction with the following products:

Knauf Joint Cement Premium 20kg
Material no: 622337




Knauf Fill & Finish 30 Premium
Material no: 5kg: 622326
Material no: 10kg: 622329



Knauf Joint Filler Premium
Material no: 10kg 622340
Material no: 20kg 622342



Knauf Joint Tape
Material no: 258337



Knauf Fibre Tape
Material no: 493679



Health & Safety

May irritate eyes or sensitive skin.

Dust may irritate respiratory system.

- Protective gloves, glasses and face mask is recommended.
- Avoid prolonged contact with skin, wash off immediately with water.
- Avoid inhaling – minimise dust, ventilate area, move person to fresh air.
- Avoid ingestion – wash mouth out immediately and drink plenty of water.
- Should any symptoms persist or allergic reaction occur, seek medical advice

Refer to the product MSDS and also the Knauf Guidance for Safe Material Management document:

MSDS: www.knauf.co.uk/product-data-sheets

Safe Material Management: www.knauf.co.uk/literature

Sustainability Credentials

Please view Product Sustainability Credentials Sheet:

www.knauf.co.uk/product-data-sheets

Customer Service

UK Tel: 0800 521 050

Eire Tel.: 01 4620739

Email: cservice@knauf.co.uk

Technical Service

UK Tel.: 0800 030 4135

Eire Tel.: 01 4620739

E-mail: technical@knauf.co.uk

Literature

UK Tel: 03700 613 700

Eire Tel.: +44 3700 613 700

Website

www.knauf.co.uk

www.knauf.ie

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Knauf
87 Broomhill Road
Tallaght
Dublin 24



KNAUF