

IKOpro BLACK BITUMEN PAINT

PRODUCT INFORMATION

IKOpro Black Bitumen Paint is an all-purpose bitumen paint, which provides waterproof protection for a wide range of substrates including cast iron, steel, concrete, brickwork, fibre cement and zinc.

	Product Code
1L	MW686431
2.5L	MW686432
5L	MW686435
22.5L	MW686437

USE

An all-purpose bitumen paint for protecting many types of common building elements such as cast iron gutters, rainwater pipes, metal gates, concrete upstands, plinths, sub-structure or concealed masonry.

FEATURES & BENEFITS

Ease of Use - brush application, straight from the tin.

Ease of preparation – no priming necessary.

PERFORMANCE & COMPOSITION

Composition:	Bitumen
Form:	Liquid
Colour:	Black
General Dimension Data	
Unit size:	1L/2.5L/5L/22.5L
Coverage Rate*:	
Concrete/Masonry	4-6m ² per litre (0.25 - 0.17L/m ²)
Metal	8-10m ² per litre (0.125 - 0.1L/m ²)
Application Temperature:	
Surface	5°C and rising
Drying Times**:	2 - 4 hours

* Subject to surface porosity

** Depending upon external conditions

DIRECTIONS FOR USE

MATERIAL HANDLING

Storage temperature must be between 5-30°C. For specific storage and handling requirements, please refer to relevant sections of the IKO Safety Data Sheet.

SURFACE PREPARATION

All surfaces must be clean, dry and free from grease, oil, dirt and loose material. Treat any algae and fungi using IKOpro Algae and Fungi Remover as required.

IKOpro Black Bitumen Paint can be applied over previously painted surfaces, provided they are well adhered. Loose or blistered paint should be removed, as should tar based paint systems.

IKOpro Black Bitumen Paint will not inhibit rust, and any iron or steel surfaces should be pre-treated with a suitable rust inhibitor and allowed to thoroughly dry. New galvanised surfaces should be prepared using a wire brush or suitable etch primer.

Porous substrates such as masonry, fibre cement, concrete should be primed using IKOpro Quick Drying Primer and allowed to dry.

APPLICATION

IKOpro Black Bitumen Paint is ready for use direct from the tin. The product should not be thinned.

Apply a minimum of 2 coats by brush. Allow each coat to dry before applying the next.

CLEANING

Brushes and tools can be cleaned with white spirit.

DISPOSAL

For specific disposal of waste, unused and contaminated packaging, please refer to relevant sections of the IKO Safety Data Sheet.

DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.