

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- Trade name: ***IKOpro Black Bitumen Paint***
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU19 Building and construction work
- **Application of the substance / the mixture** Bitumen coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
IKO PLC
Appley Lane North
Appley Bridge
Wigan
Lancashire
WN6 9AB
- **Further information obtainable from:**
uktechnical@iko.com
- **1.4 Emergency telephone number:** +44 (0)1257 256864 09:00 - 17:00 weekdays

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 3 H226 Flammable liquid and vapour.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)
- **Hazard statements**
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P102 Keep out of reach of children.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Trade name: **IKOpro Black Bitumen Paint**

(Contd. of page 1)

P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Additional information:**

EUH066 *Repeated exposure may cause skin dryness or cracking.*

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of complex substances derived from petroleum and aromatic hydrocarbons.

· **Dangerous components:**

EC number: 919-857-5 Reg.nr.: 01-2119463258-33	hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-30%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%) Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	10-<25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** Not applicable.

· **5.3 Advice for firefighters**

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Trade name: **IKOpro Black Bitumen Paint**

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Protect from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates

Inhalative	Grenswaarde	871 mg/m ³ (human)
------------	-------------	-------------------------------

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

Inhalative	Grenswaarde	330 mg/m ³ (human)
------------	-------------	-------------------------------

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Protection of hands:** Solvent resistant gloves
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Trade name: **IKOpro Black Bitumen Paint**

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· Appearance:

Form: Viscous

Colour: Black

· Odour: Solvent-like

· pH-value: Not determined.

· Change in condition

Boiling point/Boiling range: 130 °C

· Flash point: 35 °C

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 0.5 Vol %

Upper: 7.0 Vol %

· Vapour pressure at 20 °C: 27 hPa

· Density at 20 °C: 0.88 g/cm³

· Solubility in / Miscibility with

water: Insoluble.

· organic solvents: Miscible with many organic solvents.

· Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: 100 mm²/s

· Solvent content:

VOC (EC) VOC limit value (cat A/i) 500 g/L 2010.

Product contains 450 g/L.

· 9.2 Other information No further information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: Stable at environment temperature.

· 10.3 Possibility of hazardous reactions Forms flammable gases/fumes.

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 5)

Trade name: **IKOpro Black Bitumen Paint**

(Contd. of page 4)

· **LD/LC50 values relevant for classification:**

hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>5000 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>4951 mg/l (rat)
------------	----------	------------------

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

Oral	LD50	>15000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

· **Primary irritant effect:**

· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

· **Serious eye damage/irritation** Splashes in the eyes may cause irritation and reversible local damage.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause drowsiness or dizziness.

· **STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

EC50	10 mg/l (daphnia)
------	-------------------

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.


(Contd. on page 6)

Trade name: **IKOpro Black Bitumen Paint**

(Contd. of page 5)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG	UN1268
· 14.2 UN proper shipping name · ADR · IMDG	UN 1268 PETROLEUM PRODUCTS, N.O.S. (aliphatical white spirit, white spirit) exemption according 2.2.3.1.5. UN 1268, Petroleum products n.o.s., 3, III, (35 °C c.c.) Transport in accordance with 2.3.2.5 of the IMDG code.
· 14.3 Transport hazard class(es) · ADR, IMDG	
	
· Class	3 Flammable liquids.
· 14.4 Packing group · ADR, IMDG	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Stowage Category	Warning: Flammable liquids. A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1268, PETROLEUM PRODUCTS, N.O.S., 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

(Contd. on page 7)

Trade name: **IKOpro Black Bitumen Paint**

(Contd. of page 6)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction:** 3
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
This product does not contain any SVHC's.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department

· **Contact:**

Wim Verstraeten

e-mail: Wim.Verstraeten@iko.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **Version History**

Version 1 **September 2016** **New Version, New Issue**