

PRODUCT DATA SHEET

RONSEAL CHALKY FURNITURE PAINT

Ronseal Chalky Furniture Paint transforms and protects interior furniture, doors and cupboards. It provides the chalky, matt finish of traditional chalk paints but with added protection and so avoids the need to overcoat with wax.

INTRODUCTION

Ronseal Chalky Furniture Paint is a water based coating for the decoration and protection of interior surfaces such as furniture, doors and cupboards. It provides a tough and durable finish that will protect wood from knocks and scratches.

Ronseal Chalky Furniture Paint provides a chalky, matt finish with no need to overcoat with wax. It has a quick drying, low odour formula and will be touch dry in 30 minutes.

COMPOSITION

A water based paint containing an acrylic modified alkyd emulsion and high quality pigments.

PROPERTIES

Appearance – Opaque viscous paint.
Odour - Characteristic.
Solubility – Miscible with water.
VOC content – max 8 g/l (Low)

FIELDS OF APPLICATION

Suitable for use on bare wood or previously painted or varnished surfaces. It is suitable for application to cupboards, doors, furniture, shelving, skirting boards and architrave.

Not suitable for use on floors.

PREPARATION

Previously Painted or Varnished Wood:

Sand the surface thoroughly* with 240 grit paper, existing coatings should be sound. If the coating is cracked or loose sand back to bare wood (see Important Notes).

Remove any sanding dust, wipe the surface with white spirit and allow to dry thoroughly.

Bare Wood:

Sand the surface thoroughly*. Remove any sanding dust, wipe the surface with white spirit and allow to dry thoroughly.

*Take care when sanding, always wear a face mask designed to avoid the inhalation of dust.

APPLICATION

Ensure temperature is 10°C or above and the area is well ventilated during application and drying.

Stir the paint thoroughly prior to and during application. Using a synthetic filament brush apply 2 coats in the direction of the grain allowing 4 hours between coats.

Always conduct a test area to confirm colour suitability. The natural colour of the wood may affect the final colour achieved

COVERAGE

One litre will cover up to 16 square metres with one coat.

CLEAN UP

Wash brushes whilst still wet in warm soapy water.

Remove as much product as possible from brushes prior to cleaning. Do not empty any unused coating into drains or water courses.

Some local authorities may have special facilities for the disposal of waste coatings.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Safety Data Sheet available on request.

IMPORTANT NOTES

This product contains no added lead. However, wooden and metal surfaces particularly in pre-1960 buildings may have previously been treated with paint containing lead pigments. Special care must be taken when sanding or stripping. For further information consult our Technical Services Department.

FLAMMABILITY

Not flammable.

SIZES

Available in 750 ml re-sealable containers.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require on +44(0)114 240 9469.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams
Diversified Brands Ltd
Thornclyffe Park
Chapelton
Sheffield
S35 2YP**

Tel: +44(0)114 246 7171
Fax: +44(0)114 245 5629

Registered in England 2968830

E. Mail: enquiry@ronseal.co.uk
Website: www.ronseal.co.uk

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

IDECEMBER, 2016. ISSUE 1.