

0 601 8B6 001 – GOP 18V-28

Material number	0 601 8B6 001	0 601 8B6 002	0 601 8B6 070	0 601 8B6 071
EAN	3165140842587	3165140842563	3165140842617	3165140870085
1 x Starlock BIM plunge cut saw blade All 65 APB, Curved-Tec, Wood + Metal 2 608 661 781			✓	✓
1 x Starlock BIM plunge cut saw blade All 65 BSPB, Curved-Tec, Hard Wood 2 608 662 017			✓	✓
1 x Starlock BIM plunge cut saw blade AIZ 20 AB, Wood + Metal 2 608 661 640			✓	✓
1 x Starlock BIM plunge cut saw blade AIZ 32 APB, Wood + Metal, Curved-Tec 2 608 661 644			✓	✓
1 x Starlock BIM segment saw blade ACZ 85 EB, Wood + Metal 2 608 661 636			✓	✓
1 x Starlock Carbide-RIFF sanding plate AVZ 78 RT2, Grout + Abrasive 2 608 661 648			✓	✓
1 x Starlock Carbide-RIFF segment saw blade ACZ 85 RT3, Grout + Abrasive 2 608 661 642			✓	✓
1 x Starlock delta sanding plate AVZ 93 G 2 608 000 493			✓	✓
1 x StarlockPlus BIM plunge cut saw blade PAII 65 APB, Curved-Tec, Wood + Metal 2 608 662 564			✓	✓
1 x StarlockPlus BIM plunge cut saw blade PAIZ 32 APB, Curved-Tec, Wood + Metal 2 608 662 558	✓	✓	✓	✓
1 x StarlockPlus Carbide plunge cut saw blade PAIZ 32 AT, Metal 2 608 662 555			✓	✓
2 x battery GBA 18V 2.0Ah 1 600 Z00 036			✓	
2 x battery GBA 18V 5.0Ah 1 600 A00 2U5				✓
5 x sanding sheets, K 2x80, 2x120, 1x240 2 608 621 104			✓	✓
Cardboard box		✓		
L-BOXX 136 1 600 A00 1RR	✓		✓	✓
Quick charger AL 1860 CV 2 607 225 324			✓	✓
Packaging dimensions (width x length x height)	360 x 440 x 155 mm	130 x 380 x 90 mm	360 x 440 x 155 mm	360 x 440 x 155 mm
Battery voltage	18.0 V	18.0 V	18.0 V	18.0 V
Weight incl. battery	1,6 kg	1,6 kg	1,6 kg	1,6 kg



Battery capacity

2,0 Ah

5,0 Ah

Technical data

Technical data

Battery voltage	18 V
No-load rotation	8.000 – 20.000 opm
Oscillation angle on left and right	1,4 °



Noise/vibration information

Sound pressure level	84 dB(A)
Sound power level	95 dB(A)
Uncertainty K	3 dB

Sales information

Positioning

- The versatile power performer in the Bosch StarlockPlus category

User benefit

- Superior Starlock interface of optimised 3-dimensional tight connection for highest direct power transfer
- LED spot illuminates workspaces, improving work visibility even in the dark
- Snap-in function enables fast and easy tool accessory change

