

# 0 601 6A5 001 – GSA 18 V-LI C

Material number	0 601 6A5 001	0 601 6A5 004
EAN	3165140830256	3165140876407
1 x reciprocating saw blade S 922 AF, Flexible for Metal <small>available separately as set of 2: 2 608 656 036</small>	✓	✓
1 x reciprocating saw blade S 922 EF, Flexible for Metal <small>available separately as set of 2: 2 608 656 038</small>	✓	✓
1 x reciprocating saw blade S 922 HF, Flexible for Wood + Metal <small>available separately as set of 2: 2 608 656 039</small>	✓	
2 x reciprocating saw blade S 922 HF, Flexible for Wood + Metal <small>available separately as set of 5: 2 608 656 016</small>		✓
Cardboard box		✓
Inlay for L-BOXX 136	✓	
L-BOXX 136 <small>1 600 A00 1RR</small>	✓	
Packaging dimensions (width x length x height)	360 x 440 x 155 mm	110 x 315 x 105 mm
Battery voltage	18.0 V	18.0 V
Weight incl. battery	2,5 kg	2,5 kg



## Technical data

---

### Technical data

Cutting depth in wood	200 mm
Cutting depth in metal profiles and metal pipes	100 mm
Stroke lengths	21 mm
Battery voltage	18 V
Stroke rate (1st gear / 2nd gear)	0 - 3.050 spm



### Noise/vibration information

Sound pressure level	82 dB(A)
Sound power level	93 dB(A)
Uncertainty K	3 dB

## Sales information

---

### Positioning

- Compact powerhouse with low vibration

### User benefit

- Compact design for versatile – also one-handed – and overhead use
- Lowest vibration levels ensure comfortable use
- A fast sawing rate and long runtime thanks to powerful motor and high-endurance batteries