

0 601 217 104 – GSB 13 RE

Material number	0 601 217 104	0 601 217 160	0 601 217 170
EAN	3165140876872	3165140371933	3165140371940
3-piece masonry drill bit set CYL-1 (5/6/8 mm) 1 609 200 204	✓		
Depth stop 210 mm 1 613 001 010	✓	✓	✓
Keyless chuck 13 mm 2 608 572 105	✓	✓	✓
Voltage 110 V		✓	
Voltage 240 V			✓
Packaging dimensions (width x length x height)	299 x 353 x 116 mm	260 x 295 x 75 mm	237 x 295 x 75 mm
Voltage, electrical	230 V	110 V	240 V
Drill chuck, version		Keyless chuck	Keyless chuck
Spindle collar diameter		43,0 mm	43,0 mm



Technical data

Technical data

Rated input power	600 W
No-load speed	0 – 2.800 rpm
Power output	301 W
Weight	1,8 kg
Rated torque	1,8 Nm
Drill spindle connecting thread	1/2" – 20 UNF
Chuck capacity, min./max.	1,5 – 13 mm
Tool dimensions (length)	266 mm
Tool dimensions (height)	180 mm
Impact rate at no-load speed	0 – 44.800 bpm



Drilling range

Drilling diameter in concrete	13 mm
Drilling diameter in wood	25 mm
Drilling diameter in steel	10 mm
Drilling diameter in masonry	15 mm

Noise/vibration information

Sound pressure level	93 dB(A)
Sound power level	104 dB(A)
Uncertainty K	3 dB

Sales information

Positioning

- Compact 1-gear entry-level impact drill

User benefit

- 1.8 kg lightweight design and compact housing size provide for convenience in handling and manoeuvrability
- Robust design with a durable metal keyless chuck
- Delivers professional results at an optimum price performance value