

# 0 601 237 060 – GOP 30-28

Material number	0 601 237 060	0 601 237 061	0 601 237 070	0 601 237 071
EAN	3165140842730	3165140842662	3165140842747	3165140842679
1 x Starlock BIM plunge cut saw blade All 65 APB, Curved-Tec, Wood + Metal 2 608 661 781	✓		✓	
1 x Starlock BIM plunge cut saw blade All 65 BSPB, Curved-Tec, Hard Wood 2 608 662 017	✓		✓	
1 x Starlock BIM plunge cut saw blade AIZ 20 AB, Wood + Metal 2 608 661 640	✓		✓	
1 x Starlock BIM plunge cut saw blade AIZ 32 APB, Wood + Metal, Curved-Tec 2 608 661 644	✓		✓	
1 x Starlock BIM segment saw blade ACZ 85 EB, Wood + Metal 2 608 661 636	✓		✓	
1 x Starlock Carbide-RIFF sanding plate AVZ 78 RT2, Grout + Abrasive 2 608 661 648	✓		✓	
1 x Starlock Carbide-RIFF segment saw blade ACZ 85 RT3, Grout + Abrasive 2 608 661 642	✓		✓	
1 x Starlock delta sanding plate AVZ 93 G 2 608 000 493	✓		✓	
1 x StarlockPlus BIM plunge cut saw blade PAII 65 APB, Curved-Tec, Wood + Metal 2 608 662 564	✓		✓	
1 x StarlockPlus BIM plunge cut saw blade PAIZ 32 APB, Curved-Tec, Wood + Metal 2 608 662 558	✓	✓	✓	✓
1 x StarlockPlus Carbide plunge cut saw blade PAIZ 32 AT, Metal 2 608 662 555	✓		✓	
5 x sanding sheets, K 2x80, 2x120, 1x240 2 608 621 104	✓		✓	
Cardboard box		✓		✓
L-BOXX 136 1 600 A00 1RR	✓		✓	
Voltage 110 V	✓	✓		
Voltage 240 V			✓	✓
Voltage	110 V		240 V	240 V
Packaging dimensions (width x length x height)	360 x 440 x 140 mm	125 x 375 x 95 mm	360 x 440 x 135 mm	125 x 380 x 95 mm





## Technical data

### Technical data

Rated input power	300 W
No-load oscillation	8.000 – 20.000 opm
Oscillation angle on left and right	1,4 °
Weight	1,5 kg



### Noise/vibration information

Sound pressure level	81 dB(A)
Sound power level	92 dB(A)
Uncertainty K	3 dB

## Sales information

### Positioning

- Best price-performance ratio in the Bosch StarlockPlus category

### User benefit

- 300 W motor and superior Starlock interface with optimised 3-dimensional tight fit for best power transfer
- Small ergonomic handle grip provides comfortable handling and better tool control
- Magnetic mounting enables easy accessory changes