

N 50, Wall-mounted cooker hood, 60 cm, clear glass black printed
D65IHM1S0B



COOKING PASSION SINCE 1877



B

The design hood with an inclined front and high power ensures headroom while cooking.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

Features

Technical Data

Typology : Wall-mounted
Length of electrical supply cord : 130 cm
Height of product, without chimney : 323 mm
Net weight : 19.9 kg
Type of control : Electronic
Maximum output air extraction : 416 m³/h
Boost position output recirculating : 469 m³/h
Maximum output recirculating air : 367 m³/h
Boost position air extraction : 700 m³/h
Number of lights (Stck) : 2
Noise level : 58 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
Odour filter : No
Operating Mode : Convertible
Optional accessories : Z50XXP0X0, Z51AIB1X6, Z51AII1X6, Z51AIROX0, Z51AISOX0, Z51AIV1X6, Z51AXC1N6, Z51AXK0N0, Z51AXL0N0, Z53XXB1X6, Z91AXE1S1
Type of lamps used : LED
Grease filter type : Kasette
Connection rating : 263 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 60; 50 Hz
Plug type : GB plug
Installation type : Wall-mounted
Material body : Glass, Lacquered
Plug type : GB plug
Dimensions of the product, with chimney (if exists) (in) : / x x
Dimensions of the packed product : 27.16 x 29.13 x 40.94
Net weight : 44.000 lbs
Gross weight : 63.000 lbs
Motor location : Integrated motor in hood body
No-return airflow flap : No
Length of electrical supply cord : 130 cm
Dimensions of the product, with chimney (if exists) : 452 x 590.0 x 499.0 mm
Dimensions of the packed product (HxWxD) : 690 x 740 x 1040 mm
Net weight : 19.9 kg
Gross weight : 28.8 kg

Optional accessories

Z50XXP0X0 Long Life odor filter (replacement)
Z51AIB1X6 Clean Air Plus odor filter (replacement)
Z51AII1X6 Clean Air Plus recirculation kit
Z51AIROX0 Long Life recirculation kit (chimless)
Z51AISOX0 Long Life recirculation kit
Z51AIV1X6 Clean Air Plus recirc. kit (chimless)
Z51AXC1N6 Clean Air Plus recirc. kit external
Z51AXK0N0 Chimney extension 1000 mm
Z51AXL0N0 Chimney extension 1500 mm
Z53XXB1X6 Clean Air Plus odor filter (replacement)
Z91AXE1S1 Chimney standard black



4 242004 210030

*N 50, Wall-mounted cooker hood, 60 cm, clear
glass black printed
D651HM1S0B*



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 416 m³/h
Intensive 700 m³/h
- Noise max. Normal Level: Noise, max. speed in normal use: 58 dB dB*

Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- Installation: wall
- Rim ventilation

Design

- Chimney hood
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 58 dB(A) re 1 pW
Intensive: 67 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1 pW
- Power rating: 263 W
- Light Intensity: 100 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 590 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 590 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
1118 x 590 x 499 mm - mounting with outer chimney
1188-1458 x 590 x 499 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

Optional accessories

- Recirculating kit Z50XXPOX0

* In accordance with the EU-Regulation No 65/2014

N 50, Wall-mounted cooker hood, 60 cm, clear
glass black printed
D651HM1S0B

Dimensioned drawings

