

PRODUCT DATA SHEET

No. 11151/0

JULY, 2000

RONSEAL LAMINATE FLOOR SEAL

Ronseal Laminate Floor Seal is a specially formulated, water based seal, designed for the renovation and protection of worn laminate flooring. It is ideal for use on laminate flooring where the surface has become dull or scuffed.

INTRODUCTION

Ronseal Laminate Floor Seal is a high quality water based seal formulated to restore worn laminate flooring. It is ideal for use on laminate flooring where the surface has become dull or scuffed. Ronseal Laminate Floor Seal's clear film requires no buffing and offers added protection against future wear and tear, occasional water and household chemical spills.

Ronseal Laminate Floor Seal is easy to apply, simply wipe on and leave to dry, has a low odour, quick drying formulation which is especially important when treating floors.

COMPOSITION

Ronseal Laminate Floor Seal is a blend of resins and waxes as a water based emulsion.

PROPERTIES

Appearance – Off white liquid.
Viscosity – Low.
Odour – Low, inoffensive odour.
Miscible with water.

FIELDS OF APPLICATION

Ronseal Laminate Floor Seal is suitable for use over laminated floors of various types and condition.

PREPARATION

Ensure the floor is clean and dry. Remove any polish or wax that may have been previously applied using white spirit. Vacuum or sweep and remove any dirt or grease using Ronseal All Purpose Wood Cleaner.

APPLICATION

Ensure the room is warm and well ventilated. Do not shake the tin as this will cause foaming. Apply a generous, even coat using a damp, smooth floor cloth avoiding rubbing up. Always apply in the direction of the wood grain effect to ensure an even finish. The finish can be built up by applying further coats. Apply a minimum of 2 coats but more can be applied if required to cover surface wear.

DRYING TIME

Touch dry in 10 minutes and can be recoated after 1 hour. It is suitable for light traffic after 1 hour. Drying times may vary according to temperature and humidity.

CLEANING OF TOOLS

Remove as much product as possible from application equipment before cleaning.

Wash any equipment in water and detergent immediately after use.

Some local authorities have special facilities for the disposal of waste coatings.

Do not empty product into drains or water courses.

MAINTENANCE

Maintain with further coats of Ronseal Laminate Floor Seal as required. High wear areas will need more frequent application. Vacuum floors regularly to remove dust and wipe with a damp cloth. To remove dirt and grime use Ronseal All Purpose Wood Cleaner.

IMPORTANT NOTES

Refer to instructions on the pack prior to use.

Ronseal Laminate Floor Seal should only be applied to laminate floors.

Observe and follow specific guidance of laminate flooring suppliers on the use of floor seals.

Do not apply the seal across the wood grain effect as this may result in a streaky finish.

Not recommended for use over laminate floor where the surface is damaged or worn down to the backing board.

Laminate flooring which has a natural wood veneer finish may raise at the edges if water penetrates here. Ensure edges on this type of laminate floor are intact before cleaning and applying Ronseal Laminate Floor Seal. Always try on an inconspicuous test area first on Laminate Flooring of this type.

Do not apply if the surface temperature is below 10°C.

Do not pour any residual liquid back into the bottle.

Protect from frost.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition.

Ensure container is fully resealed and that the child proof closure is working correctly after use.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Ensure good ventilation when applying and during drying.

Keep out of reach of children.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Non-flammable.
Flash point above 61°C.

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

Available in a 1 litre re-sealable container.

DISPOSAL

Some local authorities have special facilities for disposal of waste paints/varnishes.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal Products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,
Thornccliffe Park,
Chapelton,
Sheffield.
S35 2YP

Tel:

+44 (0114) 240 9469 (Technical Services)

+44 (0114) 246 7171 (Main Switchboard)

Fax:

+44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a registered trademark of the Sherwin Williams Company.

JULY, 2000. ISSUE 1