

			Application				Bag Details	
			Bedding Coat	Finish Coat	Patching and Repair	Drying Time	Sizes available	Coverage
Powdered	Air-drying	 <p><b>Knauf Plasterboard Adhesive</b> A multi-purpose gypsum-based adhesive used to direct bond Knauf Plasterboards and Knauf Insulating Laminates to masonry surfaces.</p>	X	X	✓	2-3h	25kg	4.6m <sup>2</sup> (dot and dab)
		 <p><b>Wickes Reinforcing Joint Tape For Plasterboards</b> White paper tape for reinforcing joints by hand or machine application. Use with either powdered or ready-mixed jointing products.</p>	✓	X	✓	-	Per roll	150m
Powdered	Accelerated Set	 <p><b>Knauf Fill &amp; Finish 60 Premium</b> A fast setting multi-purpose gypsum-based compound for bedding tapes and beads as well as finishing. 60 minutes working time.</p>	✓	✓	✓	60min working time	10kg	45m <sup>2</sup>
		 <p><b>Knauf Joint Filler Premium</b> A fast-setting gypsum compound for bedding joints by hand application. 90 minutes working time.</p>	✓	X	✓	90min working time	10kg	55m <sup>2</sup>
Ready-mixed	Air-drying	 <p><b>Knauf Fill &amp; Finish Light</b> Lightweight ready-mixed compound for bedding tapes and finishing joints in drywall partitions and ceilings.</p>	✓	✓	✓	12-24h	5kg	11.25m <sup>2</sup>
		 <p><b>Knauf Easy Plaster</b> Lightweight patching plaster specially designed for small to large repairs to cracks in walls and ceilings. It will not shrink or crack.</p>	X	✓	✓	24h	2.5l 6l	1.88m <sup>2</sup> @6mm thick 4.5m <sup>2</sup> @6mm thick
		 <p><b>Knauf ProRoll Light</b> Roller applied plaster. Use as a finish on Knauf ProRoll Max or onto plasterboard backgrounds for a superior finish.</p>	X	✓	✓	24h @ 1mm	12.5kg	10m <sup>2</sup> @1mm thick
		 <p><b>Knauf ProRoll Max</b> Roller applied plaster. Use to level the surface of existing internal walls and ceilings. Ideal for covering textured backgrounds. Use with Knauf ProRoll Light for a superior finish.</p>	X	✓	✓	24h @ 1mm	13.5kg	10m <sup>2</sup> @1mm thick