

Product Data Sheet

Knauf ProRoll Light



Knauf ProRoll Light is a roller applied ready-mixed finishing plaster, used as a finish on plasterboard or over ProRoll Max. Apply up to 3mm thick. Up to a Q4 finish.

Areas of Application

For use onto ProRoll Max or directly on to plasterboard

Key Benefits

- Tub designed to fit a standard 9 inch roller
- Ready-mixed for convenient application
- Ideal for covering existing textured surfaces

Compliance Standards

EN13963:2014

Performance Data

Reaction to Fire (R2F)	Flexural Strength (F)	Density (kg/L)	Dangerous Substances (DS)
A2-s1, d0	NPD	1-1.4	Pass

Technical information

Colour	Weight (kg)	Coverage	Material Number
White	12.5	10m ² per tub at 1mm thickness	593010

Sustainability

Substances of very high concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Volatile Organic Compound Content (VOC)

<0.1% (<1 g/l).

Storage and Handling

Handle in accordance with good health and safety practice. Store in cool, dry conditions and keep sealed when not in use. 12 month shelf life when stored correctly. Not to be used below 10°C.

Packaging

>30% Recycled plastic tub with a steel handle, packaged on a wooden pallet with PE shrink wrap

Shelf Life/Service Life

12 months.

Disposal/Repair

Ensure container is empty before disposing. Dispose in accordance with local authority requirements for plastic containers.

Health & Safety

Wear suitable safety glasses with side shields due to risk of splashing, gloves to protect hands, and a dust mask when sanding.

Application / Installation

Apply with a medium pile 9 inch roller at a thickness of up to 1mm, and smooth with a wide spatula. To achieve the perfect smooth finish, a second skimming coat can be applied after drying. Maximum 3mm thickness for 3 layers. Drying time approximately 12-18 hours per layer, which varies according to thickness, humidity and temperature. May be used as a finishing coat on ProRoll Max.

Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)



Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

0800 521050 (option 2)
Live Webchat 09:00 -17:00
technical-uk@knauf.com

Website

www.knauf.co.uk
www.knauf.ie

Address (UK)

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Address (Ireland)

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

KML100449

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.

© Copyright Knauf 2023

Creation Date: 27/11/2023

Revision Reference: 002

Revision Date: 08/01/2024

Build for the world we live in