A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Safety Data

Mega Strength **PU Adhesive**

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Section 1: Identification of the substance/ mixture and of the company/undertaking

1.1 Product identifier
Product name: No More**Ply** Mega Strength PU Adhesive

1.2 Relevant identified uses of the substance / mixture or uses advised against
(For professional users only)
Use of substance / mixture: Isocyanate based product

1.3 Details of the supplier of the safety data sheet
NoMorePly Boarding Systems, 5 Hawthorn Park, Seacroft, LS14 1PQ
Tel: 0113 202 010
Email: technical@**No**More**Ply**.co.uk

1.4 Emergency telephone number
Emergency tel: 0113 202 010
Hours of opening: Available from Monday to Friday, Office Hours: 08.00 – 17.00

Section 2: Hazards identification

2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin irritation, Category 2
H315: Causes skin irritation.

Eye irritation, Category 2
H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation, Category 1
H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2
H351: Suspected of causing cancer.

Specific target organ toxicity - single exposure, Category 3, Respiratory system
H335: May cause respiratory irritation.

Specific target organ toxicity - repeated exposure, Category 2
H373: May cause damage to organs through prolonged or repeated exposure.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Strength **PU Adhesive**

2.2 Label Elements

Hazard pictograms:



Signal word: Danger

Hazard statements
H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H33: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary statements
Prevention:
P201: Obtain special instructions before use.

P260: Do not breathe mist or vapours.

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label: methylenediphenyl diisocyanate

Additional Labelling EUH204
Contains isocyanates. May produce an allergic reaction.
"As from 24 August 2023 adequate training is required before industrial or Professional use."

2.3 Other Hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

Section 3: Composition / information on ingredients

3.1 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
methylenediphenyl diisocyanate	26447-40-5 247-714-0 615-005-00-9 01-2120770510-62-0000	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373	>= 30 - < 50
2,2'-dimorpholinyldiethyl ether	6425-39-4 229-194-7 01-2119969278-20-0000	Eye Irrit. 2; H319	>= 1 - < 10

Additional information
For the wording of the listed hazard phrases refer to section 16.

Section 4: First aid measures

4.1 Description of first aid measures

General advice: Even minimal concentrations of isocyanate can lead to a reaction in sensitised people. Symptoms that may occur include the following: irritation of the eyes, nose, throat and lungs, possibly together with a dry throat, a feeling of chest tightness and breathing difficulties.

Immediately remove clothing if soiled by product. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If inhaled: Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of unconsciousness bring patient into stable side position for transport.

In case of skin contact: Wash off with polyethylene glycol and afterwards with plenty of water. Use a mild soap if available. Treat affected skin with cotton wool or cellulose. Call a physician if irritation develops or persists.

In case of eye contact: Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists. Protect unharmed eye.

If swallowed: Do NOT induce vomiting. If accidentally swallowed obtain immediate medical attention.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

4.2 Most important symptoms and effects, both acute and delayed

Risks:

- Causes skin irritation.
- May cause an allergic skin reaction.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause respiratory irritation.
- Suspected of causing cancer.
- May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

In instances of existing sensitisation towards isocyanates, a doctor should be consulted with regards to work-related contact with other sensitising substances, or substances which irritate the airway.

Treatment for exposure should be geared towards monitoring symptoms and the patient's clinical condition.

It must be ensured that the patient has sufficient ventilation and oxygen supply.

Isocyanates can cause sensitisation of the airways, or asthma-like symptoms (bronchospasms). Delayed breathing symptoms, including lung oedema, may occur.

People who have shown signs of breathlessness after considerable exposure should remain under observation for 24-48 hours.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

- Water spray
- Alcohol-resistant foam
- Dry powder
- Carbon dioxide (CO^2)

Unsuitable extinguishing media: DO NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: May release toxic, irritating and/or corrosive gases. In case of fire CO, NOx, isocyanates and traces of HCN can be formed.

5.3 Advice for fire-fighters

Special protective equipment for firefighters: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions:

- Use personal protective equipment.
- Use breathing protection against the effects of fumes/dust/aerosol.
- Evacuate personnel to safe areas.
- Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions: If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up:

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
- Ensure adequate ventilation.
- Send for recovery or disposal in suitable containers.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling:

- Take note of emission threshold.
- Avoid formation of aerosol.
- Do not heat the product.
- Ensure that suitable extractors are available on processing machines.
- Handle with care. Avoid inhalation and skin contact.
- Keep eye wash bottle available on working place.
- Avoid release to the environment.
- Keep out of reach of children.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapor concentration below the workplace limit, wear an adequate respiratory protective device.

Advice on protection against fire and explosion: In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers: Do not freeze. Keep tightly closed in a dry, cool and well-ventilated place. Protect against light.

Further information on storage conditions: Keep containers tightly closed in a dry, cool and well-ventilated place.

Advice on common storage: Keep away from food, drink and animal feeding stuffs. Never allow product to get in contact with water during storage.

7.3 Specific end use(s)

No further relevant information available.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

Section 8: Exposure Controls / Personal protections

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methylenediphenyl diisocyanate	26447-40-5	TWA	0,02 mg/m3 (NCO)	GB EH40
	Further information: Capable of causing occupational asthma			
		STEL	0,07 mg/m3 (NCO)	GB EH40
	Further information: Capable of causing occupational asthma			

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
methylenediphenyl diisocyanate	Workers	Dermal	Acute systemic effects	50 mg/kg
	Workers	Inhalation	Acute systemic effects	0,1 mg/m³
	Workers	Dermal	Local effects	28,7 mg/cm²
	Workers	Inhalation	Local effects	0,1 mg/m³
	Workers	Inhalation	Long-term systemic effects	0,05 mg/m³
	Workers	Inhalation	Local effects	0,05 mg/m³

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
methylenediphenyl diisocyanate	Fresh water	> 1 mg/l
	Marine water	> 0,1 mg/l
	Soil	> 1 mg/kg
	Sewage treatment plant	> 1 mg/kg

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

8.2 Exposure control

Engineering measures
Please take care on national and local requirements.
Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment
Eye protection: Tightly fitting safety goggles or equipment with better protection

Hand protection Material: Nitrile rubber or equipment with better protection

Remarks: Direct contact with the product must be avoided by organizational measures. The glove material has to be impermeable and resistant to the product/the substance/the preparation. The exact break through time can be obtained from the protective glove producer and this has to be observed. The gloves need to be disposed after the penetration time and replaced by new ones.

Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:
If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

As protection from splashes gloves made of the following materials are suitable: Nitrile (minimum thickness 0.12 mm), Disposable gloves with long cuffs.

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection: Protective clothing
When carrying out activities where unintentional skin contact with the isocyanate-based product may occur (e.g. during maintenance work, or when opening a barrel), wear long-sleeved protective clothing and gloves.

Respiratory protection: Use respiratory protection unless adequate risk management measures (exhaust/ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus.

In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Filter type: For short term, use combination charcoal and particulate filter or equipment with better protection.

Protective measures: Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling the product. Avoid contact with the eyes and skin. Store protective clothing separately. Keep away from food, drink and animal feeding stuffs.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

Section 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Properties	
Appearance	Gel
Colour	light yellow
Odour	Characteristic
Odour Threshold	is not determined
pH	is not determined
Melting point/freezing point	is not determined
Boiling point/boiling range	is not determined
Flash point	Not applicable
Evaporation rate	is not determined
Flammability (solid, gas)	Not classified as a flammability hazard
Relative vapour density	is not determined
Density	1,10 g/cm^3
Water solubility	partly soluble, reacts with water
Partition coefficient: n-octanol/water	no data available
Auto-ignition temperature	is not determined
Decomposition temperature	Not applicable
Explosive properties	Not explosive

9.2 Other information

No data available

Section 10: Stability and reactivity

10.1 Reactivity

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions: Reacts with alcohols, amines, aqueous acids and alkalis. Mixture reacts with water resulting in evolution of CO2. Evolution of CO2 in closed containers causes overpressure and produces a risk of bursting.

All information within this document is copyright of **No**More**Ply** Boarding Systems

10.4 Conditions to avoid

Conditions to avoid: No further relevant information available.

10.5 Incompatible materials

Materials to avoid:

- Amines
- Strong acids and strong bases

10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as: Nitrogen oxides (NOx) Isocyanates

Additional information: Open and release pressure carefully with pressurised containers.

Section 11: Toxicological informations

11.1. Information on toxicological effects

Acute toxicity: Acute toxicity Based on available data, the classification criteria are not met.

Product:
Acute inhalation toxicity

- Acute toxicity estimate: > 20 mg/l
- Exposure time: 4 Hours
- Test atmosphere: vapour
- Method: Calculation method

Components:
methylenediphenyl diisocyanate:

- Acute inhalation toxicity
- Acute toxicity estimate: 1,5 mg/l
- Test atmosphere: dust/mist
- Method: Calculation method

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitisation: -

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Suspected of causing cancer.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT - single exposure: May cause respiratory irritation.

STOT - repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity: Based on available data, the classification criteria are not met.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

11.2 Information on other hazards
Endocrine disrupting properties. None of the ingredients is listed.

Section 12: Ecological Information

12.1 Toxicity
No data available

12.2 Persistence and degradability
No data available

12.3 Bioaccumulative potential
Components: methylenediphenyl diisocyanate
Partition coefficient: n-octanol/water: log Pow: 4,5

12.4 Mobility in soil
Product: methylenediphenyl diisocyanate
Mobility: Medium: Soil
Remarks: Do not allow product to reach ground water, water bodies or sewage system.

12.5 Results of PBT and vPvB assessment
Product: methylenediphenyl diisocyanate
Assessment: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects
No data available

Section 13: Disposal Considerations

13.1. Waste treatment methods
Product:

- Do not dispose of with domestic refuse.
- Do not dispose of waste into sewer.
- Hand over to disposers of hazardous waste.
- The generation of waste should be avoided or minimized wherever possible.
- Incinerate under controlled conditions in accordance with all local and national laws and regulations.
- Disposal must be made according to official regulations.

Contaminated packaging:

- Disposal must be made according to official regulations.

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

Section 14: Transport information

14.1 UN Number
Not regulated as a dangerous good

14.2 UN proper shipping name
Not regulated as a dangerous good

14.3 Transport hazard class(es)
Not regulated as a dangerous good

14.4 Packaging group
Not regulated as a dangerous good

14.5 Environmental hazards
Not regulated as a dangerous good

14.6 Special precautions for user
Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code
Not applicable for product as supplied

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII):
Conditions of restriction for the following entries should be considered: Number on list 75, 3

methylenediphenyl diisocyanate (Number on list 74) benzoyl chloride

methylenediphenyl diisocyanate (Number on list 74)

4,4'-methylenediphenyl diisocyanate (Number on list 74)

4,4'-Methylenediphenyl diisocyanate, oligomers

REACH - Candidate List of Substances of Very High Concern for Authorisation (SVHC, Article 59):
Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast): Not applicable

RoHS: 2011/65/EU, Restriction of Hazardous Substances: Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Not applicable

UK REACH List of substances subject to authorisation (Annex XIV): Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

Volatile organic compounds: Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 0,01 %

The components of this product are reported in the following inventories:
NZIoC: On the inventory, or in compliance with the inventory

REACH: On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

Section 16: Other information

Full text of H-Statements

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

Full text of other abbreviations

Acute Tox.: Acute toxicity

Carc.: Carcinogenicity

Eye Irrit.: Eye irritation

Resp. Sens.: Respiratory sensitisation

Skin Irrit.: Skin irritation

Skin Sens.: Skin sensitisation

STOT RE: Specific target organ toxicity - repeated exposure

STOT SE: Specific target organ toxicity - single exposure

GB EH40: UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA: Long-term exposure limit (8-hour TWA reference period)

GB EH40 / STEL: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Test-ing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration

All information within this document is copyright of **No**More**Ply** Boarding Systems

A: **No**More**Ply** Boarding Systems / 5 Hawthorn Park / Seacroft / LS14 1PQ
E: sales@**No**More**Ply**.co.uk **T:** 0113 202 2010 **W:** www.**No**More**Ply**.co.uk

Mega Grab **Adhesive**

associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub-stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information: Modified data compared to the previous version The following sections have been updated: - Section 1 - Section 16

Classification of the mixture:		Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

Legal disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

All information within this document is copyright of **No**More**Ply** Boarding Systems