

## Xcite 1.5 Bowl & drainer



Product dimensions and installation information: note: symbol indicates position of acoustic pad on stainless products.





## INSET CUT OUT



Adittional notes: Repeated release of boiling hot water directly into coloured sinks can in extreme cases cause crazing and even cracking. Therefore we recommend great care is taken not to release the water directly on to the sink surface at full temperature.

Overall product size: 1000 x 500 x 200 corner radius 10mm

Taphole(s) detail: 2 x Ø 35m, Part drilled for drill guide

Compatability with large square taps:

Bowl 1 apx. volume (litres): 16.00

Wastehole(s) detail (mm): 90 / 90 / N/A (nb. 90mm wastes accept a waste disposal unit)

Min. base unit (refers to space required for bowl, tap and overflow only): fits 600mm carcass Min. Recessed fitting width: required (bowl(s), tap and overflow: 545mm

\*Worktop cut out size: 976x476 corner radius 10mm, for .DXF cut files please see www.abode.eu Min. & Max worktop depth or clip depth reach range: 27 - 45mm

Fitting temple supplied? No, use cut out instructions as supplied

Dishwasher under drainer? Distance from top of worktop to underside of the drainer 33mm

## \*Important, fabricator / installer notes for undermount & flushmount sinks:

The cut out size indicated is aligned with outside edge of the bowl top radius (see example below).



You should confirm with your client if the worksurface cutout is to be cut flush, inside or outside this suggested perimeter shape & size.

If you create the cutout smaller or larger than the indicated size then the fit of the accessories may be affected and should be physically checked.

## General:

All details are provided in good faith but do not include the tolerances of the material or manufacturing process.

We request that a test cutout is made in scrap timber and checked against the actual sink to be installed before committing to cutting the final worksurface.

Abode can not accept liability for problems or costs incurred by failure to follow this request.

Note: the dimensions on ceramic fireclay products are subject to wider tolerances due to the nature of this natural material and the firing process.

CAD cutout files can be downloaded from www.abodedesigns.co.uk

		·
Bowl details: (sizes in mm unless specified otherwise)		
Bowl 1 (typically main bowl):	Bowl 2 (typically 1/2 or 3/4 bowl):	Bowl 3:
Bowl 1 size L x W x D (mm): 350 x 420 x 180	Bowl 2 size L x W x D (mm): 150 x 350 x 105	Bowl 3 size L x W x D (mm): N/A x N/A x N/A
Bowl 1 construction: Moulded, 10.00mm	Bowl 2 construction: Moulded, 11.00mm	Bowl 3 construction: N/A, N/Amm
Bowl 1 floor radius (mm): 10	Bowl 2 floor radius (mm): 10	Bowl 3 floor radius (mm): N/A
Bowl 1 Wastehole diameter (mm): 90	Bowl 2 Wastehole diameter (mm): 90	Bowl 3 Wastehole diameter (mm): N/A
Bowl 1 overflow: None	Bowl 2 overflow: Cirlcular, 30mm diameter	Bowl 3 overflow: N/A
Bowl 1 texture: Matt textured	Bowl 2 texture: Matt textured	Bowl 3 texture: N/A

Bowl 2 apx. volume (litres): 3.60

21/12/2018 - This sheet is a summary of the product information full details are available on request, errors & omissions excepted, details are subject to change without prior notification. www.abodedesigns.co.uk

Bowl 3 texture: N/A Bowl 3 apx. volume (litres): N/A