

722/723SERIES BOX SECTION EXTENSION LADDERS

LIGHTWEIGHT & STRONG



Box section stiles for maximum strength and minimum ladder weight



IDEAL FOR JOBS AROUND THE WORK SITE



Heavy duty stabiliser bar for added safety



'D' shaped rungs for comfort and security



Available in double and triple styles



722/723SERIES **BOX SECTION EXTENSION LADDERS**









Nylon wheels for smooth ladder extension

- Box section stiles designed to ensure the ladder is lightweight but strong.
- Slip-resistant D rungs for comfort and security during use

SPECIFICATIONS Safe Working Product **Section** Open Weight Code x Rungs Length Length Height* **DOUBLE SECTION** 7221818[†] 2 x 6 1.85m (6') 2.95m (9'8") 6.80kg 3.60m (11'9") 7222418 2 x 8 2.42m (7'11") 4.08m (13'4") 4.69m (15'4") 9.66kg 7222918 2.98m (9'9") 4.92m (16'1") 5.50m (18') 2 x 10 11.96kg 7223518 3.54m (11'7") 6.04m (19'9") 6.58m (21'7") 2 x 12 15.34kg 4.10m (13'5") 7224118 2 x 14 7.16m (23'5") 7.66m (25'1") 17.65kg 4.38m (14'4") 7224418 2 x 15 7.73m (25'4") 8.20m (26'10") 21.35kg 7224918 2 x 17 4.94m (16'2") 8.84m (29') 9.29m (30'5") 23.55kg TRIPLE SECTION Compact ladders with a greater reach[^] 7231818 1.86m (6'1") 4.04m (13'3") 4.68m (15'4") 3 x 6 11.86kg 7232418 3 x 8 2.42m (7'11") 5.18m (17') 5.77m (18'11") 15.46kg 2.98m (9'9") 7232918 3 x 10 6.86m (22'6") 7.39m (24'3") 20.37kg 7233518 3.54m (11'7") 8.54m (28') 28.55kg 3 x 12 9.01m (29'6")

*Based on 1.75m (5'9") as the average reach height of a person. ^Compared to a double section ladder with the same closed length. *Stabiliser bar is not required or supplied with the double 1.85m model.

10.22m (33'6") 10.63m (34'10") 32.75kg



7234118

3 x 14

4.10m (13'5")

Thumb operated locking catches prevent the sections separating, both in use and when being transported or stored

Heavy duty wide stabiliser with slip-resistant feet for added safety[†]





Slip-resistant D rungs

Suitable for Professional & Non-professional use