N 70, Gas hob, 75 cm, Stainless steel T27DS59N0







Optional accessories

Z2480X0 Z32SE10X0 Z32SW11X0

The gas hob with a stainless-steel surface design and adjustable FlameSelect.

- $\sqrt{~}$ FlameSelect® Gain ultimate control of your flame.
- $\checkmark\,$ Pan Supports continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{}$ Wok Burner powerful cooking at up to 4 kW.
- $\sqrt{}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.
- $\checkmark\,$ Stainless steel surface elegant and sophisticated design.

Features

Technical Data

Product name/family : gas hob w integrated controls Construction type : Built-in Energy input : Gas Total number of positions that can be used at the same time : 5 Type of control setting devices : sword knobs Min. required niche size for installation (HxWxD) : 45 x 560-562 x 480-492 mm Width of the appliance : 750 mm Dimensions : 53 x 750 x 520 mm Dimensions of the packed product (HxWxD) : $145 \times 793 \times 597$ mm Net weight : 14.0 kg Gross weight : 15.5 kg Residual heat indicator : without Location of control panel : Hob front Basic surface material : Stainless steel Color of surface : Stainless steel Length of electrical supply cord : 100 cm Knob Material : Plastic Sealed Burners : No Type of pan support : Elongated cast iron pan support Power of heating element (kW) : 1 kW Power of 3rd heating element (kW) : 1.75 kW Power of 5th heating element (kW) : 3 kW Connection rating : 1 W Gas connection rating : 11500 $\,$ W $\,$ Fuse protection : 3 A Voltage : 220-240 V Frequency: 60; 50 Hz Main colour of product : Stainless steel Energy input : Gas Gas type : Nat gas H/E/(L) 20 (25) mbar Alternative gas type : Liquid gas G30,31 28-30/37mbar Plug type : no plug (electrical connection by electrician) Appliance Dimensions $(h \times w \times d)$ $(in) : + \times x$ Dimensions of the packed product : $5.70 \times 23.50 \times 31.22$ Net weight : 31.000 lbs Gross weight : 34.000 lbs Total number of positions that can be used at the same time : 5 Length of electrical supply cord : 100 cm Min. required niche size for installation (HxWxD) : $45 \times 560-562 \times$ 480-492 mm Dimensions : 53 x 750 x 520 mm Dimensions of the packed product (HxWxD) : 145 x 793 x 597 mm Net weight : 14.0 kg Gross weight : 15.5 kg



N 70, Gas hob, 75 cm, Stainless steel T27DS59N0



Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 4 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 750 x 520
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 11.5 KW

N 70, Gas hob, 75 cm, Stainless steel T27DS59N0



