

product information sheet

Trade Mark	Zanussi
Model	ZHC62653XA 942022098
Annual Energy Consumption (kWh/year)	100.2
Energy Efficiency class	C
Fluid Dynamic Efficiency	15.4
Fluid Dynamic Efficiency class	D
Lighting Efficiency (lux/W)	52.0634920634921
Lighting Efficiency class	A
Grease Filtering Efficiency	65.1
Grease Filtering Efficiency class	D
Air flow at minimum and maximum speed in normal use (m3/h)	295/600
Air flow at intensive or boost setting (m3/h)	-
Airborne acoustical A-weighted sound power emissions at minimum and maximum speed in normal use (dB(A))	52/69
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	-
Power consumption in standby mode (W)	0
Power consumption in off mode (W)	0.01

Product information according to Commission regulation (EU) No 66/2014

Attribute Name	Symbol	Value	Unit
Model Denomination		ZHC62653XA 942022098	
Annual Energy Consumption	AEC _{hood}	100.2	kwh/a
Time increase factor	f	1.4	
Fluid Dynamic Efficiency	FDE _{hood}	15.4	
Energy Efficiency Index	EEL _{hood}	82.4	
Measured air flow rate at best efficiency point	QBEP	341,0	m ³ /h
Measured air pressure at best efficiency point	PBEP	305	Pa
Maximum air flow	Q _{max}	600,0	m ³ /h
Measured electric power input at best efficiency point	WBEP	187,0	W
Nominal power of the lighting system	WL	6.3	W
Average illumination of the lighting system on the cooking surface	E _{middle}	328	lux
Measured power consumption in standby mode	P _s	0	W
Measured power consumption off mode	P _o	0.01	W
Sound power level	LWA	69	dB

EN 60704-2-13 - Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods

EN 50564 - Electrical and electronic household and office equipment. Measurement of low power consumption

Suggestions for a correct use in order to reduce the environmental impact:

- **Switch ON** the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is finished.
- **Increase the speed** only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations.
- **Replace the charcoal filter(s)** when necessary to maintain a good odour reduction efficiency.
- **Clean the grease filter(s)** when necessary to maintain a good grease filter efficiency.
- **Use the maximum diameter** of the ducting system indicated in this manual to optimize efficiency and minimize noise.