

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 20

SDS No.: 557650 V003.2

Revision: 01.12.2022

printing date: 01.07.2023

Replaces version from: 22.03.2022

Unibond Speed Transparent

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Unibond Speed Transparent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealant, silicone

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 1

H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

2-Octyl-2H-isothiazol-3-one

Signal word: Warning

Hazard statement: H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement: P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Evolves acetic acid during cure.

This mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

octamethylcyclotetrasiloxane 556-67-2	PBT/vPvB
Decamethylcyclopentasiloxane 541-02-6	PBT/vPvB
Dodecamethylcyclohexasiloxane 540-97-6	PBT/vPvB

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Acetic acid 64-19-7 200-580-7 01-2119475328-30	1- < 3 %	Flam. Liq. 3, H226 Skin Corr. 1A, H314 Met. Corr. 1, H290	Skin Corr. 1B; H314; C 25 - < 90 % Skin Corr. 1A; H314; C >= 90 % Eye Irrit. 2; H319; C 10 - < 25 % Skin Irrit. 2; H315; C 10 - < 25 % Met. Corr. ; H290; C >= 90 %	EU OEL
octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36	1- < 2,5 %	Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226	M chronic = 10	SVHC PBT/vPvB
Decamethylcyclopentasiloxane 541-02-6 208-764-9 01-2119511367-43	0,1-< 1 %			SVHC PBT/vPvB
Dodecamethylcyclohexasiloxane 540-97-6 208-762-8 01-2119517435-42	0,1-< 1 %	Aquatic Chronic 4, H413		SVHC PBT/vPvB
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	0,1-< 1 %	Carc. 2, Inhalation, H351		
2-Octyl-2H-isothiazol-3-one 26530-20-1 247-761-7 01-2120768921-45	0,025-< 0,25 % (0,25 %o-< 2,5 %o)	Acute Tox. 2, Inhalation, H330 Acute Tox. 3, Dermal, H311 Skin Corr. 1, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Acute Tox. 3, Oral, H301 Aquatic Chronic 1, H410 Eye Dam. 1, H318	Skin Sens. 1A; H317; C >= 0,0015 % ===== M acute = 100 M chronic = 100 ===== dermal:ATE = 311 mg/kg oral:ATE = 125 mg/kg inhalation:ATE = 0,27 mg/l;dust/mist	

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly sealed.

Store in a cool, dry place.

Temperatures between + 5 $^{\circ}$ C and + 25 $^{\circ}$ C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Joint sealant, silicone

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetic acid 64-19-7 [ACETIC ACID]	10	25	Time Weighted Average (TWA):	Indicative	ECTLV
Acetic acid 64-19-7 [ACETIC ACID]	20	50	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Acetic acid 64-19-7 [ACETIC ACID]	10	25	Time Weighted Average (TWA):		EH40 WEL
Acetic acid 64-19-7 [ACETIC ACID]	20	50	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetic acid 64-19-7 [ACETIC ACID]	10	25	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Acetic acid 64-19-7 [ACETIC ACID]	10	25	Time Weighted Average (TWA):	Indicative	ECTLV
Acetic acid 64-19-7 [ACETIC ACID]	20	50	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Acetic acid 64-19-7 [ACETIC ACID]	20	50	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL

$\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list		Environmental Exposure			Value			
	Compartment p	eriod		1	a.	I . 41		
acetic acid	aqua		mg/l 3,058 mg/l	ppm	mg/kg	others		
64-19-7	(freshwater)		5,056 mg/1					
acetic acid	aqua (marine		0,3058					
64-19-7	water)		mg/l					
acetic acid	aqua		30,58 mg/l					
64-19-7	(intermittent							
acetic acid	releases) sewage		85 mg/l					
64-19-7	treatment plant		65 Hig/1					
	(STP)							
acetic acid	sediment				11,36			
64-19-7	(freshwater)				mg/kg			
acetic acid	sediment				1,136			
64-19-7 acetic acid	(marine water) Soil		+		mg/kg 0,478			
64-19-7	5011				mg/kg			
Octamethylcyclotetrasiloxane	aqua		0,0015		mg/kg			
556-67-2	(freshwater)		mg/l					
Octamethylcyclotetrasiloxane	aqua (marine		0,00015					
556-67-2	water)		mg/l					
Octamethylcyclotetrasiloxane	sewage		10 mg/l					
556-67-2	treatment plant (STP)					1		
Octamethylcyclotetrasiloxane	(STP)		+		3 mg/kg	-		
556-67-2	(freshwater)				3 mg/kg			
Octamethylcyclotetrasiloxane	sediment				0,3 mg/kg			
556-67-2	(marine water)				, , ,			
Octamethylcyclotetrasiloxane	oral				41 mg/kg			
556-67-2	9 11				0.54			
Octamethylcyclotetrasiloxane 556-67-2	Soil				0,54 mg/kg			
Decamethylcyclopentasiloxane	aqua		0,0012					
541-02-6	(freshwater)		mg/l					
Decamethylcyclopentasiloxane 541-02-6	aqua (marine		0,00012					
Decamethylcyclopentasiloxane	water) sewage		mg/l 10 mg/l					
541-02-6	treatment plant		10 mg/i					
0.11 02 0	(STP)							
Decamethylcyclopentasiloxane	sediment				11 mg/kg			
541-02-6	(freshwater)							
Decamethylcyclopentasiloxane 541-02-6	Soil				2,54 mg/kg			
Decamethylcyclopentasiloxane	oral		1		16 mg/kg			
541-02-6								
Decamethylcyclopentasiloxane	sediment				1,1 mg/kg			
541-02-6	(marine water)				10.5 #			
Dodecamethylcyclohexasiloxane 540-97-6	sediment (freshwater)				13,5 mg/kg			
Dodecamethylcyclohexasiloxane	oral				66,7 mg/kg			
540-97-6	orar				00,7 mg/kg			
Dodecamethylcyclohexasiloxane	sediment		1		1,35 mg/kg			
540-97-6	(marine water)							
2-Octyl-2H-isothiazol-3-one	sediment				0,0475			
26530-20-1	(freshwater)				mg/kg	1		
2-Octyl-2H-isothiazol-3-one 26530-20-1	sediment (marine water)				0,00475 mg/kg	1		
2-Octyl-2H-isothiazol-3-one	aqua		0,0022		mg/Kg			
26530-20-1	(freshwater)		mg/l			1		
2-Octyl-2H-isothiazol-3-one	aqua		0,0012	<u> </u>				
26530-20-1	(intermittent		mg/l					
	releases)							
2-Octyl-2H-isothiazol-3-one	aqua (marine		0,00022					
26530-20-1	water)		mg/l	1	0.0002			
2-Octyl-2H-isothiazol-3-one 26530-20-1	Soil				0,0082 mg/kg			
20330-20-1				l .	mg/kg	I.		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
acetic acid 64-19-7	Workers	inhalation	Acute/short term exposure - local effects		25 mg/m3	
acetic acid 64-19-7	General population	inhalation	Acute/short term exposure - local		25 mg/m3	
acetic acid 64-19-7	Workers	inhalation	Long term exposure - local		25 mg/m3	
acetic acid	General	inhalation	effects Long term		25 mg/m3	
64-19-7	population	minatation	exposure - local effects		, and the second	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - systemic effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	Workers	inhalation	Long term exposure - local effects		73 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - systemic effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	inhalation	Long term exposure - local effects		13 mg/m3	
Octamethylcyclotetrasiloxane 556-67-2	General population	oral	Long term exposure - systemic effects		3,7 mg/kg	
Decamethylcyclopentasiloxane 541-02-6	Workers	inhalation	Long term exposure - systemic effects		97,3 mg/m3	
Decamethylcyclopentasiloxane 541-02-6	Workers	inhalation	Long term exposure - local effects		24,2 mg/m3	
Decamethylcyclopentasiloxane 541-02-6	General population	oral	Long term exposure - systemic effects		5 mg/kg	
Decamethylcyclopentasiloxane 541-02-6	General population	inhalation	Long term exposure - systemic effects		17,3 mg/m3	
Decamethylcyclopentasiloxane 541-02-6	General population	inhalation	Long term exposure - local effects		4,3 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	Workers	inhalation	Long term exposure - local effects		1,22 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	Workers	inhalation	Acute/short term exposure - local effects		6,1 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	General population	inhalation	Long term exposure - local effects		0,3 mg/m3	
Dodecamethylcyclohexasiloxane 540-97-6	General population	inhalation	Acute/short term exposure - local effects		1,5 mg/m3	
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m3	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m3	

Biological Exposure Indices: None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state solid Delivery form paste

Colour varied, according to coloration

Odor specific

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no

organic peroxide and does not decompose under foreseen

conditions of use

pH Not applicable, Product is non-soluble (in water).

Viscosity (kinematic) Not applicable, Product is a solid.

Solubility (qualitative) Insoluble

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable

Mixture < 0.5 Pa

Vapour pressure

(20 °C (68 °F))

Density 1,035 g/cm3 Density of pasty masses (immersion weighing

 $(20 \, ^{\circ}\text{C} \, (68 \, ^{\circ}\text{F}))$ method)

Relative vapour density:

Particle characteristics

Not applicable, Product is a solid.

Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

Evolves acetic acid during cure.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Acetic acid	LD50	3.310 mg/kg	rat	not specified
64-19-7				
octamethylcyclotetrasilox	LD50	> 4.800 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
ane				Toxicity)
556-67-2				
Decamethylcyclopentasilo	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
xane				Toxicity)
541-02-6				
Dodecamethylcyclohexasi	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
loxane				
540-97-6				
Titanium dioxide	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down
13463-67-7				Procedure)
2-Octyl-2H-isothiazol-3-	Acute	125 mg/kg		Expert judgement
one	toxicity			
26530-20-1	estimate			
	(ATE)			

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Acetic acid	LD50	> 2.000 mg/kg	not specified	not specified
64-19-7				
octamethylcyclotetrasilox	LD50	> 2.375 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
ane				Dermal Toxicity)
556-67-2				
Decamethylcyclopentasilo	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute
xane				Dermal Toxicity)
541-02-6				
Dodecamethylcyclohexasi	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
loxane				
540-97-6				
Titanium dioxide	LD50	> 10.000 mg/kg	rabbit	not specified
13463-67-7				
2-Octyl-2H-isothiazol-3-	Acute	311 mg/kg		Expert judgement
one	toxicity			
26530-20-1	estimate			
	(ATE)			

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Acetic acid	LC50	> 40 mg/l	vapour	4 h	rat	not specified
64-19-7						
octamethylcyclotetrasilox	LC50	36 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
ane						Inhalation Toxicity)
556-67-2						
Decamethylcyclopentasilo	LC50	8,67 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
xane						Inhalation Toxicity)
541-02-6						
Titanium dioxide	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
13463-67-7						
2-Octyl-2H-isothiazol-3-	Acute	0,27 mg/l	dust/mist	4 h		Expert judgement
one	toxicity					
26530-20-1	estimate					
	(ATE)					

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 404 (Acute
ane				Dermal Irritation / Corrosion)
556-67-2				
Decamethylcyclopentasilo	not irritating	24 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute
xane				Dermal Irritation / Corrosion)
541-02-6				
Dodecamethylcyclohexasi	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
loxane				
540-97-6				
Titanium dioxide	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
13463-67-7				

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
octamethylcyclotetrasilox	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
ane				Irritation / Corrosion)
556-67-2				
Decamethylcyclopentasilo	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
xane				Irritation / Corrosion)
541-02-6				
Dodecamethylcyclohexasi	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
loxane				
540-97-6				
Titanium dioxide	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
13463-67-7	_			

${\bf Respiratory\ or\ skin\ sensitization:}$

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
octamethylcyclotetrasilox ane 556-67-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Decamethylcyclopentasilo xane 541-02-6	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Dodecamethylcyclohexasi loxane 540-97-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-Octyl-2H-isothiazol-3- one 26530-20-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Acetic acid 64-19-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Acetic acid 64-19-7	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Acetic acid 64-19-7	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
octamethylcyclotetrasilox ane 556-67-2	negative	bacterial gene mutation assay	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
octamethylcyclotetrasilox ane 556-67-2	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
octamethylcyclotetrasilox ane 556-67-2	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Decamethylcyclopentasilo xane 541-02-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Decamethylcyclopentasilo xane 541-02-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Decamethylcyclopentasilo xane 541-02-6	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Dodecamethylcyclohexasi loxane 540-97-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dodecamethylcyclohexasi loxane 540-97-6	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Acetic acid 64-19-7	not carcinogenic	dermal	32 w daily	mouse	female	not specified
Decamethylcyclopentasilo xane 541-02-6	not carcinogenic	inhalation: vapour	2 y 6 h/d, 5 d/w	rat	male/female	EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity)
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
octamethylcyclotetrasilox ane 556-67-2	NOAEL P 300 ppm NOAEL F1 300 ppm	two- generation study	inhalation	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Decamethylcyclopentasilo xane 541-02-6	NOAEL P >= 2,496 mg/l NOAEL F1 >= 2,496 mg/l NOAEL F2 >= 2,496 mg/l	two- generation study	inhalation: vapour	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
Dodecamethylcyclohexasi loxane 540-97-6	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Acetic acid 64-19-7	NOAEL 290 mg/kg	oral: feed	8 w daily	rat	not specified
octamethylcyclotetrasilox ane 556-67-2	LOAEL 35 ppm	inhalation	6 h nose only inhalation 5 days/week for 13 weeks	rat	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
octamethylcyclotetrasilox ane 556-67-2	NOAEL 960 mg/kg	dermal	3 w 5 d/w	rabbit	equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Decamethylcyclopentasilo xane 541-02-6	NOAEL >= 1.000 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Decamethylcyclopentasilo xane 541-02-6	NOAEL >= 2,42 mg/l	inhalation: vapour	2 y 6 h/d, 5 d/w	rat	equivalent or similar to OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Decamethylcyclopentasilo xane 541-02-6	NOAEL >= 1.600 mg/kg	oral: gavage	28 d 6 h/d, 7 d/w	rat	equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Dodecamethylcyclohexasi loxane 540-97-6	NOAEL 1.000 mg/kg	oral: gavage	29 d daily, 7 d/w	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		•	•	
Acetic acid	LC50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
64-19-7					Acute Toxicity Test)
octamethylcyclotetrasiloxane	NOEC	0,0044 mg/l	93 d	Salmo gairdneri (new name:	EPA OPPTS 797.1600 (Fish
556-67-2				Oncorhynchus mykiss)	Early Life Stage Toxicity
					Test)
octamethylcyclotetrasiloxane	LC50	Toxicity > Water	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish
556-67-2		solubility			Acute Toxicity Test)
Decamethylcyclopentasiloxan	LC50	Toxicity > Water	96 h	Leuciscus idus	OECD Guideline 204 (Fish,
e		solubility			Prolonged Toxicity Test:
541-02-6					14-day Study)
Decamethylcyclopentasiloxan	NOEC	Toxicity > Water	90 d	Oncorhynchus mykiss	OECD Guideline 210 (fish
e		solubility			early lite stage toxicity test)
541-02-6					
Dodecamethylcyclohexasiloxa	NOEC	Toxicity > Water	90 d	Oncorhynchus mykiss	OECD Guideline 210 (fish
ne		solubility			early lite stage toxicity test)
540-97-6					
Titanium dioxide	LC50	Toxicity > Water	48 h	Leuciscus idus	OECD Guideline 203 (Fish,
13463-67-7		solubility			Acute Toxicity Test)
2-Octyl-2H-isothiazol-3-one	LC50	0,036 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
26530-20-1					Acute Toxicity Test)
2-Octyl-2H-isothiazol-3-one	NOEC	0,022 mg/l	21 d	Oncorhynchus mykiss	OECD Guideline 210 (fish
26530-20-1					early lite stage toxicity test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Acetic acid	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202
64-19-7					(Daphnia sp. Acute
					Immobilisation Test)
octamethylcyclotetrasiloxane	EC50	Toxicity > Water	48 h	Daphnia magna	EPA OTS 797.1300
556-67-2		solubility			(Aquatic Invertebrate Acute
					Toxicity Test, Freshwater
					Daphnids)
Decamethylcyclopentasiloxan	EC50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202
e		solubility			(Daphnia sp. Acute
541-02-6					Immobilisation Test)
Titanium dioxide	EC50	Toxicity > Water	48 h	Daphnia magna	OECD Guideline 202
13463-67-7		solubility			(Daphnia sp. Acute
					Immobilisation Test)
2-Octyl-2H-isothiazol-3-one	EC50	0,42 mg/l	48 h	Daphnia magna	OECD Guideline 202
26530-20-1					(Daphnia sp. Acute
					Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
octamethylcyclotetrasiloxane	NOEC	7.9 µg/l	21 d	Daphnia magna	EPA OTS 797.1330
556-67-2					(Daphnid Chronic Toxicity
					Test)
Decamethylcyclopentasiloxan	NOEC	Toxicity > Water	21 d	Daphnia magna	OECD 211 (Daphnia
e		solubility			magna, Reproduction Test)
541-02-6					
Dodecamethylcyclohexasiloxa	NOEC	Toxicity > Water	21 d	Daphnia magna	OECD 211 (Daphnia
ne		solubility			magna, Reproduction Test)

540-97-6					
Titanium dioxide	NOEC	Toxicity > Water	21 d	Daphnia magna	OECD Guideline 202
13463-67-7		solubility			(Daphnia sp. Chronic
					Immobilisation Test)
2-Octyl-2H-isothiazol-3-one	NOEC	0,0016 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
26530-20-1	1				magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Acetic acid 64-19-7	EC50	> 1.000 mg/l	72 h	Skeletonema costatum	ISO 10253:2006 (Marine algal growth inhibition test)
Acetic acid 64-19-7	NOEC	1.000 mg/l	72 h	Skeletonema costatum	ISO 10253:2006 (Marine algal growth inhibition test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
octamethylcyclotetrasiloxane 556-67-2	EC10	0,022 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Decamethylcyclopentasiloxan e 541-02-6	NOEC	Toxicity > Water solubility	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Decamethylcyclopentasiloxan e 541-02-6	EC50	Toxicity > Water solubility	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dodecamethylcyclohexasiloxa ne 540-97-6	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC50	0,00129 mg/l	48 h	Navicula pelliculosa	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC10	0,000224 mg/l	48 h	Navicula pelliculosa	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Acetic acid 64-19-7	NOEC	1.150 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
octamethylcyclotetrasiloxane 556-67-2	EC50	Toxicity > Water solubility	3 h	activated sludge	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Decamethylcyclopentasiloxan e 541-02-6	EC50	> 2.000 mg/l	3 h	activated sludge, domestic	EU Method C.11 (Biodegradation: Activated Sludge Respiration Inhibition Test)
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Acetic acid	readily biodegradable	aerobic	89 - 99 %	30 d	EU Method C.4-E (Determination
64-19-7					of the "Ready"
					BiodegradabilityClosed Bottle
					Test)
octamethylcyclotetrasiloxane	not readily biodegradable.	aerobic	3,7 %	29 d	OECD Guideline 310 (Ready
556-67-2					BiodegradabilityCO2 in Sealed
					Vessels (Headspace Test)
Decamethylcyclopentasiloxan	not readily biodegradable.	aerobic	0,14 %	28 d	OECD Guideline 310 (Ready
e					BiodegradabilityCO2 in Sealed
541-02-6					Vessels (Headspace Test)
Dodecamethylcyclohexasiloxa	not readily biodegradable.	aerobic	4,47 %	28 d	OECD Guideline 310 (Ready
ne					BiodegradabilityCO2 in Sealed
540-97-6					Vessels (Headspace Test)
2-Octyl-2H-isothiazol-3-one	not readily biodegradable.	aerobic	35 %	21 d	OECD Guideline 301 D (Ready
26530-20-1					Biodegradability: Closed Bottle
					Test)

12.3. Bioaccumulative potential

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)		_		
octamethylcyclotetrasiloxane	12.400	28 d		Pimephales	EPA OTS 797.1520 (Fish
556-67-2				promelas	Bioconcentration Test-Rainbow
					Trout)
Decamethylcyclopentasiloxan	7.060	35 d		Pimephales	OECD Guideline 305
e				promelas	(Bioconcentration: Flow-through
541-02-6					Fish Test)
Dodecamethylcyclohexasiloxa	1.160	49 d		Pimephales	OECD Guideline 305
ne				promelas	(Bioconcentration: Flow-through
540-97-6				=	Fish Test)

12.4. Mobility in soil

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
Acetic acid	-0,17	25 °C	other guideline:
64-19-7			
octamethylcyclotetrasiloxane	6,98	21,7 °C	other guideline:
556-67-2			
Decamethylcyclopentasiloxan	8,07	24,6 °C	other guideline:
e			
541-02-6			
Dodecamethylcyclohexasiloxa	8,87	23,6 °C	other guideline:
ne			
540-97-6			
2-Octyl-2H-isothiazol-3-one	2,9		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake
26530-20-1			Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Acetic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
64-19-7	Bioaccumulative (vPvB) criteria.
octamethylcyclotetrasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
556-67-2	Bioaccumulative (vPvB) criteria.
Decamethylcyclopentasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
541-02-6	Bioaccumulative (vPvB) criteria.
Dodecamethylcyclohexasiloxane	Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
540-97-6	Bioaccumulative (vPvB) criteria.
Titanium dioxide	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not
13463-67-7	be conducted for inorganic substances.
2-Octyl-2H-isothiazol-3-one	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
26530-20-1	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080410

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3077
RID	3077
ADN	3077
IMDG	3077
IATA	3077

14.2. UN proper shipping name

	ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.	.O.S.
--	-----	--	-------

(octamethylcyclotetrasiloxane,2-Octyl-2H-isothiazol-3-one)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(octamethylcyclotetrasiloxane,2-Octyl-2H-isothiazol-3-one)

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(octamethylcyclotetrasiloxane,2-Octyl-2H-isothiazol-3-one) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, (octamethylcyclotetrasiloxane,2-Octyl-2H-isothiazol-3-one)

IATA Environmentally hazardous substance, solid, n.o.s. (octamethylcyclotetrasiloxane,2-

Octyl-2H-isothiazol-3-one)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR not applicable

	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

No information available:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H351 Suspected of causing cancer.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer.

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.