

N 50, Canopy cooker hood, 52 cm, Stainless steel  
D55MH56NOB



C



Canopy hood: designed to fit neatly under an overhead unit or cabinet. They're discreet and effectively use valuable space.

- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ High extraction rate: Ensures a clear view while cooking thanks to efficient motor technology as either a ducted or recirculating solution.

#### Features

##### Technical Data

Typology : Traditional  
 Approval certificates : Australia Standards, CE, VDE  
 Length of electrical supply cord (cm) : 150  
 Required niche size for installation (HxWxD) : 418mm x 496.0mm x 264mm  
 Minimum distance above an electric hob : 500  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 8.964  
 Type of control : Electronic  
 Maximum output air extraction (m<sup>3</sup>/h) : 575  
 Boost position output recirculating (m<sup>3</sup>/h) : 290.0  
 Boost position air extraction (m<sup>3</sup>/h) : 650  
 Number of lights (Stck) : 2  
 Noise level (dB(A) re 1 pW) : 67  
 Diameter of air outlet (mm) : 120 / 150  
 Grease filter material : Washable aluminium  
 EAN code : 4242004187745  
 Connection rating (W) : 277  
 Current (A) : 3  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50  
 Plug type : GB plug  
 Installation type : Built-in

#### Optional accessories

Z5135X1	Standard odor filter (replacement)
Z5135X3	Standard recirculation kit
Z511TD1X1	Long Life recirculation kit external
Z511TP0X0	Long Life odor filter (replacement)
Z511XB1X6	Clean Air Plus odor filter (replacement)
Z511XC1X6	Clean Air Plus recirc. kit external
Z54TR00X0	gleanAir active carbon filter
Z54TR60X3	CleanAir Recirculation Kit



4 242004 187745

# N 50, Canopy cooker hood, 52 cm, Stainless steel

## D55MH56NOB

### Features

#### Features

- LED display
- 2 x 1W LED lights
- 1 metal grease filter cassette
- Stainless steel filter cover, metal grease filter
- 3 speeds plus intensive
- Automatic intensive revert (6mins)
- Rim ventilation

#### Design

- Stainless steel
- Canopy hood
- 
- Soft touch control
- Electronic controls

#### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Twin channel high performance fan motor
- In recirculation operation chimless use possible
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 575 m<sup>3</sup>/h  
Intensive 650 m<sup>3</sup>/h
- Power rating: 277 W
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 67 dB (A) re 1pW
- Noise max. Normal Level: 67 dB\*
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.5 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 418-418 x 520 x 300 mm
- Dimensions recirculating (HxWxD): 418-418 x 520 x 300 mm
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: D\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*
- Average Energy Consumption: 107.8 kWh/year\*

#### Optional accessories

- Recirculating kit Z5135X1
- Max. extraction rate: 650 m<sup>3</sup>/h
- Dimensions (HxWxD): 418 x 520 x 300 mm

\* In accordance with the EU-Regulation No 65/2014