product information sheet

| Trade Mark | AEG | |
|---|---------------------|--|
| Model | DVK6981HB 942051420 | |
| Annual Energy Consumption (kWh/year) | 40.3 | |
| Energy Efficiency class | A+ | |
| Fluid Dynamic Efficiency | 36 | |
| Fluid Dynamic Efficiency class | A | |
| Lighting Efficiency (lux/W) | 51.52777777778 | |
| Lighting Efficiency class | A | |
| Grease Filtering Efficiency | 65.1 | |
| Grease Filtering Efficiency class | D | |
| Air flow at minimum and maximum speed in normal use (m3/h) | 270/500 | |
| Air flow at intensive or boost setting (m3/h) | 750 | |
| Airborne acoustical A-weighted sound power emissions at minimum and maximum speed in normal use (dB(A)) | 43/54 | |
| Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A)) | 66 | |
| Power consumption in standby mode (W) | 0 | |
| Power consumption in off mode (W) | 0.49 | |

Product information according to Commission regulation (EU) No 66/2014

| Symbol | Value | Unit |
|---------|---|--|
| | DVK6981HB 942051420 | |
| AEChood | 40.3 | kwh/a |
| f | 0.7 | |
| FDEhood | 36,0 | |
| EEIhood | 42.6 | |
| Qbep | 390.4 | m3/h |
| Рвер | 455 | Ра |
| Qmax | 750,0 | m3/h |
| / WBEP | 137.1 | W |
| WL | 7.2 | W |
| Emiddle | 371 | lux |
| e Ps | 0 | W |
| Po | 0.49 | W |
| LWA | 54 | dB |
| | AEChood f FDEhood EEIhood QBEP PBEP Qmax WBEP WL Emiddle Ps Po | Provide Provide AEChood 40.3 AEChood 40.3 f 0.7 FDEhood 36,0 EEIhood 42.6 QBEP 390.4 PBEP 455 Qmax 750,0 WL 7.2 Emiddle 371 Ps 0 Po 0.49 |

EN 60704-2-13 - Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods

EN 50564 - Electrical and electronic household and office equipment. Measurement of low power consumption

Suggestions for a correct use in order to reduce the environmental impact:

• Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is fi nished.

• Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations.

• Replace the charcoal filter(s) when necessary to maintain a good odour reduction effi ciency.

• Clean the grease filter(s) when necessary to maintain a good grease filter efficiency.

• Use the maximum diameter of the ducting system indicated in this manual to optimize effi ciency and minimize noise.