ZGGN755K





Fast, energy-efficient cooking

Get quick, accurate cooking results with the Series 60 SpeedBurner gas hob. The burners are designed to directly heat the base of pots and pans. Saving up to 20% energy usage for boiling, frying or simmering.

Product Benefits & Features

SpeedBurner, for quicker cooking

Get cooking up to 20% faster with the our SpeedBurners. Unlike conventional gas hobs, the SpeedBurners' flames send heat directly to the base of pots and pans, for quick heating and energy saving, too. Perfect for boiling, simmering, searing and frying.

Turn up the heat, with Powerful Wok

When you need an extra burst of heat, the Powerful Wok burner is on hand. Whether you're searing steaks or prawns, the higher temperature will help achieve tender, tasty results.

- Hob type: Gas on Glass
- Rotary knob controls
- Controls position: Front Middle
- Left front zone: Mariane, Semi Rapid Burner, 2000W/80mm
- Left rear zone: Mariane, Semi Rapid Burner, 2000W/80mm
- Middle front zone: No, 0W/0mm
- Middle rear zone: No, 0W/0mm
- Right front zone: Auxiliary Burner, Mariane, 1000W/65mm
- Right rear zone: Mariane, Semi Rapid Burner, 2000W/80mm
- · Gas conversion kit
- · Main colour: Black

Cast Iron Grids, for the professional look

Strong Cast Iron Grids will give your hob a professional finish. The sturdy support will keep pots and pans flat, and their durable build will last for years.

Perfect Flame Regulation, for perfect temperature

The hob's responsive gas taps feature Perfect Flame Regulation. Giving you complete control over the temperature you want to cook your favourite dishes with.





Product Specification

1 Todaot opcomodion	
Product Installation	Built_In
Product Typology	Gas_Hob
Product Classification	Core
Installation	Independent
Size	75
Hob type	Gas On Glass
Design family	Yellow
Main colour	Black
Control Panel material	Glass
Frame type	No
Knobs colour	Black
Top Control Place	Front Middle
Type of controls	Knobs
Control function	No
Other comments categorisation	NO Led
Width mm	740
Depth mm	510
Built in height mm	45
Width cutting	560
Depth cutting	480
Radius cutting	10
Fastening	Fixing Clamps
Gas original	G20 (2H) 20 mbar
Gas replacement 2	G30/G31 (3+) 28-30/37 mbar, With Additional Injectors

Gas replacement 3	No
Gas category	II2H3+
Frequency	50-60
Voltage	220-240
Required fuse (A)	13
Cord length external	1.1